



QUICK CONNECT COUPLINGS

Full Line Catalog



Tuthill Coupling Group / **HANSEN™**
QUICK SEAL®
COUPLEURS GROMELLE™

Catalog No. 00-1


*Tuthill Coupling
Group* / **HANSEN™
QUICK SEAL®
COUPLEURS GROMELLE™**



Berea, Ohio, USA



Annemasse, Haute-Savoie, France






A Letter from the President

The success of **Tuthill Coupling Group** has been built upon a commitment to listen to and understand our customers, from the invention of the Hansen Coupling in 1915 to the present. Achieving clarity of our customers' values allows us to provide the best coupling solutions, while staying true to our heritage of the highest quality products and personalized service.

Even more, our passion for Continuous Improvement challenges us to never be satisfied and constantly strive to change for the better. Our Improvement Engine is powered by our employees; making a stand for their greatness and calling them forth to their potential is the heart of our Conscious Company philosophy. We diligently invest in our future through Radical Leadership training for every employee throughout the organization. This investment results in quicker and more creative solutions within our business processes and for our customers. While Tuthill's Vision is to build a great company, we also want our employees to have a seismic impact on our world.

Our personal approach of having employees available to gladly serve our customers and answer any question still remains a key part of our culture. Thank you for trusting us with your business.

Sincerely,



Brett Jaffe
President, Tuthill Coupling Group

Tuthill Coupling Group | **HANSEN™**
QUICK SEAL®
COUPLEURS GROMELLE™

1000 West Bagley Road, P.O. Box 805
Berea, Ohio USA 44017-0805
Tel 440 826-1115 Fax 440 826-1105
www.tuthill.com

Table of Contents

	Page Number
<i>How to Build a Socket Part No.</i>	5
<i>About Us</i>	6
<i>Markets & Industries Reference</i>	7
<i>QUICK SEAL®</i>	8-9

One-Way Shutoff Couplings

<i>Selection Chart</i>	11
<i>Interchange Chart</i>	12
<i>CC Series</i>	13
<i>1000/400/500 Series</i>	14-17
<i>3000/4000/5000/6000 Series</i>	18-22
<i>P-30 & P-40 Series</i>	23
<i>Auto-Flo 23 & 24 Series</i>	24-26
<i>Safeline Series</i>	27
<i>180 & 280 Series</i>	28-29
<i>100 Series</i>	30-31
<i>600 & 700 Series</i>	32-34
<i>2RL & 3RL Series</i>	35-37
<i>Full Bore Series</i>	38-39
<i>210 & 310 Series</i>	40-41
<i>MS Series</i>	42-43

Two-Way Shutoff Couplings

<i>Selection Chart</i>	45
<i>HK 1-8 Series</i>	46-48
<i>HK 10, 12, 20 Series</i>	49-51
<i>HKFR Series</i>	52
<i>HA 15000 Series</i>	53-54
<i>FF Flat Face Series</i>	55-57
<i>96 Series</i>	58
<i>UP10 Series</i>	59-60
<i>WA 56000 & HP3 Series</i>	61
<i>2-HKIG & 2-HKIL</i>	62-63
<i>DB Series</i>	64

Page Number

Straight Through Couplings

<i>Selection Chart</i>	66
<i>ST Series</i>	67-69
<i>P2-ST & P3-ST Series</i>	70-71
<i>FLO-TEMP Series</i>	72

Gas Couplings

<i>Gas-Mate Series</i>	74
------------------------	-----------

Accessories

<i>Flow Sensor</i>	76
<i>Check Valves</i>	77
<i>Flex-Air</i>	78-79
<i>Fittings</i>	80-81
<i>Elastomer Selection Guide</i>	82

Index

<i>Alphanumeric Parts Index</i>	83-86
---------------------------------	--------------

How To Build A Socket Part Number

Notes:

- 1) Some part numbers may be subject to minimum order quantities.
- 2) Options shown are not available for all parts and may only be available by quotation. Consult your local distributor.

EXAMPLE:

4HP26 – BV – SL – 143 – OC

Standard part number
from table listing.

Valve Material:
BV – Brass Valve
LLV – 303 Stainless Steel

SL – Sleeve Lock

OC – Oxygen Clean

Seal Material*:
138 – Silicone
143 – Fluorocarbon
192 – EPDM
115 – PTFE
118 – Neoprene

* See page 82 for full list, description and suggested uses for seal materials.

CLEANING AND LUBRICATION PROCESS FOR GASEOUS OR LIQUID OXYGEN SERVICE

<<< Part numbers cleaned for oxygen service should be denoted with an "OC" suffix >>>

This cleaning process applies to new and unused brass or stainless steel parts for 3000 psig (207 Bar) max gaseous or liquid oxygen service or aluminum parts for 150 psig (10 Bar) max gaseous or liquid oxygen service. It is based upon the recommended practices in ASTM G93 and CGA G-4.1 for cleaning, drying, inspection and packaging of materials and equipment intended for service in an oxygen-enriched environment. A copy of Tuthill Coupling Group's cleaning procedure for oxygen service may be obtained by contacting www.tuthill.com/oxygen-clean.

⚠ WARNING

Over-pressurization could result in a sudden failure of the coupling causing severe bodily injury or death. Be sure to select the proper coupling for your application and use it only within the specified service pressure range.

⚠ WARNING

Couplings do wear out. In order to avoid severe bodily injury or death, couplings must be routinely checked for condition and replaced if necessary.

The Building Blocks of a Successful Partnership... with TUTHILL COUPLING GROUP



Customer Support

Catalog

- New, easy-to-read format
- New products
- Same comprehensive technical data

Website

- Fully searchable online catalog
- Product data sheets for download
- Market information
- Application Resource Tool (ART)

Training

- Product demonstration videos
- General coupling information
- Online Distributor Training Center

Customer Service

- Dedicated Customer Service Representatives available Monday-Friday 8:00-5:00 EST

Technical Support

- Engineering Representatives answer technical product questions Monday-Friday 8:00-5:00 EST

Product Innovation


Tuthill is leading the industry with our latest development, the CC Series pneumatic coupling.

Exciting features include: >>>
Check out the CC Series on page 35 for more info!

- Safety
- High Flow
- Durability
- Flexibility
- Lightweight

Expanded Product Offering

Tuthill Coupling Group is proud to offer a full line of leak testing and filling connectors! Check out information on our new **QUICK SEAL®** brand of products on the next page or see our full **QUICK SEAL** catalog!



Dedicated Employees

Our staff is dedicated to providing top of the line service to our customers everyday. Tuthill is proud to boast a staff with a combined 1,500+ years of service! That's an average of 12+ years per employee!

Marketing Reference Guide



Aerospace



Agriculture



Carpet
Cleaning



Chemical



Construction



Defense



Energy
and Power



Food and
Beverage



General
Pneumatics



Heating/Cooling/
Refrigeration



Injection
Molding



Marine



Medical



Oil and Gas



Mining



Petrochemical



Pharmaceutical



Recreation
and
Entertainment



Transportation



Water and
Wastewater
Treatment

Tuthill Coupling Group is Proud to Hold the Following Certifications:

ISO 9001:2000



Certificate No. 006888

CRN CANADIAN REGISTRATION NUMBER

Tuthill Coupling Group is CRN certified for all non-nuclear applications in all of the Canadian provinces. Ontario Regulation 220/01 for Boilers and Pressure Vessels in Paragraph 4, states requirements for Design Registration. Tuthill Coupling Group is the only coupling manufacturer that has achieved this registration. Our CRN is OA11599.5C and our approval is valid until 2017.

PROUD MEMBERS OF:



NFPA
Solutions through
motion technology



QUICK SEAL®

APPLICATIONS:

- PUMPS
- VALVES
- CASTINGS
- AIR CONDITIONING
- REFRIGERATION EQUIPMENT
- BEVERAGE DISPENSERS
- ICE MACHINES
- DRINKING FOUNTAINS
- WATER HEATERS
- FURNACES
- GAS STOVES
- GAS TANKS
- ENGINE BLOCKS
- MUFFLERS
- OIL SYSTEMS

FOR MORE DETAILS, CHECK OUT OUR
FULL LINE QUICK SEAL® CATALOG.
REQUEST CATALOG NUMBER QS-1207.



Leak Testing And Filling Connectors

QUICK SEAL[®] products

are used for connecting vacuum and pressure lines to tubing for pressure testing, vacuum dehydrating, charging and other applications requiring a quick, leak-free connection. Since 1962, QUICK SEAL has been an industry leader in providing leak test plugs and filling connectors that have been recognized for their superior quality.

Basic Sealing Methods



End Seal - Seals on End of Tube

- Inexpensive general purpose leak testing.
- For air, water, refrigerant.




Inside Diameter (I.D.) Seal

- Works well with all test media including helium, air, and most refrigerants and gases.
- Seals in area where tube manufacturers hold their closest tolerances - assures a consistent tight fit. (except SBP)
- Seals on smooth area - provides longer seal life. (except SBP)
- I.D. sealing usually done with inexpensive, easy to replace o-rings.



Outside Diameter (O.D.) Seal

- Full flow, minimal restrictions.
- Seals on smooth surface.
- Seals have minimal exposure to test medium, last longer in hazardous duty.
- Seals are larger and longer for better sealing.



PR tube connectors in use for refrigeration testing and filling.



Expanding seal filling connector shown servicing an automotive radiator.



E self-sealing filling connector used in a pressure vessel.



CV and XCV are used for gas appliances.



ONE-WAY



Contents and Selector Chart




Coupling Series	Page	Coupling Style			Interchange				Body Size					Body Material				Locking Mechanism				Options			
		MANUAL CONNECT	PUSH-TO-CONNECT	SAFETY COUPLING	INDUSTRIAL INTERCHANGE	ARO 210/310	TRU-FLATE	CEJN 320/RECTUS 25	HANSEN UNIQUE DESIGN	1/8 INCH	1/4 INCH	3/8 INCH	1/2 INCH	3/4 INCH	ALUMINUM	BRASS	STEEL (Zinc/chromate Finish)	STAINLESS STEEL	PLASTIC (Acetal)	BALL LOCK	PIN LOCK	RING LOCK	PLASTIC FINGERS	SLEEVE LOCK	SEAL MATERIALS (Various)
CC	13		●	●	●	●	●	●			●					●	◆						▼		
1000	15	●			●						●				●		●		●				●	●	●
400	16	●			●		●				●				●				●				●	●	●
500	17	●			●							●			●				●				●	●	
3000	19		●		●						●				●					●			●	●	●
4000	20		●		●							●			●					●			●	●	●
5000	21		●		●								●		●					●			●	●	
6000	22		●		●									●	●					●			●	●	
P-30	23		●		●						●							●				●			
P-40	23		●		●							●						●				●			
Auto-Flo 23	25		●	●	●	●	●				●				●				●						
Auto-Flo 24	26		●	●				●			●				●				●						
Safeline	27		●	●	●	●					●			●		●			●						
180/280	29	●							●	●					●				●					●	
100	31	●							●		●				●				●					●	●
600/700	33/34	●							●		●				●				●				●		●
2-RL	36		●						●		●					●					●		▼	●	●
3-RL	37		●						●			●				●					●		▼	●	●
Full-Bore	39		●	●	●	●					●	●				●			●				▼		
210	41		●			●					●					●				●					
310	41		●			●						●				●				●					
MS	43		●		●						●					●				●					

▼ Sleeve lock is standard


◆ Polymer Sleeves

Interchange Chart

The plug profiles shown below are actual size. This chart can be used to help select Tuthill one-way couplings. The bottom row of this chart shows unique Tuthill plug designs.



Industrial Interchange




ARO 210

Tru-Flate

Tru-Flate

Auto-Flo 24

180/280



100

600

700

2RL

3RL



2CC Series

24CC Series

The CC Series provides unrestricted air flow, safety, efficiency and extreme durability all in one pneumatic coupling.

FEATURES

- Two-sleeve activation for safety
- Exceeds stringent cycle testing requirements without leakage
- Withstands 4,500 pounds of external force without cracking
- The safe choice for your employees due to safety venting that prevents hose whip
- Helps prevent scratches on finished product surfaces
- Does not noticeably increase the weight of the tool when attached, which helps prevent user strain and fatigue, increasing workplace productivity
- The socket can accept multiple plug configurations, making it extremely flexible

APPLICATIONS & MARKETS

- Air Tools
- General Pneumatics

Rated Pressure

Part Number	Body Size	Thread Size	Rated Air Flow	Interchanges
2CC25F	1/4"	1/4" Female NPT	34 SCFM	Industrial, ARO 210, Tru-Flate
2CC37F	1/4"	3/8" Female NPT	34 SCFM	Industrial, ARO 210, Tru-Flate
24CC25F	1/4"	1/4" Female NPT	53 SCFM	CEJN 320, Rectus 25
24CC37F	1/4"	3/8" Female NPT	53 SCFM	CEJN 320, Rectus 25
24CC25FBS	1/4"	1/4" Female BSPP	53 SCFM	CEJN 320, Rectus 25

Interchangeability

2CC	24CC
Industrial	CEJN 320
ARO 210	RECTUS 25
Tru-Flate	

Materials

- Non-marring polymer sleeves and rounded ends
- Nickel plated brass and crush resistant polymer


1/4" nominal (6.35 mm)

Rated Pressure

Series	PSI	BAR
2CC	250	17
24CC	250	17

Flow Capacity

PRESSURE DROP VS. AIR FLOW
(100 psig inlet pressure)



*scfm: Standard Cubic Feet per Minute

CHECK OUT OUR VIDEO DEMONSTRATING THE DURABILITY OF THE CC COUPLING. VISIT WWW.TUTHILL.COM.

SERIES 1000/400/500




Industrial Interchange Ball Lock quick connect couplings are designed for compressed air, gases, and liquids. Body sizes are 1/4", 3/8" and 1/2".

FEATURES

- Ball lock
- Manual operation
- Rugged, reliable
- All sizes accept US Industrial Interchange; 1/4" and 1/2" also accept ISO 1650 Series B and A-A-59439 (former MIL-C-4109) plugs
- Optional sleeve lock prevents accidental disconnection
- Optional seal and valve materials available
- Series 1000 socket available in stainless steel
- Series 400 sockets accept Tru-Flate Interchange plugs and Industrial Interchange plugs

APPLICATIONS & MARKETS

- General Pneumatics
- Industrial Plants
- Construction
- Fluid Transfer



Shown with optional sleeve lock

Interchangeability

All Sizes	1/4" & 1/2"	400 Series
US Industrial Interchange	ISO 6150 Series B A-A-59439 (former MIL-C-4109)	Tru-Flate

Materials

Socket:

- Brass Body
- Nickel Plated Steel Sleeve
- Zinc Plated Steel Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Springs
- Stainless Steel Locking Balls

Plug:

- Zinc Plated Case-Hardened Steel
- Brass
- Stainless Steel (1/4" size)

1/4" to 1/2" nominal
(6.35 mm to 12.7 mm)

-40° F to 250° F
-40° C to 120° C

Rated Pressure

Series	Size	PSI	BAR
1000	1/4"	2,000	138
400	3/8"	1,000	69
500	1/2"	500	35


NOTE:

Series 400 operating pressure is 150 psi when connected to Tru-Flate Interchange plug.

Flow Capacity

Series	†Ac
1000	24
400	45
500	72


† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.



SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
Brass				
900	1/8-27 NPTF	1.97	1.00	0.69
1100	1/4-18 NPTF	2.16	1.00	0.69
1300	3/8-18 NPTF	2.12	1.00	0.69
1000-63*	5/8-18	2.19	1.00	0.69
Stainless				
LL-1100	1/4-18 NPTF	2.16	1.00	0.69

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
Steel				
10	1/4-18 NPTF	1.75	0.65	0.56
10C§	1/4-18 NPTF	1.75	0.65	0.56
10G†	1/4-18 NPTF	1.75	0.65	0.56
12	1/8-27 NPTF	1.59	0.58	0.50
12G†	1/8-27 NPTF	2.38	0.77	0.69
14	3/8-18 NPTF	1.75	0.79	0.69
14G†	3/8-18 NPTF	2.53	0.77	0.69
Brass				
B-10	1/4-18 NPTF	1.75	0.64	0.56
Stainless				
LL-10	1/4-18 NPTF	1.75	0.65	0.56

Part No.	Thread Size	Dimensions		
		A	B	HEX
Brass				
800	1/8-27 NPTF	1.86	1.00	0.69
1000	1/4-18 NPTF	2.08	1.00	0.69
1200	3/8-18 NPTF	2.16	1.00	0.75
Stainless				
LL-1000	1/4-18 NPTF	2.08	1.00	0.69


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
Steel				
11	1/4-18 NPTF	1.63	0.79	0.69
11G†	1/4-18 NPTF	2.44	0.77	0.69
13	1/8-27 NPTF	1.47	0.65	0.56
15	3/8-18 NPTF	1.69	0.94	0.81
15G†	3/8-18 NPTF	2.50	0.84	0.75
Brass				
11B	1/4-18 NPTF	1.63	0.78	0.69
Stainless				
LL-11	1/4-18 NPTF	1.63	0.79	0.69

Part No.	Hose I.D.	Dimensions	
		A	B
Brass			
1600	1/4"	2.60	1.00
1600P‡	1/4"	2.37	1.00
1700	3/8"	2.60	1.00
1700P‡	3/8"	2.44	1.00
1800	5/16"	2.60	1.00


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
Steel			
16	1/4"	2.22	0.50
16G†	1/4"	2.97	0.77
16P‡	1/4"	2.00	0.69
16PG†‡	1/4"	2.75	0.77
17	3/8"	2.22	0.50
17G†	3/8"	2.96	0.77
17P‡	3/8"	2.06	0.87
17PG†‡	3/8"	2.85	0.87
18	5/16"	2.22	0.50
Brass			
B-17	3/8"	2.22	0.50

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
Brass					
1-SA0	3/16"	7/16"	2.62	1.00	0.56
1-SA3	3/16"	1/2"	2.62	1.00	0.63
1-SB1	1/4"	15/32"	2.69	1.00	0.63
1-SB3	1/4"	1/2"	2.69	1.00	0.63
1-SB5	1/4"	9/16"	2.69	1.00	0.69
1-SB7	1/4"	5/8"	2.69	1.00	0.75
1-SC5	5/16"	9/16"	2.81	1.00	0.69
1-SC7	5/16"	5/8"	2.81	1.00	0.75
1-SC9	5/16"	11/16"	2.81	1.00	0.81
1-SD5	3/8"	9/16"	2.81	1.00	0.69
1-SD7	3/8"	5/8"	2.81	1.00	0.75
1-SD9	3/8"	11/16"	2.81	1.00	0.81
1-SD11	3/8"	3/4"	2.81	1.00	0.88
1-SD13	3/8"	13/16"	2.81	1.00	0.94

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
Steel					
3-PA0	3/16"	7/16"	2.25	0.63	0.56
3-PA3	3/16"	1/2"	2.25	0.70	0.63
3-PB1	1/4"	15/32"	2.31	0.70	0.63
3-PB3	1/4"	1/2"	2.31	0.70	0.63
3-PB5	1/4"	9/16"	2.31	0.77	0.69
3-PB7	1/4"	5/8"	2.31	0.84	0.75
3-PB9	1/4"	11/16"	2.31	0.91	0.81
3-PB11	1/4"	3/4"	2.31	0.98	0.88
3-PC5	5/16"	9/16"	2.38	0.77	0.69
3-PC7	5/16"	5/8"	2.38	0.84	0.75
3-PC9	5/16"	11/16"	2.38	0.91	0.81
3-PD5	3/8"	9/16"	2.44	0.77	0.69
3-PD7	3/8"	5/8"	2.44	0.84	0.75
3-PD9	3/8"	11/16"	2.44	0.91	0.81
3-PD11	3/8"	3/4"	2.44	1.98	0.88
3-PD13	3/8"	13/16"	2.44	1.05	0.94
3-PD15	3/8"	7/8"	2.44	1.12	1.00

* 45° Male Flare § With Ball Check † With Bleeder Ball Check – Reduces hose whip when disconnecting ‡ For use with push-on style hose


Optional Seal Materials: 138-Silicone, 143-Fluorocarbon, 192-EPDM

SERIES 400

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
410-A	1/8-27 NPTF	2.20	1.13	0.88
410	1/4-18 NPTF	2.35	1.13	0.88
430	3/8-18 NPTF	2.35	1.13	0.88
450	1/2-14 NPTF	2.54	1.13	0.88

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
38	1/8-27 NPTF	1.72	0.72	0.63
40	1/4-18 NPTF	1.88	0.72	0.63
40G†	1/4-18 NPTF	2.65	0.77	0.69
42	3/8-18 NPTF	1.88	0.79	0.69
42G†	3/8-18 NPTF	2.65	0.77	0.69
44	1/2-14 NPTF	2.09	1.01	0.88
Brass				
B-40	1/4-18 NPTF	1.88	0.70	0.63
B-42	3/8-18 NPTF	1.88	0.77	0.69
Steel				
31AP-25M	1/4-18 NPTF	1.85	0.72	0.63
31AP-37M	3/8-18 NPTF	1.85	0.79	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
400-A	1/8-27 NPTF	2.10	1.13	0.88
400	1/4-18 NPTF	2.10	1.13	0.88
420	3/8-18 NPTF	2.35	1.13	0.88
440	1/2-14 NPTF	2.62	1.13	1.00


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
41	1/4-18 NPTF	1.63	0.79	0.69
41G†	1/4-18 NPTF	2.56	0.77	0.69
43	3/8-18 NPTF	1.81	0.94	0.81
43G†	3/8-18 NPTF	2.62	0.84	0.75
45	1/2-14 NPTF	2.06	1.15	1.00
Brass				
B-43	3/8-18 NPTF	1.81	0.91	0.81
Steel				
31AP-25F	1/4-18 NPTF	1.60	0.79	0.69
31AP-37F	3/8-18 NPTF	1.78	0.94	0.81

Part No.	Hose I.D.	Dimensions	
		A	B
4004	1/4"	2.82	1.13
4050	5/16"	2.82	1.13
4006	3/8"	2.82	1.13
4008	1/2"	2.82	1.13


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
404	1/4"	2.34	0.63
406	3/8"	2.34	0.63
408	1/2"	2.34	0.81
Brass			
B-406	3/8"	2.34	0.63

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
40-SB3	1/4"	1/2"	2.92	1.13	0.63
40-SB7	1/4"	5/8"	2.92	1.13	0.75
40-SD7	3/8"	5/8"	3.04	1.13	0.75
40-SD9	3/8"	11/16"	3.04	1.13	0.81
40-SD11	3/8"	3/4"	3.04	1.13	0.88
40-SD13	3/8"	13/16"	3.04	1.13	0.94
40-SP13	1/2"	13/16"	3.67	1.13	0.94
40-SP15	1/2"	7/8"	3.67	1.13	1.00
40-SP17	1/2"	15/16"	3.67	1.13	1.06
40-SP19	1/2"	1"	3.67	1.13	1.13

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
4-PB1	1/4"	15/32"	2.44	0.70	0.63
4-PB3	1/4"	1/2"	2.44	0.70	0.63
4-PB5	1/4"	9/16"	2.44	0.77	0.69
4-PB7	1/4"	5/8"	2.44	0.84	0.75
4-PB9	1/4"	11/16"	2.44	0.91	0.81
4-PB11	1/4"	3/4"	2.44	0.98	0.88
4-PD5	3/8"	9/16"	2.56	0.77	0.69
4-PD7	3/8"	5/8"	2.56	0.84	0.75
4-PD9	3/8"	11/16"	2.56	0.91	0.81
4-PD11	3/8"	3/4"	2.56	0.98	0.88
4-PD13	3/8"	13/16"	2.56	1.05	0.94
4-PD15	3/8"	7/8"	2.56	1.12	1.00
4-PP13	1/2"	13/16"	3.25	1.05	0.94
4-PP15	1/2"	7/8"	3.25	1.12	1.00
4-PP17	1/2"	15/16"	3.25	1.19	1.06
4-PP19	1/2"	1"	3.25	1.26	1.13

† With Bleeder Ball Check – Reduces hose whip when disconnecting

Dust Plugs Accessories:

Coupling Series	Socket Dust Plug Part No.
1000	P-SDC-1-HK
400	P-SDC-2-HK
500	P-SDC-3-HK



Vinyl Dust Plug


Optional Seal Materials:

138-Silicone,
143-Fluorocarbon,
192-EPDM

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
501	1/4-18 NPTF	2.77	1.19	1.00
510	3/8-18 NPTF	2.78	1.19	1.00
530	1/2-14 NPTF	2.97	1.19	1.00
550	3/4-14 NPTF	2.97	1.19	1.06

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
50	1/4-18 NPTF	2.25	0.79	0.69
50G†	1/4-18 NPTF	2.90	0.98	0.88
52	3/8-18 NPTF	2.25	0.87	0.75
52G†	3/8-18 NPTF	2.90	0.98	0.88
54	1/2-14 NPTF	2.44	1.01	0.88
54G†	1/2-14 NPTF	3.09	0.98	0.88
56	3/4-14 NPTF	2.50	1.23	1.06
56G†	3/4-14 NPTF	3.14	1.19	1.06
Brass				
B-52	3/8-18 NPTF	2.25	0.70	0.63
B-54	1/2-14 NPTF	2.44	0.77	0.88

Part No.	Thread Size	Dimensions		
		A	B	HEX
500-A	1/4-18 NPTF	2.72	1.19	1.00
500	3/8-18 NPTF	2.78	1.19	1.00
520	1/2-14 NPTF	3.06	1.19	1.00
540	3/4-14 NPTF	3.09	1.19	1.19


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
53-A	1/4-18 NPTF	1.92	0.79	0.69
53	3/8-18 NPTF	2.06	0.94	0.81
53G†	3/8-18 NPTF	2.90	0.98	0.88
55	1/2-14 NPTF	2.34	1.15	1.00
55G†	1/2-14 NPTF	3.17	0.98	0.88
57	3/4-14 NPTF	2.44	1.37	1.19

Part No.	Hose I.D.	Dimensions	
		A	B
570	3/8"	3.32	1.19
580	1/2"	3.24	1.19
590	3/4"	4.09	1.19


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
585	5/16"	2.66	0.69
585G†	5/16"	3.37	0.98
59	3/8"	2.66	0.69
59G†	3/8"	3.37	0.98
60	1/2"	2.66	0.75
60G†	1/2"	3.37	0.98
61	3/4"	3.50	1.00
61G†	3/4"	4.22	0.98
Brass			
B-60	1/2"	2.75	0.88

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
50-SD7	3/8"	5/8"	3.49	1.19	0.75
50-SD13	3/8"	13/16"	3.49	1.19	0.94
50-SP13	1/2"	13/16"	4.09	1.19	0.94
50-SP15	1/2"	7/8"	4.09	1.19	1.00
50-SP17	1/2"	15/16"	4.09	1.19	1.06
50-SP19	1/2"	1"	4.09	1.19	1.13
50-SR23	3/4"	1 1/8"	4.22	1.19	1.25
50-SR25	3/4"	1 3/16"	4.22	1.19	1.31
50-SR27	3/4"	1 1/4"	4.22	1.19	1.38

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
5-PB1	1/4"	15/32"	2.81	0.70	0.63
5-PB3	1/4"	1/2"	2.81	0.70	0.63
5-PB5	1/4"	9/16"	2.81	0.77	0.69
5-PB7	1/4"	5/8"	2.81	0.84	0.75
5-PD5	3/8"	9/16"	2.94	0.77	0.69
5-PD7	3/8"	5/8"	2.94	0.84	0.75
5-PD9	3/8"	11/16"	2.94	0.91	0.81
5-PD11	3/8"	3/4"	2.94	0.98	0.88
5-PD13	3/8"	13/16"	2.94	1.05	0.94
5-PD15	3/8"	7/8"	2.94	1.12	1.00
5-PP13	1/2"	13/16"	3.62	1.05	0.94
5-PP15	1/2"	7/8"	3.62	1.12	1.00
5-PP17	1/2"	15/16"	3.62	1.19	1.06
5-PP19	1/2"	1"	3.62	1.26	1.13
5-PR23	3/4"	1 1/8"	3.75	1.40	1.25
5-PR25	3/4"	1 3/16"	3.75	1.47	1.31
5-PR27	3/4"	1 1/4"	3.75	1.54	1.38

† With Bleeder Ball Check – Reduces hose whip when disconnecting

Optional Seal Materials: 143-Fluorocarbon, 192-EPDM

SERIES 3000/4000/5000/6000



Industrial Interchange Pin Lock


couplings designed for compressed air, gases, and liquids. Body sizes are 1/4", 3/8", 1/2" and 3/4".

FEATURES

- The original automatic one-way shutoff coupling designed by Hansen—The Industry Standard
- Easy, automatic, push-to-connect design provides instantaneous connection and disconnection of lines, plus automatic shut-off of socket end of line
- All sizes accept US Industrial Interchange; 1/4" and 1/2" also accept ISO 1650 Series B and A-A-59439 (former MIL-C-4109) plugs
- Optional sleeve lock prevents accidental disconnection
- Optional seal and valve materials available

APPLICATIONS & MARKETS

- Industrial Breathing Air
- Maintenance & Repair
- General Pneumatics
- Fluid Transfer



Shown with optional sleeve lock.

Interchangeability

All Sizes	1/4" & 1/2"
US Industrial Interchange	ISO 6150 Series B
	A-A-59439 (former MIL-C-4109)

Materials

Socket:

- Brass Body
- Zinc Plated Steel Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Springs
- Stainless Steel Locking Pins

Plug:

- Zinc Plated Case-Hardened Steel
- Brass
- Stainless Steel (1/4" only)

1/4" to 3/4" nominal
(6.35 mm to 19.05 mm)

-40° F to 250° F
-40° C to 120° C


Rated Pressure

Series	Size	PSI	BAR
3000	1/4"	2,000	138
4000	3/8"	1,000	69
5000	1/2"	500	35
6000	3/4"	220	15

Flow Capacity

Series	†Ac
3000	24
4000	45
5000	72
6000	125

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.




3000 SERIES

SOCKETS

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
2900	1/8-27 NPTF	2.00	1.19	0.69
3100	1/4-18 NPTF	2.19	1.19	0.69
3300	3/8-18 NPTF	2.15	1.19	0.69
3000-43*	7/16-20	2.10	1.19	0.69
3000-63*	5/8-18	2.22	1.19	0.69

Male End Connections




PLUGS

Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
10	1/4-18 NPTF	1.75	0.65	0.56
10C§	1/4-18 NPTF	1.75	0.65	0.56
10G†	1/4-18 NPTF	1.75	0.65	0.56
12	1/8-27 NPTF	1.59	0.58	0.50
12G†	1/8-27 NPTF	2.38	0.77	0.69
14	3/8-18 NPTF	1.75	0.79	0.69
14G†	3/8-18 NPTF	2.53	0.77	0.69
Brass				
B-10	1/4-18 NPTF	1.75	0.64	0.56
Stainless				
LL-10	1/4-18 NPTF	1.75	0.65	0.56

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
2800	1/8-27 NPTF	1.89	1.19	0.69
3000	1/4-18 NPTF	2.11	1.19	0.69
3200	3/8-18 NPTF	2.19	1.19	0.75


Female End Connections



Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
11	1/4-18 NPTF	1.63	0.79	0.69
11G†	1/4-18 NPTF	2.44	0.77	0.69
13	1/8-27 NPTF	1.47	0.65	0.56
15	3/8-18 NPTF	1.69	0.94	0.81
15G†	3/8-18 NPTF	2.50	0.84	0.75
Brass				
11B	1/4-18 NPTF	1.63	0.78	0.69
Stainless				
LL-11	1/4-18 NPTF	1.63	0.79	0.69

Part No. Brass	Hose I.D.	Dimensions	
		A	B
3600	1/4"	2.63	1.19
3600P‡	1/4"	2.40	1.19
3700	3/8"	2.63	1.19
3700P‡	3/8"	2.47	1.19
3800	5/16"	2.63	1.19


Hose Stem End Connections



Part No. Steel	Hose I.D.	Dimensions	
		C	D
16	1/4"	2.22	0.50
16G†	1/4"	2.97	0.77
16P‡	1/4"	2.00	0.69
16PG†‡	1/4"	2.75	0.77
17	3/8"	2.31	0.50
17G†	3/8"	2.96	0.77
17P‡	3/8"	2.06	0.87
17PG†‡	3/8"	2.85	0.87
18	5/16"	2.22	0.50
Brass			
B-17	3/8"	2.31	0.50

Part No. Brass	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
3-SA0	3/16"	7/16"	2.65	1.19	0.56
3-SA3	3/16"	1/2"	2.65	1.19	0.63
3-SB1	1/4"	15/32"	2.72	1.19	0.63
3-SB3	1/4"	1/2"	2.72	1.19	0.63
3-SB5	1/4"	9/16"	2.72	1.19	0.69
3-SB7	1/4"	5/8"	2.72	1.19	0.75
3-SB9	1/4"	11/16"	2.72	1.19	0.81
3-SB11	1/4"	3/4"	2.72	1.19	0.88
3-SC5	5/16"	9/16"	2.78	1.19	0.69
3-SC7	5/16"	5/8"	2.78	1.19	0.75
3-SC9	5/16"	11/16"	2.78	1.19	0.81
3-SD5	3/8"	9/16"	2.84	1.19	0.69
3-SD7	3/8"	5/8"	2.84	1.19	0.75
3-SD9	3/8"	11/16"	2.84	1.19	0.81
3-SD11	3/8"	3/4"	2.84	1.19	0.88
3-SD13	3/8"	13/16"	2.84	1.19	0.94

Hose Clamp End Connections



Part No. Steel	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
3-PA0	3/16"	7/16"	2.25	0.63	0.56
3-PA3	3/16"	1/2"	2.25	0.70	0.63
3-PB1	1/4"	15/32"	2.31	0.70	0.63
3-PB3	1/4"	1/2"	2.31	0.70	0.63
3-PB5	1/4"	9/16"	2.31	0.77	0.69
3-PB7	1/4"	5/8"	2.31	0.84	0.75
3-PB9	1/4"	11/16"	2.31	0.91	0.81
3-PB11	1/4"	3/4"	2.31	0.98	0.88
3-PC5	5/16"	9/16"	2.38	0.77	0.69
3-PC7	5/16"	5/8"	2.38	0.84	0.75
3-PC9	5/16"	11/16"	2.38	0.91	0.81
3-PD5	3/8"	9/16"	2.44	0.77	0.69
3-PD7	3/8"	5/8"	2.44	0.84	0.75
3-PD9	3/8"	11/16"	2.44	0.91	0.81
3-PD11	3/8"	3/4"	2.44	0.98	0.88
3-PD13	3/8"	13/16"	2.44	1.05	0.94
3-PD15	3/8"	7/8"	2.44	1.12	1.00

* 45° Male Flare § With Ball Check † With Bleeder Ball Check – Reduces hose whip when disconnecting ‡ For use with push-on style hose


Optional Seal Materials: 138-Silicone, 143-Fluorocarbon, 192-EPDM

SERIES 4000

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
4100-A	1/8-27 NPTF	2.20	1.13	0.88
4100	1/4-18 NPTF	2.35	1.13	0.88
4300	3/8-18 NPTF	2.35	1.13	0.88
4500	1/2-14 NPTF	2.54	1.13	0.88

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
38	1/8-27 NPTF	1.72	0.72	0.63
40	1/4-18 NPTF	1.88	0.72	0.63
40G†	1/4-18 NPTF	2.65	0.77	0.69
42	3/8-18 NPTF	1.88	0.79	0.69
42G†	3/8-18 NPTF	2.65	0.77	0.69
44	1/2-14 NPTF	2.09	1.01	0.88
Brass				
B-40	1/4-18 NPTF	1.88	0.70	0.63
B-42	3/8-18 NPTF	1.88	0.77	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
4000-A	1/8-27 NPTF	2.10	1.38	0.88
4000	1/4-18 NPTF	2.10	1.38	0.88
4200	3/8-18 NPTF	2.35	1.38	0.88
4400	1/2-14 NPTF	2.62	1.38	1.00


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
41	1/4-18 NPTF	1.63	0.79	0.69
41G†	1/4-18 NPTF	2.56	0.77	0.69
43	3/8-18 NPTF	1.81	0.94	0.81
43G†	3/8-18 NPTF	2.62	0.84	0.75
45	1/2-14 NPTF	2.06	1.15	1.00
Brass				
B-43	3/8-18 NPTF	1.81	0.91	0.81

Part No.	Hose I.D.	Dimensions	
		A	B
40400	1/4"	2.82	1.38
40500	5/16"	2.82	1.38
40600	3/8"	2.82	1.38
40800	1/2"	2.82	1.38


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
404	1/4"	2.34	0.63
406	3/8"	2.34	0.63
408	1/2"	2.34	0.81
Brass			
B-406	3/8"	2.34	0.63

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
4-SB3	1/4"	1/2"	2.92	1.38	0.63
4-SB5	1/4"	9/16"	2.92	1.38	0.69
4-SB7	1/4"	5/8"	2.92	1.38	0.75
4-SB9	1/4"	11/16"	2.92	1.38	0.81
4-SB11	1/4"	3/4"	2.92	1.38	0.88
4-SC7	5/16"	5/8"	2.98	1.38	0.75
4-SD5	3/8"	9/16"	3.04	1.38	0.69
4-SD7	3/8"	5/8"	3.04	1.38	0.75
4-SD9	3/8"	11/16"	3.04	1.38	0.81
4-SD11	3/8"	3/4"	3.04	1.38	0.88
4-SD15	3/8"	7/8"	3.04	1.38	1.00
4-SP13	1/2"	13/16"	3.67	1.38	0.94
4-SP15	1/2"	7/8"	3.67	1.38	1.00
4-SP17	1/2"	15/16"	3.67	1.38	1.06
4-SP19	1/2"	1"	3.67	1.38	1.13

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
4-PB1	1/4"	15/32"	2.44	0.70	0.63
4-PB3	1/4"	1/2"	2.44	0.70	0.63
4-PB5	1/4"	9/16"	2.44	0.77	0.69
4-PB7	1/4"	5/8"	2.44	0.84	0.75
4-PB9	1/4"	11/16"	2.44	0.91	0.81
4-PB11	1/4"	3/4"	2.44	0.98	0.88
4-PD5	3/8"	9/16"	2.56	0.77	0.69
4-PD7	3/8"	5/8"	2.56	0.84	0.75
4-PD9	3/8"	11/16"	2.56	0.91	0.81
4-PD11	3/8"	3/4"	2.56	0.98	0.88
4-PD13	3/8"	13/16"	2.56	1.05	0.94
4-PD15	3/8"	7/8"	2.56	1.12	1.00
4-PP13	1/2"	13/16"	3.25	1.05	0.94
4-PP15	1/2"	7/8"	3.25	1.12	1.00
4-PP17	1/2"	15/16"	3.25	1.19	1.06
4-PP19	1/2"	1"	3.25	1.26	1.13


† With Bleeder Ball Check – Reduces hose whip when disconnecting

Optional Seal Materials: 138-Silicone, 143-Fluorocarbon, 192-EPDM

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
50100	1/4-18 NPTF	2.78	1.50	1.00
5100	3/8-18 NPTF	2.79	1.50	1.00
5300	1/2-14 NPTF	2.98	1.50	1.00
5500	3/4-14 NPTF	2.98	1.50	1.06

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
50	1/4-18 NPTF	2.25	0.79	0.69
50G†	1/4-18 NPTF	2.90	0.98	0.88
52	3/8-18 NPTF	2.25	0.87	0.75
52G†	3/8-18 NPTF	2.90	0.98	0.88
54	1/2-14 NPTF	2.44	1.01	0.88
54G†	1/2-14 NPTF	3.09	0.98	0.88
56	3/4-14 NPTF	2.50	1.23	1.06
56G†	3/4-14 NPTF	3.14	1.19	1.06
Brass				
B-52	3/8-18 NPTF	2.25	0.70	0.63
B-54	1/2-14 NPTF	2.44	0.77	0.88

Part No.	Thread Size	Dimensions		
		A	B	HEX
5000-A	1/4-18 NPTF	2.72	1.50	1.00
5000	3/8-18 NPTF	2.79	1.50	1.00
5200	1/2-14 NPTF	3.07	1.50	1.00
5400	3/4-14 NPTF	3.10	1.50	1.19


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
53-A	1/4-18 NPTF	1.92	0.79	0.69
53	3/8-18 NPTF	2.06	0.94	0.81
53G†	3/8-18 NPTF	2.90	0.98	0.88
55	1/2-14 NPTF	2.34	1.15	1.00
55G†	1/2-14 NPTF	3.17	0.98	0.88
57	3/4-14 NPTF	2.44	1.37	1.19

Part No.	Hose I.D.	Dimensions	
		A	B
50400	1/4"	3.26	1.50
50500	5/16"	3.29	1.50
5700	3/8"	3.33	1.50
5800	1/2"	3.25	1.50
5900	3/4"	4.10	1.50


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
585	5/16"	2.66	0.69
585G†	5/16"	3.37	0.98
59	3/8"	2.66	0.69
59G†	3/8"	3.37	0.98
60	1/2"	2.66	0.75
60G†	1/2"	3.37	0.98
61	3/4"	3.50	1.00
61G†	3/4"	4.22	0.98
Brass			
B-60	1/2"	2.75	0.88

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
5-SD5	3/8"	9/16"	3.50	1.50	0.69
5-SD7	3/8"	5/8"	3.50	1.50	0.75
5-SD9	3/8"	11/16"	3.50	1.50	0.81
5-SD11	3/8"	3/4"	3.50	1.50	0.88
5-SD13	3/8"	13/16"	3.50	1.50	0.94
5-SD15	3/8"	7/8"	3.50	1.50	1.00
5-SP13	1/2"	13/16"	4.10	1.50	0.94
5-SP15	1/2"	7/8"	4.10	1.50	1.00
5-SP17	1/2"	15/16"	4.10	1.50	1.06
5-SP19	1/2"	1"	4.10	1.50	1.13
5-SR23	3/4"	1 1/8"	4.23	1.50	1.25
5-SR25	3/4"	1 3/16"	4.23	1.50	1.31
5-SR27	3/4"	1 1/4"	4.23	1.50	1.38

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
5-PB1	1/4"	15/32"	2.81	0.70	0.63
5-PB3	1/4"	1/2"	2.81	0.70	0.63
5-PB5	1/4"	9/16"	2.81	0.77	0.69
5-PB7	1/4"	5/8"	2.81	0.84	0.75
5-PD5	3/8"	9/16"	2.94	0.77	0.69
5-PD7	3/8"	5/8"	2.94	0.84	0.75
5-PD9	3/8"	11/16"	2.94	0.91	0.81
5-PD11	3/8"	3/4"	2.94	0.98	0.88
5-PD13	3/8"	13/16"	2.94	1.05	0.94
5-PD15	3/8"	7/8"	2.94	1.12	1.00
5-PP13	1/2"	13/16"	3.62	1.05	0.94
5-PP15	1/2"	7/8"	3.62	1.12	1.00
5-PP17	1/2"	15/16"	3.62	1.19	1.06
5-PP19	1/2"	1"	3.62	1.26	1.13
5-PR23	3/4"	1 1/8"	3.75	1.40	1.25
5-PR25	3/4"	1 3/16"	3.75	1.47	1.31
5-PR27	3/4"	1 1/4"	3.75	1.54	1.38

† With Bleeder Ball Check – Reduces hose whip when disconnecting


Optional Seal Materials: 143-Fluorocarbon, 192-EPDM

SERIES 6000

SOCKETS

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
6300	1/2-14 NPTF	2.94	1.88	1.31
6500	3/4-14 NPTF	2.94	1.88	1.31
6700	1-11½ NPTF	3.13	1.88	1.31

Male End Connections




PLUGS

Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
64A	1/2-14 NPTF	2.31	1.15	1.00
64GA†	1/2-14 NPTF	3.26	1.12	1.00
66A	3/4-14 NPTF	2.38	1.23	1.06
66GA†	3/4-14 NPTF	3.26	1.19	1.06
68A	1-11½ NPTF	2.56	1.52	1.31
Brass				
B-64A	1/2-14 NPTF	2.31	1.12	1.00
B-66A	3/4-14 NPTF	2.38	1.19	1.06

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
6200	1/2-14 NPTF	2.85	1.88	1.31
6400	3/4-14 NPTF	3.00	1.88	1.31
6600	1-11½ NPTF	3.19	1.88	1.56


Female End Connections



Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
65A	1/2-14 NPTF	2.22	1.15	1.00
65GA†	1/2-14 NPTF	3.35	1.12	1.00
67A	3/4-14 NPTF	2.22	1.37	1.19
67GA†	3/4-14 NPTF	3.38	1.33	1.19
69A	1-11½ NPTF	2.41	1.80	1.56

Part No. Brass	Hose I.D.	Dimensions	
		A	B
6800	1/2"	3.21	1.88
6900	3/4"	4.06	1.88
7000	1"	4.07	1.88

Hose Stem End Connections



Part No. Steel	Hose I.D.	Dimensions	
		C	D
70A	1/2"	2.53	0.94
70GA†	1/2"	3.53	1.12
71A	3/4"	3.44	1.06
71GA†	3/4"	4.38	1.12
72A	1"	3.44	1.31
Brass			
B-71A	3/4"	3.44	1.06

† With Bleeder Ball Check – Reduces hose whip when disconnecting

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.		Socket Dust Plug Part No.	
	Metal	Vinyl	Metal	Vinyl
3000	PDC-3000*	–	SDC-3000*	P-SDC-1-HK
4000	–	–	–	P-SDC-2-HK
5000	–	P-PDC-2-HK	–	–
6000	–	P-PDC-3-HK	–	–

*Brass



Optional Seal Materials: 143-Fluorocarbon

**NEED TO PLACE AN ORDER?
LOCATE A DISTRIBUTOR NEAR YOU
AT WWW.TUTHILL.COM.**





P-30&P-40 SERIES



Industrial Interchange Plastic quick connect couplings designed for compressed air. Body sizes are 1/4" and 3/8".

FEATURES

- Plastic socket body and plug
- Light-weight
- Less likely to damage painted or easily scratched surfaces than metal couplings
- Easy, automatic, push-to-connect design provides instantaneous connection and disconnection of lines, plus automatic shut-off of socket end of line
- Series P-30 accepts all series 3000 plugs;
Series P-40 accepts series 4000 plugs


APPLICATIONS & MARKETS

- General Pneumatics

SOCKETS

Hose Stem End Connections


Part No.	Hose I.D.	Dimensions	
		A	B
P4-30S-25H	1/4"	2.66	1.25
P7-40S-37H	3/8"	2.82	1.44



PLUGS

Male End Connections

Part No.	Thread Size	Dimensions		
		C	D	HEX
P4-30P-25M	1/4-18 NPTF	1.75	0.65	0.56
P7-40P-37M	3/8-18 NPTF	1.88	0.79	0.69



Interchangeability

All Sizes	1/4" only
US Industrial Interchange	ISO 6150 Series B A-A-59439 (former MIL-C-4109)

Materials

Socket:

- Acetal Body
- Polypropylene Sleeve
- Zinc Plated Steel Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Spring

Plug:

- Acetal
- Series P-30 accepts all Series 3000 plugs
- Series P-40 accepts all Series 4000 plugs

**1/4" to 3/8" nominal
(6.35 mm to 9.52 mm)**

Up to 125° F (52° C)

Rated Pressure


Series	Size	PSI	BAR
P-30	1/4"	150	10
P-40	3/8"	150	10

* At temperatures up to 125°

Flow Capacity

Series	† Ac
P-30	28
P-40	45

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.



SERIES AUTO-FLO 23 & 24




Auto-Flo 23 & 24 are high flow, automatic quick connect couplings designed for use with compressed air. The universal design makes the Auto-Flo an extremely flexible coupling series.

FEATURES

- Auto-Flo 23 was the first automatic universal coupling designed to operate with Industrial, ARO 210 and Tru-Flate Interchange plugs
- Auto-Flo 24 operates with CEJN 320 and Rectus 25 Interchange plugs
- Easy, automatic, push-to-connect design provides instantaneous connection and disconnection of lines, plus automatic shut-off of socket end of line
- Sleeve guard protects against accidental disconnection

APPLICATIONS & MARKETS

- General Pneumatics
- Air Tools
- Construction



Interchangeability

Auto-Flo 23	Auto-Flo 24
US Industrial Interchange	(Euro Interchange)
ISO 6150 Series B	
A-A-59439 (former MIL-C-4109)	CEJN 320
Tru-Flate Interchange	RECTUS 25
ARO 210 Interchange	



Materials

Socket:

- Brass Body
- Brass Valve
- Zinc Plated Steel Sleeve
- Buna-N (Nitrile) Seal
- Stainless Steel Spring
- Stainless Steel Locking Balls

Plug:

- Industrial Interchange
 - Zinc Plated Case-Hardened Steel
 - Brass
 - Stainless Steel
- ARO 210, Tru-Flate and CEJN/Rectus Interchanges
 - Zinc Plated Case-Hardened Steel



1/4" nominal (6.35 mm)



-40° F to 250° F
-40° C to 120° C



Pressure Ratings

Series	PSI	BAR
Auto-Flo 23	150	10
Auto-Flo 24	150	10



Flow Capacities

Plug Interchange	† Ac
Industrial	32
ARO 210	32
Tru-Flate	30
Auto-Flo 24	45

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.



1/4" Nominal


Tuthill

AUTO-FLO 23 SERIES

SOCKETS



Part No.	Thread Size	Dimensions		
		A	B	HEX
B23AS-25M	1/4-18 NPTF	2.23	0.94	0.81
B23AS-25MBST	1/4-19 BSPT	2.23	0.94	0.81
B23AS-37M	3/8-18 NPTF	2.23	0.94	0.81
B23AS-37MBST	3/8-19 BSPT	2.23	0.94	0.81
B23AS-50MBST	1/2-14 BSPT	2.23	0.94	0.88

Male End Connections






PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
Steel				
10	1/4-18 NPTF	1.75	0.65	0.56
10C§	1/4-18 NPTF	1.75	0.65	0.56
10G†	1/4-18 NPTF	1.75	0.65	0.56
12	1/8-27 NPTF	1.59	0.58	0.50
12G†	1/8-27 NPTF	2.38	0.77	0.69
14	3/8-18 NPTF	1.75	0.79	0.69
14G†	3/8-18 NPTF	2.53	0.77	0.69
Brass				
B-10	1/4-18 NPTF	1.75	0.64	0.56
Stainless				
LL-10	1/4-18 NPTF	1.75	0.65	0.56
ARO 210 Interchange				
2607	1/8-27 NPTF	1.42	0.58	0.50
2608	1/4-18 NPTF	1.68	0.65	0.56
2608B	1/4-19 BSPT	1.68	0.65	0.56
20AP-37M	3/8-18 NPTF	1.68	0.79	0.69
Tru-Flate Interchange				
21AP-25M	1/4-18 NPTF	1.65	0.65	0.56
21AP-37M	3/8-18 NPTF	1.65	0.79	0.69



Part No.	Thread Size	Dimensions		
		A	B	HEX
B23AS-25F	1/4-18 NPTF	2.02	0.94	0.81
B23AS-25FBS	1/4-19 BSPP	2.02	0.94	0.81
B23AS-37F	3/8-18 NPTF	2.02	0.94	0.81
B23AS-37FBS	3/8-19 BSPP	2.02	0.94	0.81
B23AS-50FBS	3/8-14 BSPP	2.34	0.94	1.06




Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
Steel				
11	1/4-18 NPTF	1.63	0.79	0.69
11G†	1/4-18 NPTF	2.44	0.77	0.69
13	1/8-27 NPTF	1.47	0.65	0.56
15	3/8-18 NPTF	1.69	0.94	0.81
15G†	3/8-18 NPTF	2.50	0.84	0.75
Brass				
11B	1/4-18 NPTF	1.63	0.78	0.69
Stainless				
LL-11	1/4-18 NPTF	1.63	0.79	0.69
ARO 210 Interchange				
2609	1/4-18 NPTF	1.55	0.79	0.69
2609B	1/4-19 BSPP	1.55	0.79	0.69
20AP-37F	3/8-18 NPTF	1.61	0.94	0.81
Tru-Flate Interchange				
21AP-25F	1/4-18 NPTF	1.53	0.79	0.69
21AP-37F	3/8-18 NPTF	1.59	0.94	0.81

Part No.	Hose I.D.	Dimensions	
		A	B
B23AS-25H	1/4"	2.76	0.94
B23AS-31H	5/16"	2.73	0.94
B23AS-37H	3/8"	2.73	0.94
B23AS-50H	1/2"	2.70	0.94

Hose Stem End Connections



Part No.	Thread Size	Dimensions	
		C	D
Steel			
16	1/4"	2.22	0.50
16G†	1/4"	2.97	0.77
16P‡	1/4"	2.00	0.69
16PG†‡	1/4"	2.75	0.77
17	3/8"	2.31	0.50
17G†	3/8"	2.96	0.77
17P‡	3/8"	2.06	0.87
17PG†‡	3/8"	2.85	0.87
18	5/16"	2.22	0.50
Brass			
B-17	3/8"	2.31	0.50
ARO 210 Interchange			
3946	1/4"	2.14	0.50
3947	5/16"	2.14	0.50
22238	3/8"	2.14	0.50
Tru-Flate Interchange			
21AP-25H	1/4"	2.12	0.50
21AP-37H	3/8"	2.12	0.50

* 45° Male Flare § With Ball Check † With Bleeder Ball Check – Reduces hose whip when disconnecting ‡ For use with push-on style hose

Tuthill Coupling
Group

HANSEN™
QUICK SEAL®
COUPLEURS GROMELLE™

North America

EMEA

Asia Pacific

China

Latin America

+1 440 826 1115 +33 450 84 11 22 +61 3 9839 7800 +86 21 5385 3369 +1 305 740 3381

www.tuthill.com

25

ONE-WAY

TWO-WAY

STRAIGHT-THRU

GAS


ACCESSORIES

SERIES AUTO-FLO 24

SOCKETS

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
B24AS-25M	1/4-18 NPTF	2.27	0.94	0.81
B24AS-25MBST	1/4-19 BSPT	2.27	0.94	0.81
B24AS-37MBST	3/8-19 BSPT	2.27	0.94	0.81
B24AS-50MBST	1/2-14 BSPT	2.27	0.94	0.88

Male End Connections




PLUGS

Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
24AP-25MG	1/4-18 NPTF	1.64	0.65	0.56
24AP-25MBST	1/4-19 BSPT	1.62	0.65	0.56
24AP-37MBST	3/8-19 BSPT	1.62	0.79	0.69
24AP-50MBST	1/2-14 BSPT	1.88	1.01	0.88

Part No. Brass	Thread Size	Dimensions		
		A	B	HEX
B24AS-25F	1/4-18 NPTF	2.06	0.94	0.81
B24AS-25FBS	1/4-19 BSPP	2.06	0.94	0.81
B24AS-37FBS	3/8-19 BSPP	2.06	0.94	0.81
B24AS-50FBS	1/2-14 BSPP	2.38	0.94	1.06


Female End Connections



Part No. Steel	Thread Size	Dimensions		
		C	D	HEX
24AP-25FG	1/4-18 NPTF	1.49	0.79	0.69
24AP-25FBS	1/4-19 BSPP	1.46	0.79	0.69
24AP-37FBS	3/8-19 BSPP	1.52	0.94	0.81
24AP-50FBS	1/2-14 BSPP	1.65	1.23	1.06

Part No. Brass	Hose I.D.	Dimensions	
		A	B
B24AS-25H	1/4"	2.80	0.94
B24AS-31H	5/16"	2.77	0.94
B24AS-37H	3/8"	2.77	0.94
B24AS-50H	1/2"	2.74	0.94

Hose Stem End Connections



Part No. Steel	Hose I.D.	Dimensions	
		C	D
24AP-25H	1/4"	2.08	0.50
24AP-31H	5/16"	2.08	0.50
24AP-37H	3/8"	2.08	0.50
24AP-50H	1/2"	2.08	0.63

**NEED A QUOTE? VISIT WWW.TUTHILL.COM
TO SUBMIT YOUR REQUEST QUICKLY AND
EASILY!**





SAFELINE[®] SERIES



The SAFELINE Industrial Interchange pushbutton safety coupling is designed for use with compressed air. Two-step disconnect procedure shuts off air supply and releases downstream air pressure before plug can be removed from socket, which prevents hose whip.

FEATURES


- Safe and easy to connect and disconnect
- Light weight, compact ergonomic design
- Accepts 1/4" ISO 6150 Series B and A-A-59439 (former MIL-C-4109) plugs

OPERATION

- To connect: Push plug into socket
- To disconnect: (1) Push button on side of socket. Air supply is shut off and plug pops out 3/16 inch, but is not released from socket. Downstream air is vented. (2) Push plug into socket to release latch. Pull plug from socket.

APPLICATIONS & MARKETS

- General Pneumatics
- Air Tools
- Industrial Plants
- Maintenance & Repair



Interchangeability

- US Industrial Interchange
- ISO 6150 Series B
- A-A-59439 (Former MIL-C-4109)



Materials

Socket:

- Aluminum and steel construction
- Buna-N (Nitrile) Seal

Plug:

- Use Series 3000 Plug



1/4" Nominal (6.35 mm)



-40° F to 250° F
-40° C to 120° C



Rated Pressure

Series	PSI	Bar
GD 10500	232	16




Flow Capacity

Series	†Ac
GD 10500	20


† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.

Male End Connections




Part No.	Thread Size	Dimensions		
		A	B	HEX
GD 10536 41	1/4-18 NPTF	3.18	1.02	0.67
GD 10536 83	3/8-18 NPTF	3.18	1.02	0.75

Female End Connections



Part No.	Thread Size	Dimensions		
		A	B	HEX
GD 10526 41	1/4-18 NPTF	2.97	1.02	0.67
GD 10526 83	3/8-18 NPTF	3.18	1.02	0.87

Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		A	B
GD 10556 67	1/4"	3.56	1.02
GD 10556 01	3/8"	3.56	1.02

SERIES 180&280



Miniature Ball Lock quick connect couplings designed for use with compressed air, gases and liquids.

FEATURES

- Ball lock
- Manual operation
- Series 180 and 280 sockets mate with all Series 180 plugs
- Series 180 sockets have a tire valve
- Series 280 sockets have a 1-HK valve, which provides higher flow capacity
- Chrome plating available
- Additional seal materials available

APPLICATIONS & MARKETS

- Diving
- Breathing Air
- General Pneumatics
- Pharmaceutical
- Laboratory Uses
- Medical



Interchangeability

- Proprietary Interchange



Materials

Socket:

- Brass Body and Sleeve
- Valve
 - 180: Nickel Plated Brass Tire Valve
 - 280: Brass Series 1-HK Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Springs
- Stainless Steel Locking Balls

Plug:

- Brass



1/8" nominal (3.175 mm)



-40° F to 250° F
-40° C to 120° C



Pressure Ratings


Series	PSI	BAR
180	700	48
280	3,000	207



Flow Capacities


Series	† Ac
180	2.5
280	10.0

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.




180&280 SERIES

Series 180




Series 280



Part No.	Thread Size	Dimensions		
		A	B	HEX
180	1/8-27 NPTF	1.41	0.63	0.56
28S-25M	1/4-18 NPTF	1.38	0.63	0.56


Male End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
185	1/8-27 NPTF	1.16	0.49	0.44
186	1/4-18 NPTF	1.44	0.63	0.56


Part No.	Thread Size	Dimensions		
		A	B	HEX
28S-12F	1/8-27 NPTF	1.78	0.63	0.56

Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
183	1/8" NPTF	1.19	0.56	0.50

Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
187	1/8"	1.25	0.38
189	3/16"	1.50	0.38

CAN'T FIND WHAT YOU'RE LOOKING FOR?
VISIT WWW.TUTHILL.COM FOR PRODUCT
INFORMATION OR CALL YOUR LOCAL
DISTRIBUTOR.



SERIES 100




Series 100 quick connect couplings are designed to prevent the crossing of lines. These couplings are used for compressed air and gasses.

FEATURES

- Ball lock
- Manual operation
- Non-interchangeable design prevents crossing of lines

APPLICATIONS & MARKETS

- General Pneumatics
- Industrial Plants



Interchangeability

- Proprietary Interchange



Materials

Socket:

- Brass Body
- Brass Valve
- Brass Sleeve
- Buna-N (Nitrile) Seal
- Stainless Steel Spring
- Stainless Steel Locking Balls

Plug:

- Brass



1/4" nominal (6.35 mm)



-40° F to 250° F
-40° C to 120° C



Pressure Ratings


Series	PSI	BAR
100	350	24



Flow Capacities

Series	† Ac
100	20


† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.



SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
101	1/8-27 NPTF	1.94	1.00	0.69
103	1/4-18 NPTF	2.09	1.00	0.69
105	3/8-18 NPTF	2.09	1.00	0.69
100-63*	5/8-18	2.16	1.00	0.69

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
1G1	1/8-27 NPTF	1.38	0.65	0.56
1G3	1/4-18 NPTF	1.56	0.65	0.56
1G5	3/8-18 NPTF	1.56	0.79	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
100	1/8-27 NPTF	1.78	1.00	0.69
102	1/4-18 NPTF	2.00	1.00	0.69
104	3/8-18 NPTF	2.06	1.00	0.75


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
1G2	1/4-18 NPTF	1.43	0.79	0.69

Part No.	Hose I.D.	Dimensions	
		A	B
110	1/4"	2.53	1.00
111	5/16"	2.53	1.00
112	3/8"	2.52	1.00


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
1G10	1/4"	2.00	0.56
1G12	3/8"	2.03	0.56

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
1-GB3	1/4"	1/2"	2.62	1.00	0.63
1-GB7	1/4"	5/8"	2.62	1.00	0.75
1-GD7	3/8"	5/8"	2.75	1.00	0.75
1-GD9	3/8"	11/16"	2.75	1.00	0.81

Hose Clamp End Connections



* 45° Male Flare

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.		Socket Dust Plug Part No.	
	Vinyl		Vinyl	
100	P-PDC-1-HK		P-SDC-1-HK	



ACCESS EDUCATIONAL MATERIALS,
PRODUCT NEWS, CATALOG DOWNLOADS
AND MORE AT WWW.TUTHILL.COM.



SERIES 600&700



600 & 700 Series quick connect couplings are designed for use in oxyacetylene service. Series 600 is used with oxygen. Series 700 is used with acetylene.

FEATURES

- Ball lock
- Manual operation
- Non-interchangeable designs prevent crossing of lines
- Sleeves are color coded to identify each series:
 - Series 600 sleeves are green for oxygen
 - Series 700 sleeves are red for acetylene
- Series 600 and 700 couplings can also be used with compressed air and other gases
- Sockets with the SL suffix have the sleeve lock feature to prevent accidental disconnection
- Series 600 and 700 couplings with sleeve lock feature comply with OSHA requirements*, which state couplings shall be the type that cannot be unlocked or disconnected by means of a straight pull without rotary motion.

APPLICATIONS & MARKETS

- Breathing Equipment
- Welding
- Shipyards
- General Pneumatics
- Construction
- Nitrous Oxide



Interchangeability

- Proprietary Interchange



Materials

Socket:

- Brass Body
- Brass Valve
- Painted Brass Sleeve
 - Green** - Series 600
 - Red** - Series 700
- Buna-N (Nitrile) Seal
- Stainless Steel Springs
- Stainless Steel Locking Balls

Plug:

- Brass



1/4" nominal (6.35 mm)



-40° F to 250° F
-40° C to 120° C



Pressure Ratings


Series	PSI	BAR
600 & 700	1,500	103




Flow Capacities

Series	†Ac
600 & 700	21

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.



*29 CFR 1915.55 (f)(5), 1917.152 (d)(3)(iv) and 29 CFR 1926.350 (f)(5)




See Fittings on Page 78

SOCKETS

Part No. - Brass		Thread Size	Dimensions		
Standard	Oxygen Serv.		A	B	HEX
GR-601	GR-601-SL	1/8-27 NPTF	1.84	1.00	0.69
GR-603	GR-603-SL	1/4-18 NPTF	2.03	1.00	0.69
GR-604R†	GR-604R-SL	9/16-18	1.92	1.00	0.69
GR-605	GR-605-SL	3/8-18 NPTF	1.99	1.00	0.69

Male End Connections




PLUGS

Part No.		Thread Size	Dimensions		
Brass			C	D	HEX
01A		1/8-27 NPTF	1.41	0.63	0.56
03A		1/4-18 NPTF	1.56	0.63	0.56
04-R†		9/16-18	1.41	0.63	0.56

Part No. - Brass		Thread Size	Dimensions		
Standard	Oxygen Serv.		A	B	HEX
GR-600	GR-600-SL	1/8-27 NPTF	1.73	1.00	0.69
GR-602	GR-602-SL	1/4-18 NPTF	1.95	1.00	0.69
GR-604	GR-604-SL	3/8-18 NPTF	2.03	1.00	0.69
GR-605R‡	GR-605R-SL	9/16-18	1.95	1.00	0.69


Female End Connections



Part No.		Thread Size	Dimensions		
Brass			C	D	HEX
00A		1/8-27 NPTF	1.22	0.63	0.56
02A		1/4-18 NPTF	1.41	0.77	0.69
05-R‡		9/16-18	1.38	0.77	0.69

Part No. - Brass		Hose I.D.	Dimensions	
Standard	Oxygen Serv.		A	B
GR-606	GR-606-SL	1/4"	2.47	1.00
GR-606P§	GR-606P-SL§	1/4"	2.24	1.00
GR-607	GR-607-SL	5/16"	2.47	1.00
GR-608	GR-608-SL	3/8"	2.47	1.00
GR-608P§	—	3/8"	2.31	1.00


Hose Stem End Connections



Part No.		Hose I.D.	Dimensions	
Brass			C	D
07A		1/4"	2.03	0.56
08A		5/16"	2.03	0.56
09A		3/8"	2.04	0.56

Part No. - Brass		Hose		Dimensions		
Standard	Oxygen Serv.	I.D.	O.D.	A	B	HEX
GR-6-0A3	—	3/16"	1/2"	2.49	1.00	0.63
GR-6-0B3	GR-6-0B3-SL	1/4"	1/2"	2.56	1.00	0.63
GR-6-0B5	GR-6-0B5-SL	1/4"	9/16"	2.56	1.00	0.69
GR-6-0B7	GR-6-0B7-SL	1/4"	5/8"	2.56	1.00	0.75
GR-6-0C5	—	5/16"	9/16"	2.62	1.00	0.69
GR-6-0C7	—	5/16"	5/8"	2.62	1.00	0.75
GR-6-0C9	—	5/16"	11/16"	2.62	1.00	0.81
GR-6-0D7	—	3/8"	5/8"	2.68	1.00	0.75
GR-6-0D9	—	3/8"	11/16"	2.68	1.00	0.81
GR-6-0D11	—	3/8"	3/4"	2.68	1.00	0.88

Hose Clamp End Connections



Part No.		Hose		Dimensions		
Brass		I.D.	O.D.	C	D	HEX
6-B3		1/4"	1/2"	2.13	0.70	0.63
6-B5		1/4"	9/16"	2.13	0.77	0.69
6-B7		1/4"	5/8"	2.13	0.84	0.75
6-B9		1/4"	11/16"	2.13	0.91	0.81
6-D5		3/8"	9/16"	2.25	0.77	0.69
6-D7		3/8"	5/8"	2.25	0.84	0.75
6-D9		3/8"	11/16"	2.25	0.91	0.81
6-D11		3/8"	3/4"	2.25	0.98	0.88

† R.H. Thread - 30° Female Flare ‡ R.H. Thread - Inverted Flare § For use with push-on style hose.

TO ADD A THIRD NON-INTERCHANGEABLE LINE, USE THE 100 SERIES WITH THE 600 AND 700 SERIES.




WARNING

Oxygen increases combustibility. Fire and explosion could occur causing severe bodily injury or death. Be sure to select the proper coupling for your application and use it only within the specified service pressure range.

Series 600 and 700 couplings with sleeve lock feature comply with O.S.H.A. requirements, Sec. 1915.35 (f)(5), 1916.35 (f)(5), 1917.35 (f)(5), and 1926.350 (f)(5).

SERIES 700


See Fittings on Page 78



SOCKETS

Part No. - Brass		Thread Size	Dimensions		
Standard	Acetyl. Serv.		A	B	HEX
RD-701	—	1/8-27 NPTF	1.84	1.00	0.69
RD-703	RD-703-SL	1/4-18 NPTF	2.02	1.00	0.69
RD-704L†	RD-704L-SL	9/16-18	1.92	1.00	0.69
RD-705	RD-705-SL	3/8-18 NPTF	1.99	1.00	0.69

Male End Connections




PLUGS

Part No.		Thread Size	Dimensions		
Brass			C	D	HEX
A1		1/8-27 NPTF	1.47	0.63	0.56
A3P		1/4-18 NPTF	1.63	0.63	0.56
A4-L†		9/16-18	1.50	0.63	0.56

Part No. - Brass		Thread Size	Dimensions		
Standard	Acetyl. Serv.		A	B	HEX
RD-700	RD-700-SL	1/8-27 NPTF	1.73	1.00	0.69
RD-702	RD-702-SL	1/4-18 NPTF	1.95	1.00	0.69
RD-704	RD-704-SL	3/8-18 NPTF	2.03	1.00	0.69
RD-705L‡	RD-705L-SL	9/16-18	1.95	1.00	0.69


Female End Connections



Part No.		Thread Size	Dimensions		
Brass			C	D	HEX
A2		1/4-18 NPTF	1.46	0.77	0.69
A5-L‡		9/16-18	1.38	0.77	0.69

Part No. - Brass		Hose I.D.	Dimensions	
Standard	Acetyl. Serv.		A	B
RD-706	RD-706-SL	1/4"	2.47	1.00
RD-706P§	—	1/4"	2.24	1.00
RD-707	RD-707-SL	5/16"	2.47	1.00
RD-708	RD-708-SL	3/8"	2.47	1.00


Hose Stem End Connections



Part No.		Hose I.D.	Dimensions	
Brass			C	D
A7		1/4"	2.06	0.56
A8		5/16"	2.06	0.56
A9		3/8"	2.10	0.56

Part No. - Brass		Hose		Dimensions		
Standard	Acetyl. Serv.	I.D.	O.D.	A	B	HEX
RD-7-0A3	—	3/16"	1/2"	2.49	1.00	0.63
RD-7-0B3	RD-7-0B3-SL	1/4"	1/2"	2.56	1.00	0.63
RD-7-0B5	RD-7-0B5-SL	1/4"	9/16"	2.56	1.00	0.69
RD-7-0B7	—	1/4"	5/8"	2.56	1.00	0.75
RD-7-0D7	—	3/8"	5/8"	2.68	1.00	0.75
RD-7-0D9	—	3/8"	11/16"	2.68	1.00	0.81
RD-7-0D11	—	3/8"	3/4"	2.68	1.00	0.88

Hose Clamp End Connections



Part No.		Hose		Dimensions		
Brass		I.D.	O.D.	C	D	HEX
7-B3		1/4"	1/2"	2.19	0.70	0.63
7-B5		1/4"	9/16"	2.19	0.77	0.69
7-B7		1/4"	5/8"	2.19	0.84	0.75
7-B11		1/4"	3/4"	2.19	0.98	0.88

† L.H. Thread - 30° Female Flare ‡ L.H. Thread - Inverted Flare § For use with push-on style hose.

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.	Socket Dust Plug Part No.
1000	P-PDC-1-HK	P-SDC-1-HK
400	P-PDC-1-HK	P-SDC-1-HK



2RL&3RL_{SERIES}




2RL & 3RL Ring Lock quick connect couplings have a unique interchange which Hansen designed for use with compressed air. Body sizes are 1/4" and 3/8".

FEATURES

- High flow capacity
- Push to connect
- Ring lock
- Will not disconnect when hose is dragged on the ground
- Rotate locking sleeve approximately 20° to disconnect
- Optional seal materials available

APPLICATIONS & MARKETS

- Shipyards
- General Pneumatics
- Mining
- Marine



Interchangeability

- Proprietary Interchange

Materials

Socket:

- Zinc Plated Steel Body
- Brass Socket End
- Nickel Plated Steel Sleeve
- Zinc Plated Steel Valve
- Buna-N (Nitrile) Seal
- Stainless Steel Spring
- Zinc Plated Steel Locking Ring

Plug:

- Zinc Plated Case-Hardened Steel

1/4" to 3/8" nominal
(6.35 mm to 9.52 mm)

-40° F to 250° F
-40° C to 120° C


Rated Pressure

Series	Size	PSI	BAR
2-RL	1/4"	300	20
3-RL	3/8"	300	20

Flow Capacity

Series	†Ac
2-RL	48
3-RL	80

† Air flow (scfm) with 5 psi pressure drop and 100 psig inlet pressure.




SERIES 2RL

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-R10	1/8-27 NPTF	2.01	1.06	0.88
2-R15	1/4-18 NPTF	2.16	1.06	0.88
2-R20	3/8-18 NPTF	2.16	1.06	0.88
2-R25	1/2-14 NPTF	2.35	1.06	0.88

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
2-L10	1/8-27 NPTF	1.51	0.58	0.50
2-L15	1/4-18 NPTF	1.66	0.65	0.56
2-L15G†	1/4-18 NPTF	2.64	0.77	0.69
2-L20	3/8-18 NPTF	2.04	0.79	0.69
2-L20G†	3/8-18 NPTF	2.64	0.77	0.69
2-L25	1/2-14 NPTF	2.31	1.01	0.88

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-R11	1/8-27 NPTF	1.91	1.06	0.88
2-R16	1/4-18 NPTF	1.91	1.06	0.88
2-R21	3/8-18 NPTF	2.16	1.06	0.88
2-R26	1/2-14 NPTF	2.43	1.06	1.00


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
2-L11	1/8-27 NPTF	1.36	0.65	0.56
2-L16	1/4-18 NPTF	1.54	0.79	0.69
2-L16G†	1/4-18 NPTF	2.55	0.77	0.69
2-L21	3/8-18 NPTF	1.88	0.94	0.81
2-L26	1/2-14 NPTF	2.18	1.15	1.00

Part No.	Hose I.D.	Dimensions	
		A	B
2-R17	1/4"	2.63	1.06
2-R195	5/16"	2.63	1.06
2-R22	3/8"	2.63	1.06
2-R27	1/2"	2.63	1.06


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
2-L17	1/4"	2.13	0.56
2-L195	5/16"	2.13	0.56
2-L22	3/8"	2.13	0.56
2-L27	1/2"	2.50	0.81

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
2-R18B1	1/4"	15/32"	2.73	1.06	0.63
2-R18B3	1/4"	1/2"	2.73	1.06	0.63
2-R18B5	1/4"	9/16"	2.73	1.06	0.69
2-R18B7	1/4"	5/8"	2.73	1.06	0.75
2-R18B9	1/4"	11/16"	2.73	1.06	0.81
2-R18B11	1/4"	3/4"	2.73	1.06	0.88
2-R185C5	5/16"	9/16"	2.79	1.06	0.69
2-R185C7	5/16"	5/8"	2.79	1.06	0.75
2-R185C9	5/16"	11/16"	2.79	1.06	0.81
2-R23D5	3/8"	9/16"	2.85	1.06	0.69
2-R23D7	3/8"	5/8"	2.85	1.06	0.75
2-R23D9	3/8"	11/16"	2.85	1.06	0.81
2-R23D11	3/8"	3/4"	2.85	1.06	0.88
2-R23D13	3/8"	13/16"	2.85	1.06	0.94
2-R28P13	1/2"	13/16"	3.48	1.06	0.94
2-R28P15	1/2"	7/8"	3.48	1.06	1.00

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
2-L18B1	1/4"	15/32"	2.23	0.70	0.63
2-L18B3	1/4"	1/2"	2.23	0.70	0.63
2-L18B5	1/4"	9/16"	2.23	0.77	0.69
2-L18B7	1/4"	5/8"	2.23	0.84	0.75
2-L18B9	1/4"	11/16"	2.23	0.91	0.81
2-L18B11	1/4"	3/4"	2.23	0.98	0.88
2-L185C5	5/16"	9/16"	2.29	0.77	0.69
2-L185C7	5/16"	5/8"	2.29	0.84	0.75
2-L185C9	5/16"	11/16"	2.29	0.91	0.81
2-L23D5	3/8"	9/16"	2.35	0.77	0.69
2-L23D7	3/8"	5/8"	2.35	0.84	0.75
2-L23D9	3/8"	11/16"	2.35	0.91	0.81
2-L23D11	3/8"	3/4"	2.35	0.98	0.88
2-L23D13	3/8"	13/16"	2.35	1.05	0.94
2-L28P13	1/2"	13/16"	3.41	1.05	0.94
2-L28P15	1/2"	7/8"	3.41	1.12	1.00

† With Bleeder Ball Check – Reduces hose whip when disconnecting.

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.	Socket Dust Plug Part No.
2-RL	P-PDC-1-HK	P-SDC-1-HK
3-RL	P-PDC-2-HK	P-SDC-2-HK




Optional Seal Materials: 138-Silicone, 143-Fluorocarbon, 192-EPDM

3RL SERIES

SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
3-R15	1/4-18 NPTF	2.34	1.31	1.00
3-R20	3/8-18 NPTF	2.35	1.31	1.00
3-R25	1/2-14 NPTF	2.54	1.31	1.00
3-R30	3/4-14 NPTF	2.54	1.31	1.06

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
3-L10	1/8-27 NPTF	1.54	0.72	0.63
3-L15	1/4-18 NPTF	1.70	0.72	0.63
3-L15G†	1/4-18 NPTF	2.64	0.98	0.88
3-L20	3/8-18 NPTF	1.76	0.79	0.69
3-L20G†	3/8-18 NPTF	2.64	0.98	0.88
3-L25	1/2-14 NPTF	2.31	1.01	0.88
3-L25G†	1/2-14 NPTF	2.83	0.98	0.88
3-L30	3/4-14 NPTF	2.38	1.23	1.06
3-L30G†	3/4-14 NPTF	2.88	1.19	1.06

Part No.	Thread Size	Dimensions		
		A	B	HEX
3-R16	1/4-18 NPTF	2.29	1.31	1.00
3-R21	3/8-18 NPTF	2.35	1.31	1.00
3-R26	1/2-14 NPTF	2.63	1.31	1.00
3-R31A	3/4-14 NPTF	2.66	1.31	1.19


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
3-L16	1/4-18 NPTF	1.48	0.79	0.69
3-L16G†	1/4-18 NPTF	2.39	0.98	0.88
3-L21	3/8-18 NPTF	1.63	0.94	0.81
3-L21G†	3/8-18 NPTF	2.64	0.98	0.88
3-L26	1/2-14 NPTF	2.25	1.15	1.00
3-L26G†	1/2-14 NPTF	2.91	0.98	0.88
3-L31	3/4-14 NPTF	2.25	1.37	1.19

Part No.	Hose I.D.	Dimensions	
		A	B
3-R17	1/4"	2.82	1.31
3-R195	5/16"	2.85	1.31
3-R22	3/8"	2.89	1.31
3-R27	1/2"	2.81	1.31
3-R32	3/4"	3.66	1.31


Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
3-L17	1/4"	2.16	0.63
3-L195	5/16"	2.16	0.63
3-L195G†	5/16"	3.11	0.98
3-L22	3/8"	2.16	0.75
3-L22G†	3/8"	3.11	0.98
3-L27	1/2"	2.16	0.81
3-L27G†	1/2"	3.11	0.98
3-L32	3/4"	3.13	1.00
3-L32G†	3/4"	3.96	0.98

Part No.	Hose		Dimensions		
	I.D.	O.D.	A	B	HEX
3-R23D7	3/8"	5/8"	3.06	1.31	0.75
3-R23D9	3/8"	11/16"	3.06	1.31	0.81
3-R23D11	3/8"	3/4"	3.06	1.31	0.88
3-R23D13	3/8"	13/16"	3.06	1.31	0.94
3-R28P13	1/2"	13/16"	3.66	1.31	0.94
3-R28P15	1/2"	7/8"	3.66	1.31	1.00
3-R28P17	1/2"	15/16"	3.66	1.31	1.06
3-R33R23	3/4"	1 1/8"	3.79	1.31	1.25
3-R33R25	3/4"	1 3/16"	3.79	1.31	1.31
3-R33R27	3/4"	1 1/4"	3.79	1.31	1.38

Hose Clamp End Connections



Part No.	Hose		Dimensions		
	I.D.	O.D.	C	D	HEX
3-L23D7	3/8"	5/8"	2.45	0.84	0.75
3-L23D9	3/8"	11/16"	2.45	0.91	0.81
3-L23D11	3/8"	3/4"	2.45	0.98	0.88
3-L23D13	3/8"	13/16"	2.45	1.05	0.94
3-L23D15	3/8"	7/8"	2.45	1.12	1.00
3-L28P13	1/2"	13/16"	3.14	1.05	0.94
3-L28P15	1/2"	7/8"	3.14	1.12	1.00
3-L28P17	1/2"	15/16"	3.14	1.19	1.06
3-L28P19	1/2"	1"	3.14	1.26	1.13
3-L33R23	3/4"	1 1/8"	3.56	1.40	1.25
3-L33R25	3/4"	1 3/16"	3.56	1.47	1.31
3-L33R27	3/4"	1 1/4"	3.56	1.54	1.38

† With Bleeder Ball Check – Reduces hose whip when disconnecting.

Optional Seal Materials: 143-Fluorocarbon

SERIES FULL-BORE




The Full-Bore Series is a premium automatic one-way shutoff coupling. Two sleeves must be actuated in sequence to bleed off back pressure and release the connector, preventing accidental uncoupling. Available in 3/8" and 1/2" capacities.

FEATURES

- Pressure relieving feature fully vents downstream air, making connection/disconnection fast and easy, and eliminating hose whip
- Unique straight-through design eliminates restrictive springs and poppet valves, allowing unimpeded air flow
- Two-sleeve activation prevents accidental disconnect

APPLICATIONS & MARKETS

- Construction
- Railyards
- Maintenance & Repair
- General Pneumatics
- In-Plant/Industrial



Interchangeability

All Sizes	1/2" only
Industrial Interchange	A-A-59439 (former MIL-C-4109)

Materials

Socket:

- Carbon Steel
- Hard Drawn Steel Spring
- Buna-N Valve
- Stainless Steel Locking Balls

Plug:

- Carbon Steel

3/8" to 1/2" nominal
(9.52 mm to 12.70 mm)


-40° F to 200° F
-40° C to 93° C

Rated Pressure
250 psig (17 Bar)

Flow Capacity

Size	Ac †
3/8"	63 cfm
1/2"	101 cfm

† Air flow (scfm) with 5 psig pressure drop and 100 psig inlet pressure.




FULL-BORE SERIES

3/8" SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
23203-013	3/8" NPT	3.80	1.25	1.00
23203-014	1/2" NPT	2.80	1.25	1.00

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
40	1/4" NPT	1.88	0.72	0.63
42	3/8" NPT	1.88	0.79	0.69
44	1/2" NPT	2.09	1.01	0.88

Part No.	Thread Size	Dimensions		
		A	B	HEX
23203-300	3/8" NPT	3.17	1.25	1.00
23203-004	1/2" NPT	3.92	1.25	1.00


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
41	1/4" NPT	1.63	0.79	0.69
43	3/8" NPT	1.81	0.94	0.81
45	1/2" NPT	2.06	1.15	1.00

Part No.	Hose I.D.	Dimensions	
		A	B
23203-024	3/8"	4.36	1.25
23203-025	1/2"	4.48	1.25

Hose Stem End Connections




Part No.	Hose I.D.	Dimensions	
		C	D
404	1/4"	2.34	0.63
406	3/8"	2.34	0.63
408	1/2"	2.34	0.81

1/2" SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
23204-014	1/2" NPT	4.43	1.38	1.13
23204-015	3/4" NPT	4.67	1.38	1.13


Male End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
52	3/8" NPT	2.25	0.87	0.75
54	1/2" NPT	2.44	1.01	0.88
56	3/4" NPT	2.50	1.23	1.06

Part No.	Thread Size	Dimensions		
		A	B	HEX
23204-400	1/2" NPT	3.31	1.38	1.13
23204-005	3/4" NPT	3.30	1.38	1.13


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
53	3/8" NPT	2.06	0.94	0.81
55	1/2" NPT	2.34	1.15	1.00
57	3/4" NPT	2.44	1.37	1.19

Part No.	Hose I.D.	Dimensions	
		A	B
23204-025	1/2"	4.15	1.38
23204-026	3/4"	4.15	1.38

Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
59	3/8"	2.66	0.69
60	1/2"	2.66	0.75
61	3/4"	3.50	1.00

ACCESS EDUCATIONAL MATERIALS,
PRODUCT NEWS, CATALOG DOWNLOADS
AND MORE AT WWW.TUTHILL.COM.



SERIES 210&310




The 210 and 310 Interchange Series are 1/4" and 3/8" capacity automatic, pin-type couplings designed for one-way shutoff operation.

FEATURES

- Automatic push-to-connect
- Pin-lock design

APPLICATIONS & MARKETS

- Construction
- Maintenance & Repair
- In-Plant/Industrial
- Pneumatic Tools



Interchangeability

- ARO Interchange



Materials

Socket:

- Carbon Steel
- Hard Drawn Steel Spring
- Buna-N Valve Washer
- Alloy Steel Locking Pins

Plug:

- Carbon Steel



**1/4" to 3/8" nominal
(6.35 mm to 9.52 mm)**



**-40° F to 200° F
-40° C to 93° C**




**Rated Pressure
250 psig (17 Bar)**



Flow Capacity

Series	Ac †
210	19 cfm
310	50 cfm

† Air flow (scfm) with 5 psig pressure drop and 100 psig inlet pressure.






210&310 SERIES

210 SERIES SOCKETS

Part No.	Steel	Thread Size	Dimensions		
			A	B	HEX
210-212		1/4" NPT	1.95	1.02	0.69
210-213		3/8" NPT	1.91	1.02	0.69

Male End Connections




PLUGS

Part No.	Steel	Thread Size	Dimensions		
			C	D	HEX
2607		1/8" NPT	1.42	0.58	0.50
2608		1/4" NPT	1.68	0.65	0.56

Part No.	Steel	Thread Size	Dimensions		
			A	B	HEX
210		1/4" NPT	1.87	1.02	0.69
62210*		1/4" NPT	1.87	1.02	0.69


Female End Connections



Part No.	Steel	Thread Size	Dimensions		
			C	D	HEX
2609		1/4" NPT	1.55	0.79	0.69

Part No.	Steel	Hose I.D.	Dimensions	
			A	B
210-022		1/4"	2.39	1.02
210-215		3/8"	2.39	1.02

Hose Stem End Connections




Part No.	Steel	Hose I.D.	Dimensions	
			C	D
3946		1/4"	2.14	0.50
3947		5/16"	2.14	0.50
22238		3/8"	2.14	0.50

* Same as Model 210 but with brass valve

310 SERIES SOCKETS

Part No.	Steel	Thread Size	Dimensions		
			A	B	HEX
310-313		3/8" NPT	2.38	1.21	0.94


Male End Connections



Part No.	Steel	Thread Size	Dimensions		
			D	E	HEX
22239		1/4" NPT	1.91	0.72	0.63
3804		3/8" NPT	1.91	0.79	0.69

Part No.	Steel	Thread Size	Dimensions		
			A	B	HEX
310		3/8" NPT	2.10	1.21	0.94


Female End Connections



Part No.	Steel	Thread Size	Dimensions		
			D	E	HEX
3806		3/8" NPT	1.84	0.94	0.81

Part No.	Steel	Hose I.D.	Dimensions	
			A	B
310-222		3/8"	2.97	1.21

Hose Stem End Connections



Part No.	Steel	Hose I.D.	Dimensions	
			C	D
3807		3/8"	2.37	0.63

**TUTHILL COUPLING GROUP NOW OFFERS
DEMONSTRATION VIDEOS FEATURING NEW &
POPULAR PARTS. VISIT THE LEARNING ZONE AT
WWW.TUTHILL.COM TO SEE WHAT'S NEW!**



SERIES MS




The MS Series is an economical automatic one-way shutoff coupling. With steel pins securing the mating connector, the MS Series is available in 1/4" capacity.

FEATURES

- Automatic push-to-connect
- Pin-lock design

APPLICATIONS & MARKETS

- Construction
- Maintenance & Repair
- In-Plant/Industrial
- Pneumatic Tools



Interchangeability

- Industrial Interchange
- A-A-59439 (former MIL-C-4109)



Materials

Socket:

- Carbon Steel
- Hard Drawn Steel Spring
- Buna-N Valve Washer
- Alloy Steel Locking Pins

Plug:

- Carbon Steel



1/4" nominal (6.35 mm)



-40° F to 200° F
-40° C to 93° C




Rated Pressure
250 PSIG (17 Bar)



Flow Capacity

Series	Ac †
MS	26 cfm


† Air flow (scfm) with 5 psig pressure drop and 100 psig inlet pressure.



SOCKETS

Part No.	Thread Size	Dimensions		
		A	B	HEX
MSCM22-000	1/4" NPT	1.95	1.02	0.69
MSCM23-000	3/8" NPT	1.91	1.02	0.69

Male End Connections




PLUGS

Part No.	Thread Size	Dimensions		
		C	D	HEX
10	1/4" NPT	1.75	0.65	0.56
12	1/8" NPT	1.59	0.58	0.50
14	3/8" NPT	1.75	0.79	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
MSCF22-000	1/4" NPT	1.95	1.02	0.69
MSCM23-000	3/8" NPT	1.95	1.02	0.69


Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
11	1/4" NPT	1.63	0.79	0.69
13	1/8" NPT	1.47	0.65	0.56
15	3/8" NPT	1.69	0.94	0.81

Part No.	Hose I.D.	Dimensions	
		A	B
MSCH22-000	1/4"	2.39	1.02
MSCH23-000	3/8"	2.39	1.02

Hose Stem End Connections



Part No.	Hose I.D.	Dimensions	
		C	D
16	1/4"	2.22	0.50
17	3/8"	2.22	0.50

**CAN'T FIND WHAT YOU'RE LOOKING FOR?
VISIT WWW.TUTHILL.COM FOR PRODUCT
INFORMATION OR CALL YOUR LOCAL
DISTRIBUTOR.**



TWO-
WAY



Contents and Selector Chart



		Coupling Style			Body Size								Body Material				Locking Mechanism			Options				
		MANUAL CONNECT	PUSH-TO-CONNECT	SAFETY COUPLING	1/8 INCH	1/4 INCH	3/8 INCH	1/2 INCH	3/4 INCH	1 INCH	1¼ INCH	1½ INCH	2¼ INCH	BRASS	STEEL (Zinc/chromate Finish)	STAINLESS STEEL (303)	STAINLESS STEEL (316)	PLASTIC (Polypropylene)	BALL LOCK	THREADED SLEEVE	PLASTIC FINGERS	SLEEVE LOCK	SEAL MATERIALS (Various)	DUST CAP/PLUG
Coupling Series	Page																							
1-HK	47	●			●								●	●	●	●		●			●	●	●	
2-HK	47	●				●							●	●	●	●		●			●	●	●	
P2-HK	47	●				●											●			●		●	●	
3-HK	47	●					●						●	●	●	●		●			●	●	●	
4-HKP	47	●						●					●	●	●	●		●			●	●	●	
6-HKP	47	●							●				●	●	●	●		●			●	●	●	
8-HKP	47	●								●			●	●	●	●		●			●	●	●	
10-HK	50	●									●		●	●	●			●			●	●		
12-HK	50	●										●	●	●	●			●			●	●	●	
20-HK	50	●											●	●	●			●			●	●	●	
HKFR	52	●						●	●	●				●	●			●			★		●	
HA 15000	54	●				●	●	●	●	●				●				●					●	
FF	56/57		●	●		●	●	●	●	●				●				●			★	●	●	
96	58	●		●					●	●	●		●						●					
UP10	60	●				●								●				●			★		●	
WA 56000	61	●				●								●					●				●	
2-HKIG	63	●				●									●			●				●	●	
2-HKIL	63	●													●			●				●	●	
DB	64		●	●		●	●	●	●	●						●		●				●		

★ Sleeve Lock is Standard

SERIES HK 1-HK TO 8-HK




Series HK Couplings are the most versatile couplings available and are suitable for use with various liquids, chemicals, steam, gases and vacuum. Series HK couplings conform to the dimensional requirements of ISO 7241-1 Series B. Body sizes range from 1/8" to 1".

FEATURES

- The coupling that set the industry standard
- Multiple options make the HK our most versatile coupling series available
- Brass, steel and stainless steel construction available in all sizes; 1/4" body size is also available in polypropylene
- End connections are female NPTF, BSPP and SAE o-ring boss
- Heavy duty steel couplings for use in high impulse service available in most sizes
- Steam coupling available in 3/8" body size

APPLICATIONS & MARKETS

- Agriculture
- Military
- HVAC
- Hydraulic Tool
- Law Enforcement/Rescue
- Food and Beverage
- General Industry
- Chemical
- Trucks
- Construction
- Oil and Gas
- Aerospace
- Fluid Transfer
- Consumer Products
- Medical
- Transportation



Interchangeability

- ISO 7241-1 Series B



Materials

- Brass, zinc-plated steel, stainless steel or polypropylene (1/4" only) construction
- Stainless steel spring, balls and retaining ring
- Buna-N (Nitrile) seal
- PTFE back-up rings in steel and stainless steel sockets



1/8" to 1" nominal
(4.4 mm to 25.4 mm)



-40° F to 250° F
-40° C to 121° C
(with standard seal)





Rated Pressure Chart

Part Number	Body Size inches (mm)	Brass		Steel		Stainless Steel	
		PSI	BAR	PSI	BAR	PSI	BAR
1-HK	1/8 (4.4)	3,000	207	4,000	275	5,000	344
2-HK	1/4 (5.9)	2,700	345	5,000	255	3,700	255
3-HK	3/8 (7.8)	2,200	152	3,700	255	3,700	255
4-HKP	1/2 (10)	2,250	155	5,000	345	4,250	293
6-HKP	3/4 (17)	2,000	138	4,000	275	3,500	242
8-HKP	1 (19.6)	1,500	103	4,000	275	3,000	207
Part Number	Body Size inches (mm)	Polypropylene		Temperature Range			
		PSI	BAR				
P2-HK	1/4 (5.9)	50	4	+35° F to 150° F			




Flow Capacity





Socket



Plug

SOCKETS

Body Size (inch)	Part Number					Thread Size (female)			Dimensions (inches)		
	Brass	Steel		Stainless Steel		NPTF	BSPP	SAE	A	B	Across Flats
		Standard	High Impulse	303	316						
1/8	B1-H11	1-H11	—	LL1-H11	ML1-H11	1/8-27	—	—	1.91	0.98	0.56
1/8	—	1-H4	—	LL1-H4	—	—	—	7/16-20	2.06	0.98	0.69
1/4	B2-H16	2-H16	2-H16	LL2-H16	ML2-H16	1/4-18	—	—	2.26	1.14	0.75
1/4	B2-H16BS	2-H16BS	2-H16BS	LL2-H16BS	ML2-H16BS	—	1/4-19	—	2.31	1.14	0.75
1/4	—	2-H6	2-H6	LL2-H6	—	—	—	9/16-18	2.40	1.14	0.88
3/8	B3-H21	3-H21	3-H21C	LL3-H21	ML3-H21	3/8-18	—	—	2.56	1.42	0.88
3/8	B3-H21BS	3-H21BS	—	LL3-H21BS	ML3-H21BS	—	3/8-19	—	2.56	1.42	0.88
3/8	—	3-H8	3-H8C	LL3-H8	—	—	—	3/4-16	2.74	1.42	1.00
1/2	B4-HP26	4-HP26	4-HP26	LL4-HP26	ML4-HP26	1/2-14	—	—	2.96	1.86	1.13
1/2	B4-HP26BS	4-HP26BS	4-HP26BS	LL4-HP26BS	ML4-HP26BS	—	1/2-14	—	2.96	1.86	1.13
1/2	—	4-HP10	4-HP10	LL4-HP10	—	—	—	7/8-14	3.05	1.86	1.25
3/4	B6-HP31	6-HP31	6-HP31	LL6-HP31	ML6-HP31	3/4-14	—	—	3.48	2.22	1.31
3/4	B6-HP31BS	6-HP31BS	6-HP31BS	LL6-HP31BS	ML6-HP31BS	—	3/4-14	—	3.48	2.22	1.31
3/4	—	6-HP12	6-HP12	LL6-HP12	—	—	—	1 1/16-12	3.67	2.22	1.38
1	B8-HP36	8-HP36	8-HP36	LL8-HP36	ML8-HP36	1-1 1/2	—	—	4.13	2.61	1.75
1	B8-HP36BS	8-HP36BS	8-HP36BS	LL8-HP36BS	ML8-HP36BS	—	1-11	—	4.13	2.61	1.75
1	—	8-HP16	8-HP16	LL8-HP16	—	—	—	1 5/16-12	4.13	2.61	1.88

A = Overall Length B = Maximum Diameter

PLUGS

Body Size (inch)	Part Number					Thread Size (female)			Dimensions (inches)			
	Brass	Steel		Stainless Steel		NPTF	BSPP	SAE	C	D	E	HEX
		Standard	High Impulse	303	316							
1/8	B1-K11	1-K11	—	LL1-K11	ML1-K11	1/8-27	—	—	1.26	0.65	0.44	0.56
1/8	—	1-K4	—	LL1-K4	—	—	—	7/16-20	1.41	0.79	0.59	0.69
1/4	B2-K16	2-K16	2-K16C	LL2-K16	ML2-K16	1/4-18	—	—	1.52	0.87	0.56	0.75
1/4	B2-K16BS	2-K16BS	—	LL2-K16BS	ML2-K16BS	—	1/4-19	—	1.52	0.87	0.56	0.75
1/4	—	2-K6	2-K6C	LL2-K6	—	—	—	9/16-18	1.66	1.01	0.70	0.88
3/8	B3-K21	3-K21	3-K21C	LL3-K21	ML3-K21	3/8-18	—	—	1.76	1.01	0.61	0.88
3/8	B3-K21BS	3-K21BS	—	LL3-K21BS	ML3-K21BS	—	3/8-19	—	1.76	1.01	0.61	0.88
3/8	—	3-K8	3-K8C	LL3-K8	—	—	—	3/4-16	1.94	1.15	0.79	1.00
1/2	B4-KP26	4-KP26	4-KP26	LL4-KP26	ML4-KP26	1/2-14	—	—	2.03	1.30	0.76	1.13
1/2	B4-KP26BS	4-KP26BS	4-KP26BS	LL4-KP26BS	ML4-KP26BS	—	1/2-14	—	2.03	1.30	0.76	1.13
1/2	—	4-KP10	4-KP10	LL4-KP10	—	—	—	7/8-14	2.11	1.37	0.84	1.19
3/4	B6-KP31	6-KP31	6-KP31	LL6-KP31	ML6-KP31	3/4-14	—	—	2.36	1.52	0.71	1.31
3/4	B6-KP31BS	6-KP31BS	6-KP31BS	LL6-KP31BS	ML6-KP31BS	—	3/4-14	—	2.36	1.52	0.71	1.31
3/4	—	6-KP12	6-KP12	LL6-KP12	—	—	—	1 1/16-12	2.54	1.59	0.89	1.38
1	B8-KP36	8-KP36	8-KP36	LL8-KP36	ML8-KP36	1-11 1/2	—	—	2.85	1.88	0.97	1.63
1	B8-KP36BS	8-KP36BS	8-KP36BS	LL8-KP36BS	ML8-KP36BS	—	1-11	—	2.85	1.88	0.97	1.63
1	—	8-KP16	8-KP16	LL8-KP16	—	—	—	1 5/16-12	2.85	2.17	0.97	1.88

C = Overall Length D = Maximum Diameter E = Exposed Length when Connected

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.		Socket Dust Plug Part No.	
	Metal	Vinyl	Metal	Vinyl
1-HK	PDC-1-HK*	P-PDC-1-HK	SDC-1-HK*	P-SDC-1-HK
2-HK	PDC-2-HK*	P-PDC-2-HK	SDC-2-HK*	P-SDC-2-HK
3-HK	PDC-3-HK*	P-PDC-3-HK	SDC-3-HK*	P-SDC-3-HK
4-HK	PDC-4-HK**	P-PDC-4-HK	SDC-4-HK**	P-SDC-4-HK
6-HK	PDC-6-HK**	P-PDC-6-HK	SDC-6-HK**	P-SDC-6-HK
8-HK	PDC-8-HK**	P-PDC-8-HK	SDC-8-HK**	P-SDC-8-HK

* Brass ** Aluminum



SERIES HK 1-HK TO 8-HK

OPTIONS


- Non-valved socket and plug
- Bleeder-style plug
- Seals: PTFE, Neoprene, Fluorocarbon, Buna-N, EPDM and Kalrez (see Elastomer Selection Guide, page 82)
- Valve actuator in socket or plug
- Sleeve lock

Series P2-HK Plastic Coupling

The Series P2-HK coupling is intended for use with air, water and various chemicals at low pressure. It is designed for use where an economical, light weight, corrosion resistant coupling is desired. All components, except springs and seals, are molded from natural polypropylene with a UV inhibitor. Valve springs are 316 stainless steel. Fluorocarbon seals are standard. EPDM seals are optional.

Part No.	Thread Size NPTF	Dimensions			Part No.	Thread Size NPTF	Dimensions			
		A	B	HEX			C	D	E	HEX
PP2-H25F	1/4-18	2.38	1.45	0.88	PP2-K25F	1/4-18	1.65	1.01	0.67	0.88

E = Exposed length when connected




Series 3-HK Steam Coupling

The steam coupling has a large diameter flange on the sleeve to aid gripping while the user wears heavy gloves. EPDM seals are standard, and can be used with steam at temperatures up to 350°F. Options are BSPP threads, sleeve lock, EPDM seals for use with steam at temperatures above 350°F and fluorocarbon seals.

Part No.	Thread Size NPTF	Dimensions			Part No.	Thread Size NPTF	Dimensions			
		A	B	Across Flats			C	D	E	HEX
B3-H21Y	3/8-18	2.56	1.75	0.88	B3-K21-192	3/8-18	1.76	1.01	0.61	0.88


E = Exposed length when connected



Release Clamp with Chain


When fluid lines may be subjected to a damaging pull, couplings can be mounted to disconnect automatically, sealing both ends of a line against fluid loss. The socket sleeve can be anchored to a stationary bracket, either directly or with a chain. Excessive pull on the plug end of the line moves the socket body forward relative to the sleeve, and the plug is released without damage to the line. Release Clamp Assembly Kits are available for Series 1-HK through 8-HKP sockets.

Series	Kit Part No.
1-HK	1-HRC-K
2-HK	2-HRC-K
3-HK	3-HRC-K
4-HKP	4-HRC-K
6-HKP	6-HRC-K
8-HKP	8-HRC-K



Bleeder-Style Plugs & One-Way Shut-Off Conversion Via (VAA)

Bleeder-style plugs can be used on air lines to prevent hose whip when disconnecting a line by reducing the exhaust velocity of air. Bleeder-style plugs can be used on hydraulic lines to prevent static pressure from building up in disconnected lines. Valves of these plugs are manufactured such that a small leak path exists when the plug is disconnected. Bleeder-style plugs are available in Series 1-HK through 6-HKP.



Typical use of VAA option with series HK

Series	Plug Part No.	Valve Actuator
1-HK	B1-K11-VB	B1-K11-VAA
2-HK	B2-K16-VB	B2-K16-VAA
2-HK	2-K16C-VB	2-K16C-VAA
3-HK	B3-K21-VB	B3-K21-VAA
3-HK	3-K21-VB	3-K21-VAA
3-HK	3-K21C-VB	3-K21C-VAA
4-HKP	4-KP26-VB	4-KP26-VAA
6-HKP	B6-KP31-VB	B6-KP31-VAA
6-HKP	6-KP31-VB	6-KP31-VAA




Series 10-20 HK Couplings have the same features as the 1-8 HK, but have larger bodies and higher flow rates. Series HK couplings conform to the dimensional requirements of ISO 7241-1 Series B*. Body sizes range from 1¼" to 2½".

FEATURES

- Brass, steel and stainless steel construction available in all sizes
- End connections are female NPTF and BSPP
- Heavy duty steel couplings for use in high impulse service available in 12 HK and 20 HK

APPLICATIONS & INDUSTRIES

- Agriculture
- Hydraulic Tool
- General Industry
- Construction
- Fluid Transfer
- Chemical
- Oil and Gas
- Transportation
- Food and Beverage
- Trucks
- Nuclear



* No ISO Standard available for the 10HK.



Interchangeability
- ISO 7241-1 Series B*



Materials

- Brass, zinc-plated steel or stainless steel construction
- Stainless steel springs, balls and retaining rings
- Buna-N (Nitrile) seals



1-1/4" to 2-1/2" nominal
(31.75 mm to 63.5 mm)



-40° F to 250° F
-40° C to 121° C
(with standard seal)




Rated Pressure

Part Number	Body Size inches (mm)	Brass		Steel		Stainless Steel	
		PSI	BAR	PSI	BAR	PSI	BAR
10-HK	1¼ (26.7)	1,200	83	1,700	118	1,700	118
12-HK	1½ (35.1)	1,500	104	2,200	152	2,200	152
20-HK	2¾ (46.0)	700	49	1,500	104	1,500	104




Flow Capacity



SERIES HK

10-HK
12-HK
20-HK



SOCKETS

Body Size (inch)	Part Number				Thread Size (female)		Dimensions (inches)		
	Brass	Steel		303 Stainless Steel	NPTF	BSPP	A	B	HEX
		Standard	High Impulse						
1¼*	B10-H41	10-H41	—	LL10-H41	1¼-11½	—	4.51	2.73	2.38
1¼*	—	10-H41BS	—	LL10-H41BS	—	1¼-11	4.51	2.73	2.38
1½	B12-H41	12-H41	12-H41C	LL12-H41	1½-11½	—	4.82	3.23	2.38
1½	B12-H41BS	12-H41BS	12-H41CBS	LL12-H41BS	—	1½-11	4.82	3.23	2.38
1½	B12-H46	12-H46	12-H46C	LL12-H46	1½-11½	—	4.82	3.23	2.38
1½	B12-H46BS	12-H46BS	12-H46CBS	LL12-H46BS	—	1½-11	4.82	3.23	2.38
2½	B20-H51	20-H51	20-H51C	LL20-H51	2-11½	—	5.55	4.11	3.75
2½	B20-H51BS	20-H51BS	20-H51BS	LL20-H51BS	—	2-11	5.55	4.11	3.75
2½	B20-H56	20-H56	20-H56C	LL20-H56	2½-8	—	6.14	4.11	3.75
2½	B20-H56BS	20-H56BS	20-H56BS	LL20-H56BS	—	2½-11	6.14	4.11	3.75
2½	B20-H61	20-H61	20-H61C	LL20-H61	3-8	—	7.00	4.11	4.00
2½	B20-H61BS	20-H61BS	20-H61BS	LL20-H61BS	—	3-11	7.00	4.11	4.00

A = Overall Length B = Maximum Diameter

PLUGS

Body Size (inch)	Part Number				Thread Size (female)		Dimensions (inches)			
	Brass	Steel		303 Stainless Steel	NPTF	BSPP	C	D	E	HEX
		Standard	High Impulse							
1¼*	B10-K41	10-K41	—	LL10-K41	1¼-11½	—	4.25	2.73	2.33	2.38
1¼*	—	10-K41BS	—	LL10-K41BS	—	1¼-11	4.25	2.73	2.33	2.38
1½	B12-K41	12-K41	12-K41C	LL12-K41	1½-11½	—	4.76	3.02	2.67	2.38
1½	B12-K41BS	12-K41BS	12-K41CBS	LL12-K41BS	—	1½-11	4.76	3.02	2.67	2.38
1½	B12-K46	12-K46	12-K46C	LL12-K46	1½-11½	—	4.76	3.02	2.67	2.38
1½	B12-K46BS	12-K46BS	12-K46CBS	LL12-K46BS	—	1½-11	4.76	3.02	2.67	2.38
2½	B20-K51	20-K51	20-K51C	LL20-K51	2-11½	—	5.49	4.31	2.97	3.75
2½	B20-K51BS	20-K51BS	20-K51CBS	LL20-K51BS	—	2-11	5.49	4.31	2.97	3.75
2½	B20-K56	20-K56	20-K56C	LL20-K56	2½-8	—	6.08	4.31	3.56	3.75
2½	B20-K56BS	20-K56BS	20-K56CBS	LL20-K56BS	—	2½-11	6.08	4.31	3.56	3.75
2½	B20-K61	20-K61	20-K61C	LL20-K61	3-8	—	6.94	4.31	4.42	4.00
2½	B20-K61BS	20-K61BS	20-K61CBS	LL20-K61BS	—	3-11	6.94	4.31	4.42	4.00


C = Overall Length D = Maximum Diameter E = Exposed Length when Connected

* ISO 7241-1 Series B does not include 1-1/4 inch body size couplings; therefore, Series 10-HK is not covered by this standard


Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.	Socket Dust Plug Part No.
12-HK	PDC-12-HK*	SDC-12-HK*
20-HK	PDC-20-HK*	SDC-20-HK*

* Aluminum



Metal Dust Cap




Metal Dust Plug

SPECIAL ORDERING INSTRUCTIONS FOR HK SERIES

How to build a socket or plug part number with options:

Example: 4-HP26 - VAA - SL - 143



Notes:

- 1) The NV option should be specified for a socket and a plug when a non-valved coupling is desired. Non-valved Series 1-HK through 8-HKP plugs do not contain seals. Do not specify a seal material.
- 2) The VAA option should be specified for either a socket or a plug when a one-way coupling is desired. (Not available for series 10 HK)
- 3) The VB option can be ordered for Series 1-HK through 6-HKP plugs to prevent pressure build-up in disconnected hydraulic lines or to reduce hose whip when disconnecting pneumatic lines.
- 4) Series HK couplings are designed for use with elastomer seals. PTFE is not an elastomer. It is rigid and not resilient. Couplings with PTFE seals may leak and/or be difficult to connect. Force to connect may be reduced by heating connected couplings in hot water; then, cooling before disconnecting. PTFE seals are available for Series 1-HK through 8-HKP, except Series P2-HK.
- 5) The 146 seal option may be specified for fuels and hydraulic fluids that are known to cause standard Buna-N seals to swell excessively.
- 6) The 236 EPDM seal option should be ordered for use with steam at or above 350° F. The 192 EPDM seal option should be ordered for hot water above 180° F and steam below 350° F.
- 7) Some part numbers may be subject to minimum order quantities and/or available only by special quotation. Consult your local distributor.
- 8) High Impulse – The high strength steel and heat treatment used to give increased resistance to “brinelling” (indentations by locking balls in the plug groove).

VISIT WWW.TUTHILL.COM FOR A COMPLETE LISTING OF PARTS, INFORMATION DOWNLOADS AND MORE!



SERIES HKFR



The HKFR Series is a quick disconnect, hydraulic coupling, that is designed for hazardous BOP (Blow-Out Preventer) service in the Oil & Gas Industry. It meets or exceeds the ISO 7241-1 Series B standard.

FEATURES

- Easy visual verification: BOP designation is clearly marked on the socket and plug, along with a distinctive red socket sleeve and red plug wrench flats for simple identification
- Dependable: equipped with ball-locking technology that provides a consistent, positive connection
- Compact design: ideal for building panels where space is limited
- Easy to use: connect and disconnect quickly without tools and no risk of cross threading
- Safe: sleeve lock is standard which prevents accidental disconnects
- Environmental protection: two-way valve design minimizes fluid spillage

APPLICATIONS & MARKETS

- Oil & Gas



Interchangeability

- ISO 7241-1 Series B



Materials

- Steel
- Stainless Steel (ML8HFR36)



1/2" to 1" nominal
(12.7 mm to 25.4 mm)



Certified to 1300° F (700° C)

(see Lloyd's Register Certification below)



Rated Pressure Chart

Part Number	Body Size inches	Maximum Burst Pressure (Connected)		Minimum Burst Pressure (Connected)	
		PSI	BAR	PSI	BAR
4HFR26	1/2	7,000	482	28,000	1,931
6HFR26	3/4	5,000	344	18,150	1,251
8HFR26	1	5,000	344	20,000	1,379
ML8HFR36*	1	5,000	344	20,000	1,379

* Stainless Steel

Lloyd's Register Certification

All of the above items carry a Lloyd's Registry Certificate for fire conditions stated in API 16D and EUB Directive 35. These parts met the requirements that state couplings shall be capable of maintaining pressure when exposed to a 700° C (1,300° F) temperature for a five-minute period. Testing for this certification was conducted at the following pressures in the connected condition:



4HFR26 / 4KFR26: 3,000 PSI / 206 BAR
6HFR31 / 6KFR31: 3,000 PSI / 206 BAR
8HFR36 / 8KFR36: 4,000 PSI / 275 BAR
ML8HFR36 / ML8KFR36: 4,000 PSI / 275 BAR

SOCKETS

Part No.	Body Size	Thread Detail (Female)	Dimensions		
			A	B	Across Flats
4HFR26	1/4"	1/2-14 NPTF	2.96	1.86	1.13
6HFR26	3/4"	3/4-14 NPTF	3.48	2.22	1.31
8HFR26	1"	1-1½ NPTF	4.13	2.61	1.75
ML8HFR36*	1"	1-1½ NPTF	4.13	2.61	1.75

* Stainless Steel

Female End Connections



PLUGS

Part No.	Thread Size	Dimensions			
		C	D	E	HEX
4KFR26	1/2-14 NPTF	2.03	1.30	0.76	1.13
5HFR31	3/4-14 NPTF	2.36	1.52	0.71	1.31
8KFR36	1-1½ NPTF	2.85	1.88	0.97	1.63
ML8KFR36*	1-1½ NPTF	2.85	1.88	0.97	1.63

HA 15000 SERIES




The Series HA 15000 is a general purpose hydraulic and fluid transfer coupling that conforms to the dimensional requirements of ISO 7241-1 Series A. Body sizes range from 1/4" to 1".

FEATURES

- Ball lock
- Manual connect, disconnect
- Poppet valving
- Slim profile
- Zinc plated steel construction
- NPTF and BSPP end connections
- Available push-to-connect socket designed for bulkhead mounting (1/2" body size only)

APPLICATIONS & MARKETS

- Construction
- Agriculture
- General Industry
- Fluid Transfer



Interchangeability

- ISO 7241-1 Series A

Materials

- Zinc-plated steel construction
- Stainless steel spring, balls and retaining ring
- Buna-N (Nitrile) seal


1/4" to 1" nominal
(6.35 mm to 25.4 mm)

-4° F to 212° F
-20° C to 100° C


Rated Pressure

Body Size	PSI	BAR
1/4"	4,565	315
3/8"	4,565	315
1/2"	3,625	250
3/4"	3,625	250
1"	2,900	200

Flow Capacity



SERIES HA 15000



SOCKETS

Body Size (inch)	Part Number (Steel)	Thread Size (female)		Dimensions (inches)		
		NPTF	BSPP	A	B	Across Flats
1/4	HA 15211 00	1/4-18	—	1.89	0.98	0.75
1/4	HA 15011 00	—	1/4-19	1.89	0.98	0.75
3/8	HA 15221 00	3/8-18	—	2.21	1.18	0.91
3/8	HA 15021 00	—	3/8-19	2.21	1.18	0.91
1/2	HA 15231 00	1/2-14	—	2.64	1.49	1.06
1/2	HA 15031 00	—	1/2-14	2.64	1.49	1.06
1/2	HA 15236 00*	1/2-14	—	2.64	1.49	1.06
1/2	HA 15036 00*	—	1/2-14	2.64	1.49	1.06
3/4	HA 15241 00	3/4-14	—	3.25	1.88	1.38
3/4	HA 15041 00	—	3/4-14	3.25	1.88	1.38
1	HA 15251 00	1-11½	—	3.86	2.08	1.62
1	HA 15051 00	—	1-11	3.86	2.08	1.62

* Push-to-Connect Socket A = Overall Length B = Maximum Diameter

PLUGS


Body Size (inch)	Part Number (Steel)	Thread Size (female)		Dimensions (inches)			
		NPTF	BSPP	C	D	E	Hex
1/4	HA 15212 00	1/4-18	—	1.41	0.86	0.80	0.75
1/4	HA 15012 00	—	1/4-19	1.41	0.86	0.80	0.75
3/8	HA 15222 00	3/8-18	—	1.63	1.04	0.79	0.91
3/8	HA 15022 00	—	3/8-19	1.63	1.04	0.79	0.91
1/2	HA 15232 00	1/2-14	—	1.92	1.22	0.92	1.06
1/2	HA 15032 00	—	1/2-14	1.92	1.22	0.92	1.06
3/4	HA 15242 00	3/4-14	—	2.42	1.58	1.09	1.38
3/4	HA 15042 00	—	3/4-14	2.42	1.58	1.09	1.38
1	HA 15252 00	1-11½	—	2.81	1.85	1.19	1.62
1	HA 15052 00	—	1-11	2.81	1.85	1.19	1.62

C = Overall Length D = Maximum Diameter E = Exposed Length when Connected

Push-to-Connect Socket

Part Numbers
HA 15036 00 &
HA 15236 00

This system allows automatic connection and disconnection simply by pushing the plug into or pulling it out of the socket body. Pulling on the hose moves the socket body forward relative to the bulkhead mounted double-acting sleeve, and the plug is released without damage to the hose.



Dust Caps and Dust Plugs Accessories:

Body Size (inch)	Plug Dust Cap Part No.	Socket Dust Plug Part No.
1/4	HP 15112 00	HP 15111 00
3/8	HP 15122 00	HP 15121 00
1/2	HP 15132 00	HP 15131 00
3/4	HP 15142 00	HP 15141 00
1	HP 15152 00	HP 15151 00





The Series FF is a flat face dry break or minimum spill hydraulic coupling that meets or exceeds the ISO 16028 standard. FF series is ideal for applications where hydraulic spillage is a concern and interchangeability with other manufacturers is important. Body sizes are 1/4", 3/8", 1/2", 5/8", 3/4", and 1".

FEATURES

- Heavy knurled sleeve creates a non-slip grip
- Meets or exceeds ISO 16028 standard
- 5075 psi maximum operating pressure for all sizes (connected and disconnected)
- Push-to-connect
- Standard sleeve-locking device prevents accidental disconnection
- Color identification rings available to help prevent the crossing of lines

APPLICATIONS & MARKETS

- Agriculture
- Construction
- Hydraulic Tools
- Overhead Bucket Hoists
- Oil & Gas
- General Industry
- Chemical
- Trucks
- Skidsteer Loaders
- Injection Molding
- Railway
- Transportation
- Mining
- Public Utilities



Interchangeability

- ISO 16028



Materials

- Zinc plated steel with clear chromate and QPQ finish; RoHS Compliant
- Stainless steel spring and locking balls
- Buna-N (Nitrile) seal



1/4" to 1" nominal
(6.35 mm to 25.4 mm)









-4° F to 212° F
-20° C to 100° C




Rated Pressure
5075 psi (350 BAR)
maximum operating pressure



Flow Capacity
(see below)



SERIES FF



Socket

Plug

SOCKETS


Body Size	Part Number	Thread Size	Dimensions (inches)			
			Socket			Coupling Connected Length
			A	B	Hex Size	
1/4"	6FFS25BS	1/4" BSPP	2.13	1.06	0.87	3.7
	6FFS25	1/4" NPT	2.13	1.06	0.87	
	6FFS56UN	9/16" UNF	2.13	1.06	0.87	
3/8"	10FFS37BS	3/8" BSPP	2.68	1.26	1.06	4.61
	10FFS37	3/8" NPT	2.68	1.26	1.06	
	10FFS50BS	1/2" BSPP	2.8	1.26	1.06	
	10FFS50	1/2" NPT	2.8	1.26	1.06	4.84
	10FFS16FMET	M16 x 150	2.8	1.26	1.06	
	10FFS56UN	9/16" UNF	2.8	1.26	1.06	
	10FFS75UN	3/4" UNF	2.8	1.26	1.06	
	10FFS87UN	7/8" UNF	2.91	1.26	1.18	5.08
	10FFS56ORM*	9/16" UNF	3.11	1.26	0.94	5.47
	10FFS75ORM*	3/4" UNF	3.19	1.26	0.94	5.63
1/2"	12FFS50BS	1/2" BSPP	3.23	1.5	1.42	5.24
	12FFS50	1/2" NPT	3.23	1.5	1.42	
	12FFS75BS	3/4" BSPP	3.35	1.5	1.42	5.47
	12FFS75	3/4" NPT	3.35	1.5	1.42	
	12FFS75UN	3/4" UNF	3.23	1.5	1.42	
	12FFS87UN	7/8" UNF	3.35	1.5	1.42	
	12FFS106UN	1-1/16" UN	3.46	1.5	1.42	5.71

* = external thread

PLUGS

Body Size	Part Number	Thread Size	Dimensions (inches)			
			Plug			Coupling Connected Length
			C	D	Hex Size	
1/4"	6FFP25BS	1/4" BSPP	2.01	0.63	0.87	3.7
	6FFP25	1/4" NPT	2.01	0.63	0.87	
	6FFP56UN	9/16" UNF	2.01	0.63	0.87	
3/8"	10FFP37BS	3/8" BSPP	2.56	0.78	1.06	4.61
	10FFP37	3/8" NPT	2.56	0.78	1.06	
	10FFP50BS	1/2" BSPP	2.68	0.78	1.06	
	10FFP50	1/2" NPT	2.68	0.78	1.06	4.84
	10FFP16FMET	M16 x 150	2.68	0.78	1.06	
	10FFP56UN	9/16" UNF	2.68	0.78	1.06	
	10FFP75UN	3/4" UNF	2.68	0.78	1.06	
	10FFP87UN	7/8" UNF	2.8	0.78	1.18	5.08
	10FFP56ORM*	9/16" UNF	2.99	0.78	0.94	5.47
	10FFP75ORM*	3/4" UNF	3.07	0.78	0.94	5.63
1/2"	12FFP50BS	1/2" BSPP	2.68	0.96	1.42	5.24
	12FFP50	1/2" NPT	2.68	0.96	1.42	
	12FFP75BS	3/4" BSPP	2.8	0.96	1.42	5.47
	12FFP75	3/4" NPT	2.8	0.96	1.42	
	12FFP75UN	3/4" UNF	2.68	0.96	1.42	
	12FFP87UN	7/8" UNF	2.8	0.96	1.42	
	12FFP106UN	1-1/16" UN	2.91	0.96	1.42	5.71

* = external thread



Socket

Plug

SOCKETS

Body Size	Part Number	Thread Size	Dimensions (inches)			
			Socket			Coupling
			A	B	Hex Size	Connected Length
5/8"	16FFS50BS	1/2" BSPP	3.23	1.65	1.42	5.24
	16FFS50	1/2" NPT	3.23	1.65	1.42	
	16FFS75BS	3/4" BSPP	3.35	1.65	1.42	5.47
	16FFS75	3/4" NPT	3.35	1.65	1.42	
	16FFS75UN	3/4" UNF	3.23	1.65	1.42	5.24
	16FFS87UN	7/8" UNF	3.35	1.65	1.42	5.47
3/4"	16FFS106UN	1-1/16" UN	3.46	1.65	1.42	5.71
	19FFS75BS	3/4" BSPP	3.78	1.81	1.65	6.7
	19FFS75	3/4" NPT	3.78	1.81	1.65	
	19FFS100BS	1" BSPP	3.78	1.81	1.65	
	19FFS100	1" NPT	3.78	1.81	1.65	
	19FFS106UN	1-1/16" UN	3.78	1.81	1.65	
1"	19FFS131UN	1-5/16" UNF	3.78	1.81	1.65	7.28
	25FFS100BS	1" BSPP	4.06	2.17	2.17	
	25FFS100	1" NPT	4.06	2.17	2.17	
	25FFS125BS	1-1/4" BSPP	4.06	2.17	2.17	
	25FFS125	1-1/4" NPT	4.06	2.17	2.17	
	25FFS162UN	1-5/8" UN	4.06	2.17	2.17	

* = external thread

PLUGS

Body Size	Part Number	Thread Size	Dimensions (inches)			
			Plug			Coupling
			C	D	Hex Size	Connected Length
5/8"	16FFP50BS	1/2" BSPP	2.68	1.06	1.42	5.24
	16FFP50	1/2" NPT	2.68	1.06	1.42	
	16FFP75BS	3/4" BSPP	2.8	1.06	1.42	5.47
	16FFP75	3/4" NPT	2.8	1.06	1.42	
	16FFP75UN	3/4" UNF	2.68	1.06	1.42	5.24
	16FFP87UN	7/8" UNF	2.8	1.06	1.42	5.47
3/4"	16FFP106UN	1-1/16" UN	2.91	1.06	1.42	5.71
	19FFP75BS	3/4" BSPP	3.74	1.18	1.65	6.7
	19FFP75	3/4" NPT	3.74	1.18	1.65	
	19FFP100BS	1" BSPP	3.74	1.18	1.65	
	19FFP100	1" NPT	3.74	1.18	1.65	
	19FFP106UN	1-1/16" UN	3.74	1.18	1.65	
1"	19FFP131UN	1-5/16" UNF	3.74	1.18	1.65	7.28
	25FFP100BS	1" BSPP	4.09	1.42	2.17	
	25FFP100	1" NPT	4.09	1.42	2.17	
	25FFP125BS	1-1/4" BSPP	4.09	1.42	2.17	
	25FFP125	1-1/4" NPT	4.09	1.42	2.17	
	25FFP162UN	1-5/8" UN	4.09	1.42	2.17	

* = external thread

Dust Caps and Dust Plugs Accessories:

Body Size (inch)	Plug Dust Cap Part No.	Socket Dust Plug Part No.
1/4	PDC6FF	SDC6FF
3/8	PDC10FF	SDC10FF
1/2	PDC12FF	SDC12FF
5/8	PDC16FF	SDC16FF
3/4	PDC19FF	SDC19FF
1	PDC25FF	SDC25FF



Vinyl Dust Cap



Vinyl Dust Plug

SERIES 96



The Series 96 coupling is a heavy-duty wing nut coupling designed for use in hydraulic lines where dry break and minimum air inclusion are required. It is ideal for hydraulic dump trucks, oil field equipment, spreading equipment and applications requiring the ability to connect and/or disconnect under pressure. Body sizes are 3/4", 1" and 1 1/4".

FEATURES

- Flat face valve design
- Non-spill double shut-off with minimum air inclusion
- Connect/disconnect under pressure
- Corrosion resistant brass body
- Plugs can be bulkhead mounted
- Interchanges with other manufacturers' couplings

APPLICATIONS & INDUSTRIES

- Trucks
- Construction
- Oil and Gas
- Transportation



Interchangeability

- Other manufacturers' couplings



Materials

- Brass body (socket & plug)
- Zinc plated steel wing nut (socket)
- Stainless steel spring
- Buna-N (Nitrile) seal



3/4" to 1 1/4" nominal
(19.05 mm to 31.75 mm)



-40° F to 250° F
-40° C to 121° C





Rated Pressure

Body Series	PSI	BAR
3/4"	3,000	207
1"	3,000	207
1 1/4"	2,750	190



Flow Capacity




Bulkhead Mounting Flanges

Dust Caps and Dust Plugs Accessories

Body Series	Part No.	Diameters (inches)		Plug Dust Cap (Brass)	Socket Dust Plug (Brass)
		Bolt Hole A	Bolt Circle B		
3/4"	FL96-075	0.201	2.13	PDC-96-075	SDC-96-075
1"	FL96-100	0.201	2.38	PDC-96-100	SDC-96-100
1 1/4"	FL96-125	0.201	2.63	PDC-96-125	SDC-96-125

SOCKETS

Body Size	Part No.	Thread Size NPTF	Dimensions		
			A	B	Across Flats
3/4"	96-S31	3/4-14	3.10	4.06	1.15
1"	96-S36	1-11 1/2	3.79	4.45	1.44
1 1/4"	96-S41	1 1/4-11 1/2	3.95	5.35	1.78



PLUGS

Body Size	Part No.	Thread Size NPTF	Dimensions		
			C	D	Across Flats
3/4"	96-P31	3/4-14	3.13	1.75	1.31
1"	96-P36	1-11 1/2	3.55	2.02	1.56
1 1/4"	96-P41	1 1/4-11 1/2	3.71	2.38	1.88

UP10 SERIES




The Series UP10 is a high pressure hydraulic quick connect coupling designed to operate at pressures up to 10,000 psi. Unlike most high pressure hydraulic couplings that are screw-to-connect, the UP10 Series has a ball locking mechanism, making it quicker & easier to connect. Body size is 1/4".

FEATURES

- Ball lock
- Slim profile
- High strength steel construction
- Poppet valves with metal-to-metal sealing
- 1/4" & 3/8" male & female NPTF end connections
- Standard sleeve lock

APPLICATIONS & MARKETS

- Construction
- Hydraulic Tools



Interchangeability

- Proprietary



Materials

- High strength steel body and valve
- Stainless steel spring & balls
- Buna-N (Nitrile) seal
- PTFE back-up ring (socket)



1/4" nominal
(6.35 mm)




-40° F to 250° F
-40° C to 121° C



Rated Pressure
10,000 psi (700 BAR)



Flow Capacity



ONE-WAY

TWO-WAY

STRAIGHT-THRU

GAS

ACCESSORIES


SERIES UP10

SOCKETS

PLUGS

Part No.	Thread Size	Dimensions		
		A	B	HEX
UP10S-25M	1/4-18 NPTF	2.69	1.18	0.88
UP10S-37M	3/8-18 NPTF	2.69	1.18	0.88


Male End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
UP10P-25M	1/4-18 NPTF	2.59	0.97	0.88
UP10P-37M	3/8-18 NPTF	2.59	0.97	0.88

Part No.	Thread Size	Dimensions		
		A	B	HEX
UP10S-25F	1/4-18 NPTF	2.64	1.18	0.88
UP10S-37F	3/8-18 NPTF	2.69	1.18	0.88

Female End Connections



Part No.	Thread Size	Dimensions		
		C	D	HEX
UP10P-25F	1/4-18 NPTF	2.54	0.97	0.88
UP10P-37F	3/8-18 NPTF	2.59	0.97	0.88

Dust Caps and Dust Plugs Accessories:

Coupling Series	Plug Dust Cap Part No.	Socket Dust Plug Part No.
UP10	P-PDC-2-HK	P-SDC-2-HK



ACCESS EDUCATIONAL MATERIALS,
PRODUCT NEWS, CATALOG DOWNLOADS
AND MORE AT WWW.TUTHILL.COM.





Thread-to-Connect 10,000 PSI



WA 56000/HP3 SERIES



Series WA 56000 and HP3 are high pressure hydraulic screw together couplings designed to operate at pressures up to 10,000 psi. Their rugged design makes them suitable for use in hydraulic ram, pump and high impulse applications. The WA 56000 has a poppet valve and HP3 has a ball valve. Body sizes are 1/4" and 3/8".

FEATURES

- Threaded latching
- Rugged steel construction
- Poppet valves with elastomer seal standard in 1/4" coupling
- Poppet valves and ball valves available in 3/8" coupling
- Body size matches thread size. 1/4" and 3/8" body sizes do not interchange.

APPLICATIONS & MARKETS

- General Industry
- Oil & Gas
- Test Equipment
- Hydraulic Tools
- Construction


Dust Caps and Dust Plugs Accessories:

Body Size	Plug Dust Cap Part No.	Socket Dust Plug Part No.
1/4"	WA 56114 00	WA 56117 00
3/8"	WA 56124 00	WA 56127 00



Sockets – Male End Connections

Part No.	Valve Type	Thread Size NPTF	Dimensions		
			A	B	HEX
WA 56517 00	Poppet	1/4-18	2.36	1.12	0.88
WA 56527 00	Poppet	3/8-18	2.76	1.38	1.06
HP3SB37M	Ball	3/8-18	2.76	1.38	1.06



Plugs – Female End Connections

Part No.	Valve Type	Thread Size NPTF	Dimensions		
			C	D	Across Flats
WA 56514 00	Poppet	1/4-18	1.26	1.10	0.75
WA 56524 00	Poppet	3/8-18	1.52	1.26	0.91
HP3PB37F	Ball	3/8-18	1.52	1.26	0.91

Interchangeability

- Other manufacturers' couplings

Materials

- Zinc plated steel construction
- High strength steel ball valve
- Stainless steel spring
- WA: Buna-N (Nitrile) seal
- HP3: Urethane seal
- PTFE back-up ring (WA socket)


1/4" and 3/8" nominal
(6.35 mm and 9.525 mm)

-40° F to 250° F
-40° C to 121° C

Rated Pressure

Body Size	PSI	BAR
1/4"	10,000	690
3/8"	10,000	690

Flow Capacity



SERIES 2-HKIG&2-HKIL



Series 2-HKIG and 2-HKIL stainless steel couplings can be used with various liquids and gases. They are functionally identical, but do not interchange. They can be used where it is necessary to avoid crossing lines.

FEATURES

- Ball lock
- Manual operation
- Do not interchange with one another
- 1/4" body size
- All-stainless steel construction
- Sockets available with right-angle connection


APPLICATIONS & INDUSTRIES

- Chemical
- General Industry
- Military
- Food and Beverage
- Aerospace

2-HKIG



2-HKIL



Interchangeability

- Proprietary



Materials

- Stainless steel body, valve, sleeve, spring, balls and retaining ring
- Buna-N (Nitrile) seal; optional PTFE, Fluorocarbon, and EPDM
- Socket identification ring
 - 2-HKIG: White acetal
 - 2-HKIL: Black acetal



**1/4" nominal
(6.35 mm)**




**-40° F to 250° F
-40° C to 121° C**



**Rated Pressure
1500 psi (103 BAR)**



Flow Capacity





1/4" Nominal




2-HKIG&2-HKIL SERIES

SOCKETS

2-HKIG


PLUGS

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-HIG10	1/8-27 NPTF	2.18	1.06	0.81
2-HIG15	1/4-18 NPTF	2.31	1.06	0.81
2-HIG20	3/8-18 NPTF	2.31	1.06	0.81
2-HIG720*	7/16-20	2.27	1.06	0.81
2-HIG-LLRA720†*	7/16-20	2.09	1.06	—



Part No.	Thread Size	Dimensions		
		C	D	HEX
2-KIG-F15	1/4-18 NPTF	1.98	1.01	0.69
2-KIG-F20	3/8-18 NPTF	1.98	1.01	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-HIG11	1/8-27 NPTF	2.18	1.06	0.81
2-HIG16	1/4-18 NPTF	2.26	1.06	0.81




Part No.	Thread Size	Dimensions		
		C	D	HEX
2-KIG-F16	1/4-18 NPTF	1.84	1.01	0.69
2-KIG-F720*	7/16-20	1.61	1.01	0.69
2-KIG-F	9/16-18	1.17	1.01	0.88

SOCKETS

2-HKIL


PLUGS

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-HIL10	1/8-27 NPTF	2.18	1.06	0.81
2-HIL15	1/4-18 NPTF	2.31	1.06	0.81
2-HIL20	3/8-18 NPTF	2.31	1.06	0.81
2-HIL720*	7/16-20	2.27	1.06	0.81
2-HIL-LLRA720†*	7/16-20	2.09	1.06	—



Part No.	Thread Size	Dimensions		
		C	D	HEX
2-KIL-F15	1/4-18 NPTF	1.98	1.01	0.69
2-KIL-F20	3/8-18 NPTF	1.98	1.01	0.69

Part No.	Thread Size	Dimensions		
		A	B	HEX
2-HIL11	1/8-27 NPTF	2.18	1.06	0.81
2-HIL16	1/4-18 NPTF	2.26	1.06	0.81



Part No.	Thread Size	Dimensions		
		C	D	HEX
2-KIL-F16	1/4-18 NPTF	1.84	1.01	0.69
2-KIL-F720*	7/16-20	1.61	1.01	0.69
2-KIL-F	5/8-18	1.17	1.01	0.88

* 1/4" SAE Flare † Right-Angle End Connection

Dust Caps Accessories:

Coupling Series	Plug Dust Cap Part No.
2-HKIG	P-PDC-2-HK
2-HKIL	P-PDC-2-HK



Optional Seal Materials: 115-PTFE, 143-Fluorocarbon, 192-EPDM

SERIES DB



The Series DB is designed for fluid handling where minimum spillage and minimum air inclusion are required. Couplings in this series are constructed of 316L stainless steel, which makes them suitable for use in cooling systems, chemical, pharmaceutical and food processing industries. Unique interchange prevents the crossing of lines (except 3/8" size). Body sizes range from 1/4" to 1".

FEATURES

- Ball lock
- Push-to-connect
- Minimal fluid loss when disconnecting
- Minimal air inclusion when connecting
- High flow capacity
- NPTF and BSPP threads available

Spillage & Air Inclusion


Body Size	Spillage Max. per Disconnect	Air Inclusion Max. per Connect
1/4"	0.010 ml	0.005 ml
3/8"	0.016 ml	0.010 ml
1/2"	0.020 ml	0.020 ml
3/4"	0.030 ml	0.100 ml
1"	0.035 ml	0.126 ml

APPLICATIONS & INDUSTRIES

- Fluid Transfer
- Chemical
- Transportation
- Nuclear
- Food and Beverage
- Oil and Gas
- Military
- Cooling Systems
- Pharmaceutical
- Medical Equipment
- Consumer Products
- Aerospace

SOCKETS

Body Size (inch)	Part No.	Thread Size (Female)	Dimensions		
			A	B	HEX
1/4	2DBS-25F	1/4-18 NPTF	1.98	1.02	0.88
1/4	2DBS-25FBS	1/4-19 BSPP	1.98	1.02	0.88
3/8	3DBS-37F	3/8-18 NPTF	2.36	1.27	1.06
3/8	3DBS-37FBS	3/8-19 BSPP	2.36	1.27	1.06
1/2	4DBS-50F	1/2-14 NPTF	2.52	1.59	1.38
1/2	4DBS-50FBS	1/2-14 BSPP	2.52	1.59	1.38
3/4	6DBS-75F	3/4-14 NPTF	3.21	2.00	1.62
3/4	6DBS-75FBS	3/4-14 BSPP	3.21	2.00	1.62
1	8DBS-100F	1-11½ NPTF	3.52	2.25	1.81
1	8DBS-100FBS	1-11 BSPP	3.52	2.25	1.81



Interchangeability

- ISO 16028 (3/8" only)
- Proprietary (All other sizes)

Materials

- 316L stainless steel construction
- Fluorocarbon and EPDM seals, optional Kalrez or other seal materials upon request


1/4" to 1" nominal
(6.35 mm to 19.6 mm)

-4° F to 212° F
-20° C to 100° C

Rated Pressure

Body Size	Socket		Plug		Connected	
	PSI	BAR	PSI	BAR	PSI	BAR
1/4"	2,030	140	2,755	190	2,755	190
3/8"	2,030	140	2,610	180	2,610	180
1/2" - 1"	1,450	100	2,030	140	2,030	140

Flow Capacity



PLUGS

Body Size (inch)	Part No.	Thread Size (Female)	Dimensions		
			C	D	HEX
1/4	2DBP-25F	1/4-18 NPTF	1.65	1.00	0.87
1/4	2DBP-25FBS	1/4-19 BSPP	1.65	1.00	0.87
3/8	3DBP-37F	3/8-18 NPTF	2.42	1.05	0.91
3/8	3DBP-37FBS	3/8-19 BSPP	2.42	1.05	0.91
1/2	4DBP-50F	1/2-14 NPTF	2.63	1.37	1.18
1/2	4DBP-50FBS	1/2-14 BSPP	2.63	1.37	1.18
3/4	6DBP-75F	3/4-14 NPTF	3.19	1.73	1.50
3/4	6DBP-75FBS	3/4-14 BSPP	3.19	1.73	1.50
1	8DBP-100F	1-11½ NPTF	3.52	2.08	1.81
1	8DBP-100FBS	1-11 BSPP	3.52	2.08	1.81



Straight Through

Contents and Selector Chart



STRAIGHT THROUGH

Coupling Series	Page	Body Size										Body Material				Locking Mechanism		Options		
		1/8 INCH	1/4 INCH	3/8 INCH	1/2 INCH	3/4 INCH	1 INCH	1 1/4 INCH	1 1/2 INCH	2 INCH	2 1/2 INCH	BRASS	STEEL (Plugs Only)	STAINLESS STEEL (303)	PLASTIC (Polypropylene)	BALL LOCK	PLASTIC FINGERS	SLEEVE LOCK	SEAL MATERIALS (Various)	DUST CAP/PLUG
1-ST	68/69	●										●	●	●		●		●	●	
2-ST	68/69		●									●	●	●		●		●	●	▼
3-ST	68/69			●								●	●	●		●		●	●	▼
4-ST	68/69				●							●	●	●		●		●	●	
6-ST	68/69					●						●	●	●		●		●	●	◆
8-ST	68/69						●					●	●	●		●		●	●	★
10-ST	68/69							●				●	●	●		●		●	●	★
12-ST	68/69								●			●	●	●		●		●	●	
16-ST	68/69									●		●	●	●		●		●	●	
20-ST	68/69										●	●	●			●		●	●	
P2-ST	70		●												●		●			
P3-ST	70			●											●		●			
Flo-Temp	72		●	●	●							●	●			●				

▼ Socket Dust Plug Only

◆ Socket Dust Plug and Dust Cap

★ Plug Dust Cap Only



Series ST straight through couplings are designed for use where minimum pressure drop is required and valving is not needed. They are well suited for use on pressure wash, steam and carpet cleaning equipment, and many fluid transfer systems. Body sizes range from 1/8" to 2 1/2".

FEATURES



- Ball lock
- Manual operation
- Smooth bore permits free flow of liquid or gas
- Male and female NPTF, BSPP and hose stem connections

APPLICATIONS & MARKETS

- General Industry
- Fluid Transfer
- Chemical
- Food and Beverage
- Injection Molding
- Marine
- Military
- Carpet Cleaning
- Steam Cleaning
- Medical
- Food and Beverage
- Breathing Equipment
- Pressure Wash
- Cooling Systems



Flow Capacity



Interchangeability

- Other manufacturers' ST style couplings



Materials

- Brass or 303 stainless steel socket
- Stainless steel spring, balls and retaining ring
- Brass, zinc plated steel and 303 stainless steel plug
- High impulse heat treated 416 stainless steel plugs available in 1/4" and 3/8" body sizes
- Buna-N (Nitrile) seal; PTFE (1-ST through 8-ST), Neoprene, Fluorocarbon (FKM) and EPDM available



1/8" to 2 1/2" nominal
(3.175 mm to 63.5 mm)




-40° F to 250° F
-40° C to 121° C



Rated Pressure*

Series	Body Size	Brass Socket Brass Plug		Brass Socket Steel Plug		Stainless Steel Socket & Plug	
		PSI	BAR	PSI	BAR	PSI	BAR
1-ST	1/8"	2,800	193	3,400	234	4,200	290
2-ST	1/4"	5,200	359	5,500	379	7,500	517
3-ST	3/8"	2,800	193	4,200	290	6,300	434
4-ST	1/2"	2,200	152	3,500	241	3,600	248
6-ST	3/4"	1,700	117	2,100	145	3,000	207
8-ST	1"	1,300	90	2,000	138	2,000	138
10-ST	1 1/4"	1,700	117	2,700	186	2,200	152
12-ST	1 1/2"	1,400	97	2,200	152	2,500	172
16-ST	2"	1,400	97	2,200	152	1,500	103
20-ST	2 1/2"	900	62	1,500	103	-	-


* Pressure ratings are for sockets and plugs with threaded end connections. Pressure ratings of couplings with hose stems may be significantly lower, and will depend on the type of hose and the method of clamping. Refer to hose manufacturer's end connection pressure ratings. The best way to determine suitability for an application is to run pressure testing under controlled conditions.



SERIES ST


SOCKETS

Male End Connections



Body Size	Part Number		Thread Size		Dimensions		
	Brass	Stainless	NPTF	BSPP	A	B	Hex
1/8	1-S10	LL1-S10	1/8-27	—	1.06	0.72	0.56
1/8	1-S10BS	LL1-S10BS	—	1/8-28	1.08	0.72	0.56
1/4	2-S15	LL2-S15	1/4-18	—	1.72	0.97	0.81
1/4	2-S15BS	LL2-S15BS	—	1/4-19	1.56	0.97	0.81
3/8	3-S20	LL3-S20	3/8-18	—	1.75	1.16	1.00
3/8	3-S20BS	LL3-S20BS	—	3/8-19	1.71	1.16	1.00
1/2	4-S25	LL4-S25	1/2-14	—	2.03	1.34	1.13
1/2	4-S25BS	LL4-S25BS	—	1/2-14	1.85	1.34	1.13
3/4	6-S30	LL6-S30	3/4-14	—	2.22	1.72	1.44
3/4	6-S30BS	—	—	3/4-14	2.11	1.72	1.44
1	8-S35	—	1-11½	—	2.53	2.03	1.75
1	8-S35BS	—	—	1-11	2.43	2.03	1.75


Female End Connections



Body Size	Part Number		Thread Size		Dimensions		
	Brass	Stainless	NPTF	BSPP	A	B	Hex
1/8	1-S11	LL1-S11	1/8-27	—	1.06	0.72	0.56
1/8	1-S11BS	LL1-S11BS	—	1/8-28	1.03	0.72	0.56
1/4	2-S16	LL2-S16	1/4-18	—	1.50	0.97	0.81
1/4	2-S16BS	LL2-S16BS	—	1/4-19	1.50	0.97	0.81
3/8	3-S21	LL3-S21	3/8-18	—	1.59	1.16	1.00
3/8	3-S21BS	LL3-S21BS	—	3/8-19	1.59	1.16	1.00
1/2	4-S26	LL4-S26	1/2-14	—	1.91	1.34	1.13
1/2	4-S26BS	LL4-S26BS	—	1/2-14	1.91	1.34	1.13
3/4	6-S31	LL6-S31	3/4-14	—	2.06	1.72	1.44
3/4	6-S31BS	LL6-S31BS	—	3/4-14	2.06	1.72	1.44
1	8-S36	LL8-S36	1-11½	—	2.33	2.03	1.75
1	8-S36BS	LL8-S36BS	—	1-11	2.33	2.03	1.75
1¼	10-S41*	LL10-S41	1¼-11½	—	2.44	2.50	2.00
1¼	10-S41BS*	—	—	1¼-11	2.51	2.50	2.00
1½	12-S46*	LL12-S46	1½-11½	—	2.88	3.13	2.63
1½	12-S46BS*	LL12-S46BS	—	1½-11	2.88	3.13	2.63
2	16-S51*	LL16-S51	2-11½	—	3.09	3.75	3.00
2	16-S51BS*	LL16-S51BS	—	2-11	3.30	3.75	3.00
2½	20-S56*	—	2½-8	—	3.44	4.50	3.50

* With Steel Sleeve


Hose Stem Connections




Body Size	Part Number		Hose I.D.	Dimensions	
	Brass	Stainless		A	B
1/8	1-S12	LL1-S12	3/16"	1.41	0.72
1/8	1-S17	LL1-S17	1/4"	1.41	0.72
1/4	2-S17	LL2-S17	1/4"	2.10	0.97
3/8	3-S22	LL3-S22	3/8"	2.09	1.16
1/2	4-S27	LL4-S27	1/2"	2.19	1.34
3/4	6-S32	LL6-S32	3/4"	3.19	1.72
1	8-S37	LL8-S37	1"	3.32	2.03

PLUGS


Male End Connections



Female End Connections



Hose Stem Connections



Body Size (inch)	Part Number			Thread Size (female)		Dimensions (inches)		
	Brass	Steel	Stainless	NPTF	BSPP	C	D	Hex
1/8	B1-T10	1-T10	LL1-T10	1/8-27	—	1.06	0.51	0.44
1/8	B1-T10BS	—	—	—	1/8-28	0.97	0.65	0.56
1/8	B1-T15	1-T15	—	1/4-18	—	1.22	0.65	0.56
1/4	B2-T15	2-T15	LL2-T15	1/4-18	—	1.56	0.65	0.56
1/4	—	—	HL2-T15*	1/4-18	—	1.56	0.65	0.56
1/4	B2-T15BS	2-T15BS	LL2-T15BS	—	1/4-19	1.46	0.87	0.75
3/8	B3-T20	3-T20	LL3-T20	3/8-18	—	1.69	0.79	0.69
3/8	—	—	HL3-T20*	3/8-18	—	1.69	0.79	0.69
3/8	B3-T20BS	3-T20BS	LL3-T20BS	—	3/8-19	1.59	1.01	0.88
1/2	B4-T25	4-T25	LL4-T25	1/2-14	—	2.01	1.01	0.88
1/2	B4-T25BS	4-T25BS	LL4-T25BS	—	1/2-14	1.82	1.15	1.00
3/4	B6-T30	6-T30	LL6-T30	3/4-14	—	2.20	1.23	1.06
3/4	B6-T30BS	—	LL6-T30BS	—	3/4-14	2.08	1.44	1.25
1	B8-T35	8-T35	LL8-T35	1-11½	—	2.49	1.59	1.38
1	B8-T35BS	—	—	—	1-11	2.36	2.02	1.75
1¼	B10-T40	10-T40	LL10-T40	1¼-11½	—	2.72	2.02	1.75
1¼	B10-T40BS	—	—	—	1¼-11	2.55	2.31	2.00
1½	B12-T45	12-T45	—	1½-11½	—	3.31	2.60	2.25
1½	B12-T45BS	—	—	—	1½-11	3.19	2.60	2.25
2	B16-T50	16-T50	LL16-T50	2-11½	—	3.50	3.18	2.75
2	—	—	LL16-T50BS	—	2-11	3.54	3.18	2.75
2½	B20-T55	—	—	2½-8	—	4.24	3.75	3.25

Body Size (inch)	Part Number			Thread Size (female)		Dimensions (inches)		
	Brass	Steel	Stainless	NPTF	BSPP	C	D	Hex
1/8	B1-T11	1-T11	LL1-T11	1/8-27	—	0.97	0.58	0.50
1/8	B1-T11BS	—	LL1-T11BS	—	1/8-28	0.97	0.65	0.56
1/4	B2-T16	2-T16	LL2-T16	1/4-18	—	1.45	0.79	0.69
1/4	—	—	HL2-T16*	1/4-18	—	1.45	0.79	0.69
1/4	B2-T16BS	2-T16BS	LL2-T16BS	—	1/4-19	1.45	0.87	0.75
3/8	B3-T21	3-T21	LL3-T21	3/8-18	—	1.63	0.94	0.81
3/8	—	—	HL3-T21*	3/8-18	—	1.63	0.94	0.81
3/8	B3-T21BS	3-T21BS	LL3-T21BS	—	3/8-19	1.63	1.01	0.88
1/2	B4-T26	4-T26	LL4-T26	1/2-14	—	1.92	1.15	1.00
1/2	B4-T26BS	4-T26BS	LL4-T26BS	—	1/2-14	1.92	1.23	1.06
3/4	B6-T31	6-T31	LL6-T31	3/4-14	—	2.01	1.37	1.19
3/4	B6-T31BS	—	LL6-T31BS	—	3/4-14	2.01	1.52	1.31
1	B8-T36	8-T36	LL8-T36	1-11½	—	2.21	1.80	1.56
1	B8-T36BS	8-T36BS	LL8-T36BS	—	1-11	2.23	1.80	1.56
1¼	B10-T41	10-T41	LL10-T41	1¼-11½	—	2.34	2.31	2.00
1¼	B10-T41BS	—	—	—	1¼-11	2.53	2.31	2.00
1½	B12-T46	12-T46	LL12-T46	1½-11½	—	2.88	2.60	2.25
1½	B12-T46BS	—	—	—	1½-11	2.88	2.60	2.25
2	B16-T51	16-T51	—	2-11½	—	3.03	3.18	2.75
2	B16-T51BS	—	—	—	2-11	3.25	3.18	2.75
2½	B20-T56	20-T56	—	2½-8	—	3.37	3.75	3.25

* High impulse heat treated 416 stainless steel

Body Size (inch)	Part Number			Hose I. D.	Dimensions (inches)	
	Brass	Steel	Stainless		C	D Ø
1/8	B1-T12	—	LL1-T12	3/16"	1.28	0.44
1/8	B1-T17	—	LL1-T17	1/4"	1.28	0.44
1/4	B2-T17	2-T17	LL2-T17	1/4"	1.93	0.56
3/8	B3-T22	3-T22	LL3-T22	3/8"	2.09	0.69
1/2	B4-T27	4-T27	LL4-T27	1/2"	2.17	0.88
3/4	B6-T32	6-T32	LL6-T32	3/4"	3.17	1.19
1	B8-T37	8-T37	—	1"	3.28	1.50

Dust Caps and Dust Plugs Accessories:



Series	Plug Dust Cap (Vinyl)	Socket Dust Plug (Vinyl)
2-ST	—	P-SDC-1-HK
3-ST	—	P-SDC-2-HK
6-ST	P-PDC-4-HK	P-SDC-4-HK
8-ST	P-PDC-6-HK	—
10-ST	P-PDC-8-HK	—

SERIES P2-ST&P3-ST



Series P2-ST and P3-ST couplings have the same design as the ST, but with polypropylene construction, specifically designed for use with medical equipment. They can also be used in a variety of low pressure fluid transfer applications.

FEATURES

- Interchange with 2-ST and 3-ST
- Excellent chemical resistance
- Light weight

APPLICATIONS & INDUSTRIES

- Medical
- Chemical
- Fluid Transfer
- Pharmaceutical



Interchangeability

- 2-ST and 3-ST



Materials

- Polypropylene construction
- Buna-N (Nitrile) seal



1/4" to 3/8" nominal
(6.35 mm to 9.525 mm)



-4° F to 176° F
-20° C to 80° C



Rated Pressure


Temperature*	PSI	BAR
75°	110	8
200°	30	2

*235° F maximum sterilization temperature

SOCKETS

PLUGS

Series	Part No.	Hose I.D.	Dimensions	
			A	B
P2-ST	P2-STs-25H	1/4"	2.07	1.12
Each P2-ST socket uses one Part No. 902-7 o-ring.				
P3-ST	P3-STs-37H	3/8"	2.61	1.37
Each P3-ST socket uses one Part No. 902-10-199 o-ring.				



Series	Part No.	Thread Size	Dimensions		
			C	D	HEX
P2-ST	P2-STP-25M	1/4-18 NPTF	1.56	0.65	0.56
P3-ST	P3-STP-25M	1/4-18 NPTF	1.69	0.79	0.69
P3-ST	P3-STP-37M	3/8-18 NPTF	1.69	0.79	0.69

Series	Part No.	Hose I.D.	Dimensions		
			C	D	HEX
P3-ST	P3-STP-37H	3/8"	2.16	0.79	0.69

CAN'T FIND WHAT YOU'RE LOOKING FOR?
VISIT WWW.TUTHILL.COM FOR PRODUCT
INFORMATION OR CALL YOUR LOCAL
DISTRIBUTOR .





Straight Through

200
300
500

FLO-TEMP SERIES



Flo-Temp couplings provide the flow needed to cool or heat injection molds and die casting dies. Sockets are available non-valved for maximum flow and valved to prevent fluid loss when disconnected. Flo-Temp couplings can be used with water-glycol, hot water and hot oil. Body sizes are 1/4", 3/8" and 1/2".

FEATURES

- Non-valved straight through models for maximum flow
- Valved sockets for automatic shut-off when line is disconnected
- Sockets available with straight, 90° or 45° hose stems or without hose stem
- Brass plugs with male pipe thread for recessed mounting to avoid damage to plugs when molds are being changed or stored

APPLICATIONS & INDUSTRIES

- Injection Molding
- Heating/Cooling

REPLACEMENT PARTS

Description	Part Number		
	Series 200	Series 300	Series 500
Seal	WFT-200-228	WFT-300-228	WFT-500-228
Valve	VFT-200	VFT-300	VFT-500
Valve O-Ring	902-3-143	903-8-143	914-3-143
Valve Spring	VSFT-200	VS-3000	VSFT-500



Interchangeability

- Other manufacturers' coolant line couplings



Materials

- Brass socket construction
- Stainless steel spring and locking balls
- Fluorocarbon seal (-30° F to +450° F)
- Brass plug



1/4" to 1/2" nominal
(6.35 mm to 12.7 mm)




-30° F to 450° F
-34° C to 232° C



Rated Pressure
200 psi / 14 BAR




Flow Capacity



SERIES FLO-TEMP


200
300
500

SOCKETS



Without Hose Stem

Body Size (inch)	Part Number	Dimensions (inches)			Thread Size NPTF
		A	B	HEX	
1/4	LNFT-200	1.68	0.67	0.56	1/8-27
3/8	LNFT-300	2.18	0.89	0.75	1/4-18
1/2	LNFT-500	2.00	1.17	1.13	1/2-14




Straight Hose Stem

Body Size (inch)	Part Number		Hose I.D.	Dimensions (inches)		
	Non-Valved	Valved		A	B	C
1/4	FTS-204	FTS-204V	1/4"	1.20	0.67	2.25
1/4	FTS-204HP*	FTS-204VHP*	1/4"	1.20	0.67	2.09
1/4	FTS-205	FTS-205V	5/16"	1.20	0.67	2.09
1/4	FTS-206	FTS-206V	3/8"	1.20	0.67	2.25
1/4	FTS-206HP*	FTS-206VHP*	3/8"	1.20	0.67	2.34
3/8	FTS-306	FTS-306V	3/8"	1.60	0.91	2.68
3/8	FTS-306HP*	FTS-306VHP*	3/8"	1.61	0.89	2.75
3/8	FTS-308	FTS-308V	1/2"	1.61	0.88	2.82
3/8	FTS-308HP*	FTS-308VHP*	1/2"	1.61	0.88	2.82
1/2	FTS-504	FTS-504V	1/2"	2.25	1.18	3.42
1/2	FTS-504HP*	FTS-504VHP*	1/2"	2.25	1.18	3.62
1/2	FTS-506	FTS-506V	3/4"	2.22	1.18	3.85
1/2	FTS-506HP*	FTS-506VHP*	3/4"	2.22	1.18	4.35

*Part numbers with HP suffix have push-on hose barb. All other FTS part numbers have standard hose barb.

90° Hose Stem

Body Size (inch)	Part Number		Hose I.D.	Dimensions (inches)		
	Non-Valved	Valved		A	B	C
1/4	FTS-214	FTS-214V	1/4"	1.36	0.67	2.17
1/4	FTS-214HP*	FTS-214VHP*	1/4"	1.18	0.67	1.76
1/4	FTS-215	FTS-215V	5/16"	1.18	0.67	1.76
1/4	FTS-216	FTS-216V	3/8"	1.17	0.67	1.76
1/4	FTS-216HP*	FTS-216VHP*	3/8"	1.17	0.67	1.76
3/8	FTS-316	FTS-316V	3/8"	1.60	0.88	2.43
3/8	FTS-316HP*	FTS-316VHP*	3/8"	1.60	0.88	2.43
3/8	FTS-318	FTS-318V	1/2"	1.60	0.88	2.43
3/8	FTS-318HP*	FTS-318VHP*	1/2"	1.60	0.88	2.43




45° Hose Stem

Body Size (inch)	Part Number		Hose I.D.	Dimensions (inches)		
	Non-Valved	Valved		A	B	C
1/4	FTS-224	FTS-224V	1/4"	1.17	0.67	2.40
1/4	FTS-224HP*	FTS-224VHP*	1/4"	1.17	0.67	2.40
1/4	FTS-225	FTS-225V	5/16"	1.17	0.67	2.40
1/4	FTS-226	FTS-226V	3/8"	1.17	0.67	2.40
1/4	FTS-226HP*	FTS-226VHP*	3/8"	1.17	0.67	2.40
3/8	FTS-326	FTS-326V	3/8"	1.80	0.90	3.70
3/8	FTS-326HP*	FTS-326VHP*	3/8"	1.80	0.90	3.17
3/8	FTS-328	FTS-328V	1/2"	1.60	0.90	3.17
3/8	FTS-328HP*	FTS-328VHP*	1/2"	1.60	0.90	3.17


PLUGS

Male Pipe Thread



Body Size (inch)	Part Number	Thread Size	Dimensions (inches)			Installation Recess	
			D	E	HEX	Dia.	Depth
1/4	FTP-251	1/8-27 NPTF	0.94	0.49	0.44	0.69	0.69
1/4	FTP-251BST	1/8-28 BSPT	0.94	0.49	0.44	0.69	0.69
1/4	FTP-252	1/4-18 NPTF	1.15	0.63	0.56	0.84	0.94
1/4	FTP-252BST	1/4-19 BSPT	1.15	0.63	0.56	0.84	0.94
1/4	FTP-253	3/8-18 NPTF	1.19	0.77	0.69	1.00	0.94
3/8	FTP-352	1/4-18 NPTF	1.40	0.63	0.56	1.00	1.09
3/8	FTP-352BST	1/4-19 BSPT	1.40	0.63	0.56	1.00	1.09
3/8	FTP-353	3/8-18 NPTF	1.40	0.77	0.69	1.00	1.13
3/8	FTP-353BST	3/8-19 BSPT	1.40	0.77	0.69	1.00	1.13
3/8	FTP-354	1/2-14 NPTF	1.56	0.98	0.88	1.19	1.25
1/2	FTP-554	1/2-14 NPTF	1.75	0.98	0.88	1.25	1.50
1/2	FTP-556	3/4-14 NPTF	1.75	1.25	1.13	1.50	1.56

Female Pipe Thread



Body Size (inch)	Part Number	Thread Size	Dimensions (inches)		
			D	E	HEX
1/4	FTP-251-F	1/8-27 NPTF	1.00	0.58	0.50
1/4	FTP-251-FBS	1/8-28 BSPT	1.00	0.65	0.56
1/4	FTP-252-F	1/4-18 NPTF	1.20	0.72	0.63
1/4	FTP-252-FBS	1/4-19 BSPT	1.20	0.87	0.75
1/4	FTP-253-F	3/8-18 NPTF	1.25	0.87	0.75
3/8	FTP-352-F	1/4-18 NPTF	1.38	0.72	0.63
3/8	FTP-352-FBS	1/4-19 BSPT	1.28	0.87	0.75
3/8	FTP-353-F	3/8-18 NPTF	1.40	0.87	0.75
3/8	FTP-353-FBS	3/8-19 BSPT	1.40	1.01	0.88
3/8	FTP-354-F	1/2-14 NPTF	1.62	1.08	0.94
1/2	FTP-554-F	1/2-14 NPTF	1.72	1.08	0.94
1/2	FTP-556-F	3/4-14 NPTF	1.78	1.30	1.13



Gas





SERIES Gas-Mate



Gas-Mate couplings are one-way shut-off safety couplings designed for the connection of gas cooking appliances and other gas-fired devices. Body sizes are 3/8", 1/2", 3/4", 1" and 1 1/4".

FEATURES

- Connect and disconnect without using wrenches
- Automatic shut-off when plug is removed from socket
- In case of fire, heat-sensitive plug allows socket valve to close, stopping gas flow
- Push-to-connect (1 1/4" only)



APPLICATIONS & INDUSTRIES

- Industrial
- Fuel Gas Systems



SOCKETS

PLUGS

Body Size	Part No.	Thread Size NPTF	Dimensions		
			A	B	Across Flats
3/8"	100-006	3/8-18	2.44	1.13	1.00
1/2"	100-008	1/2-14	2.84	1.38	1.13
3/4"	100-010	3/4-14	3.17	1.75	1.50
1"	100-012	1-11 1/2	3.94	2.13	1.75



Body Size	Part No.	Thread Size NPTF	Dimensions		
			A	B	HEX
1 1/4"	GMS1250FH	1 1/4-11 1/2	4.15	2.28	2.00



Body Size	Part No.	Thread Size NPTF	Dimensions		
			C	D	HEX
3/8"	100-506	3/8-18	1.59	0.94	0.81
1/2"	100-508	1/2-14	1.94	1.16	1.00
3/4"	100-510	3/4-14	2.06	1.52	1.31
1"	100-512	1-11 1/2	2.47	1.73	1.50

Body Size	Part No.	Thread Size NPTF	Dimensions		
			C	D	HEX
1 1/4"	GMP1250F	1 1/4-11 1/2	2.44	2.16	1.88

Dust Caps and Dust Plugs Accessories:

Body Size	Plug Dust Cap Part No.		Socket Dust Plug Part No.	
	Metal	Vinyl	Metal	Vinyl
3/8"	PDC-2-HK*	P-PDC-2-HK	SDC-2-HK*	P-SDC-2-HK
1/2"	PDC-3-HK*	P-PDC-3-HK	SDC-3-HK*	P-SDC-3-HK
3/4"	PDC-4-HK**	P-PDC-4-HK	SDC-4-HK**	P-SDC-4-HK
1"	PDC-6-HK**	P-PDC-6-HK	SDC-6-HK**	P-SDC-6-HK

*Brass **Aluminum



CANADIAN
STANDARDS
ASSOCIATION*

Complies with the requirements of
ANSI Z21.41 & CSA 6.9.

* CSA design certified, in both the United States and Canada, for natural gas, manufactured gas, liquefied petroleum and LP gas-air mixtures at pressures not in excess of 1/2 psig (3.5 kPa).



SERIES FS Flow Sensor





Series FS Flow Sensors are designed to protect personnel and property in case of hose failure in compliance with Federal Safety Regulations. Flow Sensors are intended for use with compressed air.

FEATURES

- Automatically shuts off air flow to ruptured hose
- Reduces risk of injury or damage from hose whip
- Automatically resets after failure correction
- 250 psig pressure rating (all sizes)
- Low pressure drop
- Operates in any orientation
- Compact design, economical, tamper-resistant

APPLICATIONS & INDUSTRIES

- General Industry
- Pneumatic Tools




Materials

- Brass body
- Acetal valve (1/4" - 1")
- Brass valve (1 1/2")
- Stainless steel valve spring



Rated Pressure



Flow Data - The graph above indicates the minimum inlet pressure for various hose lengths. Each Flow Sensor has a shut-off flow rating dependent upon inlet pressure. The length of hose and fitting size are critical in the proper operation of the valve. For example, with the B8-FS-50F-8 Flow Sensor, the hose I.D. must be 1/2" using only 1/2" pipe thread end fittings. Thirty feet of hose requires at least 20 psig inlet pressure; fifty feet of hose requires at least 28 psig inlet pressure; and seventy-five feet of hose requires at least 36 psig inlet pressure. Inlet pressures lower than those indicated on the curves above will not guarantee protection in case of hose failure. Valve shut-off occurs only when flow exceeds the flow rating for the inlet pressure.

If hose lengths greater than 75 feet are required, a 1/2" size or larger Flow Sensor must be installed on the inlet end of each 75-foot section, and a correspondingly higher inlet pressure must be supplied for proper operation of the Flow Sensor to assure safety.

Body Size	Part Number	Thread Size NPTF	Shut-Off Flow, scfm, at Inlet Pressure, Psig								Dimensions	
			60	80	100	100	140	160	180	200	Length	Hex
1/4"	B4-FS-25F-2	1/4-18	16	18	20	22	23	25	26	27	2.14	0.75
3/8"	B6-FS-37F-5	3/8-18	41	46	50	55	59	63	66	69	2.50	.088
1/2"	B8-FS-50F-8	1/2-14	65	73	80	87	93	99	704	109	3.12	1.06
3/4"	B12-FS-100F-21	3/4-14	105	118	130	141	152	161	169	177	3.68	1.38
1"	B16-FS-100F-21	1-11 1/2	170	191	210	227	245	260	273	286	1.75	1.75
1 1/2"	B24-FS-150F-45	1 1/2-11 1/2	365	410	450	489	525	557	586	615	5.86	2.50

All Flow Sensors have a pressure drop of approximately 2 psid at 80% of shut-off flow.



CHECK OUT OUR DEMONSTRATION VIDEO AT WWW.TUTHILL.COM.



IN-LINE CHECK VALVES




Series RA 4000 in-line check valves are designed to allow flow of fluid in one direction only and limit the line's internal pressure (to the cracking pressure). They are rugged and reliable, offer low pressure drop and have elastomer valve seals for leak-free operation. Available sizes are 1/4" to 2".

FEATURES

- One-piece zinc plated steel body
- High strength steel valve provides excellent reliability under severe operating conditions
- The valve has a captive nitrile (Buna-N) seal, assuring no leakage at low and high pressures
- Low pressure drop versus flow rate
- Cracking pressure: 7 psi (0.5 bar)
- Cracking pressure is non-adjustable
- Contact supplier for availability of alternative cracking pressures

APPLICATIONS & INDUSTRIES

- Agriculture
- Construction
- Hydraulic Tools
- General Industry
- Fluid Transfer
- Oil and Gas



* The cracking pressure corresponds to the full discharge pressure (valve fully open) with a tolerance of ±10%.




1/4" to 2" nominal
(6.35 mm to 50.80 mm)




Rated Pressure

Size (inch)	Part No.	Thread NPTF	Dimensions		Rated Pressure	
			A	Hex	PSI	BAR
1/4	RA 04210 00	1/4-18	1.97	0.75	10,150	700
3/8	RA 04220 00	3/8-18	2.36	0.91	10,150	700
1/2	RA 04230 00	1/2-14	2.76	1.06	7,250	500
3/4	RA 04240 00	3/4-14	3.39	1.38	7,250	500
1	RA 04250 00	1-11½	3.94	1.62	7,250	500
1¼	RA 04260 00	1¼-11½	5.12	2.17	4,350	300
1½	RA 04270 00	1½-11½	5.31	2.56	4,350	300
2	RA 04290 00	2-11½	5.91	2.95	4,350	300



Pressure Drop vs. Flow Rate



FITTINGS FLEX-AIR



Materials

- Integrated steel/polyurethane construction
- Steel balls
- Buna-N (Nitrile) seal
- Thread sealant standard on male NPTs

The Flex-Air Fitting is designed to rotate 360° at up to a 75° angle. The Flex-Air Fitting helps to alleviate Carpal Tunnel Syndrome and other stress related injuries in the workplace.

FEATURES

- Unique design provides free 360° rotation with up to a 75° flex angle in any direction
- Many styles and sizes available
- 145 psig (10 Bar) pressure rating (all models)

BENEFITS

- Provides flexibility of tool position to help alleviate CTS (Carpal Tunnel Syndrome) and back stress resulting in fewer lost-time injuries
- Minimizes paint damage
- Prevents kinking of air supply hose

APPLICATIONS & INDUSTRIES

- General Industry
- Pnuematic Tools



**NEED TO PLACE AN ORDER?
LOCATE A DISTRIBUTOR NEAR YOU
AT WWW.TUTHIL.COM.**





FLEX-AIR FITTINGS

Female to Male



Part Number	FA25F-25M
Inside Dia.	0.2" (5 mm)
Connectors	1/4" NPT Female 1/4" NPT Male



Part Number	FA25F-37M
Inside Dia.	0.3" (7.5 mm)
Connectors	1/4" NPT Female 3/8" NPT Male



Part Number	FA37F-37M
Inside Dia.	0.3" (7.5 mm)
Connectors	3/8" NPT Female 3/8" NPT Male

Hose Barb to Male



Part Number	FA37H-37M
Inside Dia.	0.3" (7.5 mm)
Connectors	3/8" Barb 3/8" NPT Male

Male to Male



Part Number	FA25M-25M
Inside Dia.	0.2" (5 mm)
Connectors	1/4" NPT Male 1/4" NPT Male



Part Number	FA37M-37M
Inside Dia.	0.3" (7.5 mm)
Connectors	3/8" NPT Male 3/8" NPT Male

ARO to Male



Part Number	FA25AR-25M
Inside Dia.	0.2" (5 mm)
Connectors	ARO 210 Interchange 1/4" NPT Male

Industrial Plug to Male



Part Number	FA25P-25M
Inside Dia.	0.2" (5 mm)
Connectors	1/4" Industrial Interchange 1/4" NPT Male



Part Number	FA37P-25M
Inside Dia.	0.3" (7.5 mm)
Connectors	3/8" Industrial Interchange 1/4" NPT Male

RL Plug to Male



Part Number	FA3RL-37M
Inside Dia.	0.3" (7.5 mm)
Connectors	3/8" RL Plug 3/8" NPT Male

Lincoln to Male



Part Number	FA25LI-25M
Inside Dia.	0.2" (5 mm)
Connectors	Lincoln Interchange 1/4" NPT Male

ONE-WAY

TWO-WAY



STRAIGHT-THRU

GAS

ACCESSORIES

FITTINGS

Hose Clamps (Brass) • Compression Type, Reusable

Male Pipe Thread
(MPT)

Female Pipe Thread
(FPT)


1/8-27 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series A	3/16"	7/16"	1A0	—
	3/16"	1/2"	1A3	—
Series B	1/4"	15/32"	1B1	—
	1/4"	1/2"	1B3	—
	1/4"	9/16"	1B5	—
	1/4"	5/8"	1B7	—

1/4-18 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series A	3/16"	7/16"	2A0	—
	3/16"	1/2"	2A3	—
Series B	1/4"	15/32"	2B1	3B1
	1/4"	1/2"	2B3	3B3
	1/4"	9/16"	2B5	3B5
	1/4"	5/8"	2B7	3B7
	1/4"	11/16"	2B9	3B9
Series C	5/16"	9/16"	2C5	—
	5/16"	5/8"	2C7	3C7
	5/16"	11/16"	2C9	—
Series D	3/8"	5/8"	2D7	3D7
	3/8"	11/16"	2D9	3D9
	3/8"	3/4"	2D11	3D11
	3/8"	7/8"	2D15	3D15
Series P	1/2"	13/16"	2P13	—
	1/2"	7/8"	2P15	—
	1/2"	15/16"	2P17	—
	1/2"	1"	2P19	—

3/8-18 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series B	1/4"	15/32"	4B1	—
	1/4"	1/2"	4B3	—
	1/4"	9/16"	4B5	—
	1/4"	5/8"	4B7	—
Series C	5/16"	5/8"	4C7	—
	5/16"	11/16"	4C9	—
Series D	3/8"	5/8"	4D7	5D7
	3/8"	11/16"	4D9	5D9
	3/8"	3/4"	4D11	5D11
	3/8"	7/8"	4D15	5D15
Series P	1/2"	13/16"	4P13	—
	1/2"	7/8"	4P15	—
	1/2"	15/16"	4P17	—
	1/2"	1"	4P19	—

1/2-14 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series P	1/2"	13/16"	6P13	7P13
	1/2"	7/8"	6P15	7P15
	1/2"	15/16"	6P17	7P17
	1/2"	1"	6P19	7P19
Series R	3/4"	1 1/8"	6R23	—
	3/4"	1 1/4"	6R25	—
	3/4"	1 1/2"	6R27	—


3/4-14 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series P	1/2"	13/16"	8P13	—
	1/2"	7/8"	8P15	—
	1/2"	15/16"	8P17	—
	1/2"	1"	8P19	—
Series R	3/4"	1 1/8"	8R23	—
	3/4"	1 1/4"	8R25	—
	3/4"	1 1/2"	8R27	—

1-11 1/2 NPTF				
	Hose		Part No.	
	I.D.	O.D.	MPT	FPT
Series R	3/4"	1 1/8"	10R23	—
	3/4"	1 1/4"	10R25	—
	3/4"	1 1/2"	10R27	—

Swivel Nut Hose Clamps (Brass) • Compression Type, Reusable

With Brass Male Swivel Insert – External Seat (inverted flare) for use with paint spray and oxygen fittings, etc. (Will accept 37° or 45° flare.)


9/16-18 Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series A	3/16"	7/16"	4LA0*
	3/16"	7/16"	4RA0
	3/16"	1/2"	4LA3*
	3/16"	1/2"	4RA3
Series B	1/4"	15/32"	4RB1
	1/4"	1/2"	4LB3*
	1/4"	1/2"	4RB3
	1/4"	9/16"	4LB5*
	1/4"	9/16"	4RB5
Series D	1/4"	5/8"	4RB7
	3/8"	5/8"	4RD7
	3/8"	11/16"	4RD9
	3/8"	3/4"	4RD11



1/4-18 NPSM Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series B	1/4"	15/32"	5RB1
	1/4"	1/2"	5RB3
	1/4"	9/16"	5RB5
	1/4"	5/8"	5RB7
Series C	5/16"	5/8"	5RC7
Series D	3/8"	5/8"	5RD7
	3/8"	11/16"	5RD9
	3/8"	3/4"	5RD11

* Left-hand thread for acetylene service

With Steel Female Swivel Insert, 37° Female Flare, for use with flared tube fittings.



7/16-20 Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series B	1/4"	15/32"	720B1
	1/4"	1/2"	720B3
	1/4"	9/16"	720B5
	1/4"	5/8"	720B7

5/8-18 Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series D	3/8"	5/8"	2FD7
	3/8"	11/16"	2FD9
	3/8"	3/4"	2FD11

9/16-18 Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series D	3/8"	5/8"	4FD7
	3/8"	11/16"	4FD9
	3/8"	3/4"	4FD11
	3/8"	7/8"	4FD11

3/4-16 Straight Thread			
	Hose		Part No.
	I.D.	O.D.	
Series P	1/2"	13/16"	1216P13
	1/2"	7/8"	1216P15

FITTINGS

Hose Stems




Hose Stem-to-Male Pipe Thread			
Hose I.D.	Thread NPTF	Part No.	
		Brass	Stainless
3/16"	1/8-27	SN16	LLS16
1/4"	1/8-27	SN17	—
3/8"	1/8-27	SN18	—
3/16"	1/4-18	S19	—
1/4"	1/4-18	S20	LLS20
5/16"	1/4-18	S205	—
3/8"	1/4-18	S21	—
1/2"	1/4-18	S22	—
1/4"	3/8-18	S23	—
3/8"	3/8-18	S24	LLS24
1/2"	3/8-18	S25	—
1/2"	1/2-14	S26	LLS26
3/4"	3/4-14	—	LLS30
1"	1-11½	—	LLS35

Splicers (Brass)




Hose Stem-to-Hose Stem		
Hose I.D.	Part No.	
3/16"	HS-30	
1/4"	HS-31	
5/16"	HS-32	
3/8"	HS-33	
1/2"	HS-34	




Hose Clamp-to-Hose Clamp		
Hose I.D.	Hose O.D.	Part No.
1/4"	15/32"	HSC-B1
1/4"	1/2"	HSC-B3
1/4"	5/8"	HSC-B7
5/16"	5/8"	HSC-C7
5/16"	11/16"	HSC-C9
3/8"	9/16"	HSC-D5
3/8"	5/8"	HSC-D7
3/8"	11/16"	HSC-D9
3/8"	3/4"	HSC-D11


Unions (Brass)




**Part No.
H25MHU**
1/4" Male Pipe Thread Union half consists of H25HMHU01 body and 902-8 o-ring.




**Part No.
HHU25M**
1/4" Male Pipe Thread Union half




**Part No.
H25HHU**
1/4" Hose Stem Union half consists of H25HHU01 stem, 902-8 o-ring and HUSN1 sleeve



**Part No.
HHU25F**
1/4" Female Pipe Thread Union half




**Part No.
H37HHU**
3/8" Hose Stem Union half consists of H37HHU01 stem, 902-8 o-ring and HUSN1 sleeve




**Part No.
HHU37H**
3/8" Hose Stem Union half

Any union half shown on the left can be used with any union half shown on the right.


Adapters




Oxygen Adapter (Brass)	
Part No.	Thread Size
9-MBR	1/4-18 NPTF x 9/16-18 Right Hand



Pipe-to-Pipe Adapter (Brass)	
Part No.	Thread Size
18-MAM	1/8-27 NPTF x 1/4-18 NPTF
19-MBM	1/4-18 NPTF x 1/4-18 NPTF
20-MBM	1/4-18 NPTF x 3/8-18 NPTF



Flare-to-Pipe Adapter (Stainless)	
Part No.	Thread Size
A-402	7/16-20 (1/4" 45° Flare) x 1/4-18 NPTF



Flare-to-Flare Adapter (Stainless)	
Part No.	Thread Size
A-394	7/16-20 (1/4" 45° Flare) Both Ends
A-375	5/8-18 (3/8" 45° Flare) Both Ends

All stainless steel fittings listed on this page are machined from Type 303 stainless steel bar stock.

SELECTION GUIDE ELASTOMER

Select seals compatible with the service intended for the couplings. Allowance must be made for the kind of fluid to be conveyed and its temperature. Chemically active fluids will destroy some seal materials. Certain seals withstand high temperatures, whereas others cannot. Use this elastomer selection guide to find the appropriate seal. NOTE: Elastomer or seal material listed as “Standard” is furnished in most Tuthill couplings. Elastomers designated as “-118”, “-146”, “-192”, etc., are available as optional seal material for some couplings. Other seal materials available upon request to suit requirements. Consult your local distributor.

NOTE: Service conditions may vary. The following information it is intended as a guide only and is not a guarantee.

Seal Information

Dash No.	Compound
-***	Buna-N – 90 Durometer
-115	PTFE
-118	Neoprene
-143	Fluorocarbon
-146	Buna-N – 70 Durometer
-192*	EPDM
-235†	Kalrez
-236*	EPDM

*** No Dash Number required for standard seal material

* “-192” and “-236” compounds are not compatible with mineral-based greases or oils

† Kalrez seals available by special quotation

FLUID	HANSEN ELASTOMER
Air (to 200° F)	Standard
Air (above 200° F)	-143
Acetone	-192▼
Acetylene	Standard
Alcohol, Ethyl	-192▼
Alcohol, Methyl	Standard
Alkalies	-192▼
Ammonia, Anhydrous	Standard
Ammonium Hydroxide	-192▼
Aroclor	-143
Brake Fluid, Non-Petroleum Based	-192▼
Butane	-146
Carbon Dioxide	Standard
Carbon Tetrachloride	-143
Cellulube	-192▼
Creosote	Standard
Diesel Fuel	-146
Diester Lubricants	-143
Ethane	-146
Ethanol	-192▼
Ethylene Glycol	-192▼
Freon (most varieties)	-118
Gasoline, Aromatic & Non-Aromatic	-143
Glycerin	Standard
Helium	Standard
Heptane	-146
Hexane	-146
Houghto-Safe Series 200, 600, 5000	Standard
Houghto-Safe Series 1000	-192▼
Hydraulic Fluid, Petroleum-based with Aniline Point above 160° F	Standard
Hydrolube	Standard
Jet Fuel (to 250° F)	-146
Jet Fuel (above 250° F)	-143

FLUID	HANSEN ELASTOMER
Kerosene	-146
Lindol	-192▼
L.P. Gases	Standard
Methane	-146
Methanol	Standard
Methyl Ethyl Ketone	-192▼
Methyl Iso-Butyl Ketone	-192▼
MIL-H-5606A	Standard
Mineral Spirits	-146
Natural Gas	Standard
Nitrogen	Standard
Octane	-143
Oils, including: Animal, Mineral with Aniline Point above 160° F and Non-Food Service Vegetable OS45 & OS45-1	Standard
Oxygen	-143
	Service conditions dictate Elastomer Selection
Pentane	-146
Perchloroethylene	-143
Propane	Standard
Propylene	-143
Pydraul	-143
Steam (to 350° F)	-192▼
Steam (above 350° F)	-236▼
Stoddard Solvent	-146
Toluene	-143
Transmission Oil, Automotive	Standard
Trichloroethylene	-143
Turpentine	Standard
Versilube F-50	-192▼
Water (to 180° F)	Standard
Water (above 180° F)	-192▼

▼ “-192” and “-236” compounds are not compatible with mineral-based greases or oils

Alphanumeric Parts Index

Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page
1A0	80	2-HIL-LLRA720	63	3-PD5	15, 19	4-PB11	16, 20	5RD11	80
1A3	80	2-HK	46, 47, 48	3-PD7	15, 19	4-PD5	16, 20	5-SD5	21
1B1	80	2-HKIG	62	3-PD9	15, 19	4-PD7	16, 20	5-SD7	21
1B3	80	2-HKIL	62	3-PD11	15, 19	4-PD9	16, 20	5-SD9	21
1B5	80	2-HRC-K	48	3-PD13	15, 19	4-PD11	16, 20	5-SD11	21
1B7	80	2-K6	47	3-PD15	15, 19	4-PD13	16, 20	5-SD13	21
GD 10556 01	27	2-K6C	47	3-S20	68	4-PD15	16, 20	5-SD15	21
1-H4	47	2-K16	47	3-S20BS	68	4-PP13	16, 20	5-SP13	21
1-H11	47	2-K16BS	47	3-S21	68	4-PP15	16, 20	5-SP15	21
1-HK	46-48	2-K16C	47	3-S21BS	68	4-PP17	16, 20	5-SP17	21
1-HRC-K	48	2-K16C-VB	48	3-S22	68	4-PP19	16, 20	5-SP19	21
1-K4	47	2-KIG-F	63	3-SA0	19	4RA0	80	5-SR23	21
1-K11	47	2-KIG-F15	63	3-SA3	19	4RA3	80	5-SR25	21
1-S10	68	2-KIG-F16	63	3-SB1	19	4RB1	80	5-SR27	21
1-S10BS	68	2-KIG-F20	63	3-SB3	19	4RB3	80	6DBP-75F	64
1-S11	68	2-KIG-F720	63	3-SB5	19	4RB5	80	6DBP-75FBS	64
1-S11BS	68	2-KIL-F	63	3-SB7	19	4RB7	80	6DBS-75F	64
1-S12	68	2-KIL-F15	63	3-SB9	19	4RD7	80	6DBS-75FBS	64
1-S17	68	2-KIL-F16	63	3-SB11	19	4RD9	80	6FFP25	56
1-SA0	15	2-KIL-F20	63	3-SC5	19	4RD11	80	6FFP25BS	56
1-SA3	15	2-KIL-F720	63	3-SC7	19	4-S25	68	6FFP56UN	56
1-SB1	15	2P13	80	3-SC9	19	4-S25BS	68	6FFS25	56
1-SB3	15	2P15	80	3-SD5	19	4-S26	68	6FFS25BS	56
1-SB5	15	2P17	80	3-SD7	19	4-S26BS	68	6FFS56UN	56
1-SB7	15	2P19	80	3-SD9	19	4-S27	68	6HFR26	52
1-SC5	15	2-S15	68	3-SD11	19	4-SB3	20	6-HK	47
1-SC7	15	2-S15BS	68	3-SD13	19	4-SB5	20	6-HKP	46, 48
1-SD5	15	2-S16	68	3-ST	67	4-SB7	20	6-HP12	47
1-SD7	15	2-S16BS	68	3-T20	69	4-SB9	20	6-HP31	47
1-SD9	15	2-S17	68	3-T20BS	69	4-SB11	20	6-HP31BS	47
1-SD11	15	2-ST	67	3-T21	69	4-SC7	20	6-HRC-K	48
1-SD13	15	2-T15	69	3-T21BS	69	4-SD5	20	6-KP12	47
1-ST	67	2-T15BS	69	3-T22	69	4-SD7	20	6-KP31	47
1-T10	69	2-T16	69	4B1	80	4-SD9	20	6-KP31BS	47
1-T11	69	2-T16BS	69	4B3	80	4-SD11	20	6-KP31-VB	48
1-T15	69	2-T17	69	4B5	80	4-SD15	20	6P13	80
2A0	80	3B1	80	4B7	80	4-SP13	20	6P15	80
2A3	80	3B3	80	4C7	80	4-SP15	20	6P17	80
2B1	80	3B5	80	4C9	80	4-SP17	20	6P19	80
2B3	80	3B7	80	4D7	80	4-SP19	20	6R23	80
2B5	80	3B9	80	4D9	80	4-ST	67	6R25	80
2B7	80	3C7	80	4D11	80	4-T25	69	6R27	80
2B9	80	3D7	80	4D15	80	4-T25BS	69	6-S30	68
2C5	80	3D9	80	4DBP-50F	64	4-T26	69	6-S30BS	68
2C7	80	3D11	80	4DBP-50FBS	64	4-T26BS	69	6-S31	68
2C9	80	3D15	80	4DBS-50F	64	4-T27	69	6-S31BS	68
2CC25F	13	3DBP-37F	64	4DBS-50FBS	64	5D7	80	6-S32	68
2CC37F	13	3DBP-37FBS	64	4FD7	80	5D9	80	6-ST	67
2D7	80	3DBS-37F	64	4FD9	80	5D11	80	6-T30	69
2D9	80	3DBS-37FBS	64	4FD11	80	5D15	80	6-T31	69
2D11	80	3-H8	47	4HFR26	52	5HFR31	52	6-T32	69
2D15	80	3-H8C	47	4-HK	47	5-PB1	17, 21	7P13	80
2DBP-25F	64	3-H21	47	4-HKP	46, 48	5-PB3	17, 21	7P15	80
2DBP-25FBS	64	3-H21BS	47	4-HP10	47	5-PB5	17, 21	7P17	80
2DBS-25F	64	3-H21C	47	4-HP26	47	5-PB7	17, 21	7P19	80
2DBS-25FBS	64	3-HK	46-48	4-HP26BS	47	5-PD5	17, 21	8DBP-100F	64
2FD7	80	3-HRC-K	48	4-HRC-K	48	5-PD7	17, 21	8DBP-100FBS	64
2FD9	80	3-K8	47	4KFR26	52	5-PD9	17, 21	8DBS-100F	64
2FD11	80	3-K8C	47	4-KP10	47	5-PD11	17, 21	8DBS-100FBS	64
2-H6	47	3-K21	47	4-KP26	47	5-PD13	17, 21	8HFR26	52
2-H16	47	3-K21BS	47	4-KP26BS	47	5-PD15	17, 21	8-HK	47
2-H16BS	47	3-K21C	47	4-KP26-VB	48	5-PP13	17, 21	8-HKP	46, 48
2-HIG10	63	3-K21C-VB	48	4LA0	80	5-PP15	17, 21	8-HP16	47
2-HIG11	63	3-K21-VB	48	4LA3	80	5-PP17	17, 21	8-HP36	47
2-HIG15	63	3-PA0	15, 19	4LB3	80	5-PP19	17, 21	8-HP36BS	47
2-HIG16	63	3-PA3	15, 19	4LB5	80	5-PR23	17, 21	8-HRC-K	48
2-HIG20	63	3-PB1	15, 19	4P13	80	5-PR25	17, 21	8KFR36	52
2-HIG720	63	3-PB3	15, 19	4P15	80	5-PR27	17, 21	8-KP16	47
2-HIG-LLRA720	63	3-PB5	15, 19	4P17	80	5RB1	80	8-KP36	47
2-HIL10	63	3-PB7	15, 19	4P19	80	5RB3	80	8-KP36BS	47
2-HIL11	63	3-PB9	15, 19	4-PB1	16, 20	5RB5	80	8P13	80
2-HIL15	63	3-PB11	15, 19	4-PB3	16, 20	5RB7	80	8P15	80
2-HIL16	63	3-PC5	15, 19	4-PB5	16, 20	5RC7	80	8P17	80
2-HIL20	63	3-PC7	15, 19	4-PB7	16, 20	5RD7	80	8P19	80
2-HIL720	63	3-PC9	15, 19	4-PB9	16, 20	5RD9	80	8R23	80

Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page
8R25	80	12-H46CBS	50	20-K51BS	50	44	16, 20	406	16, 20
8R27	80	12-HK	49, 50	20-K51C	50	45	16, 20	408	16, 20
8-S35	68	12-K41	50	20-K51CBS	50	50	17, 21	410	16
8-S35BS	68	12-K41BS	50	20-K56	50	50G	17, 21	410-A	16
8-S36	68	12-K41C	50	20-K56BS	50	50-SD7	17	420	16
8-S36BS	68	12-K41CBS	50	20-K56C	50	50-SD13	17	430	16
8-S37	68	12-K46	50	20-K56CBS	50	50-SP13	17	440	16
8-ST	67	12-K46BS	50	20-K61	50	50-SP15	17	450	16
8-T35	69	12-K46C	50	20-K61BS	50	50-SP17	17	500	14, 17
8-T36	69	12-K46CBS	50	20-K61C	50	50-SP19	17	500-A	17
8-T36BS	69	12-S46	68	20-K61CBS	50	50-SR23	17	501	17
8-T37	69	12-S46BS	68	20-MBM	81	50-SR25	17	510	17
9-MBR	81	12-ST	67	20-S56	68	50-SR27	17	520	17
10	15, 19, 25	12-T45	69	20-ST	67	52	17, 21	530	17
10C	15, 19, 25	12-T46	69	20-T56	69	52G	17, 21	540	17
10FFP16FMET	56	13	15, 19, 25	21AP-25F	25	53	17, 21	550	17
10FFP37	56	14	15, 19, 25	21AP-25H	25	53-A	17, 21	570	17
10FFP37BS	56	14G	15, 19, 25	21AP-25M	25	53G	17, 21	580	17
10FFP50	56	15	15, 19, 25	21AP-37F	25	54	17, 21	585	17, 21
10FFP50BS	56	15G	15, 19, 25	21AP-37H	25	54G	17, 21	585G	17, 21
10FFP56ORM	56	16	15, 19, 25	21AP-37M	25	55	17, 21	590	17
10FFP56UN	56	16FFP50	57	Auto-Flo 23	24, 25	55G	17, 21	720B1	80
10FFP75ORM	56	16FFP50BS	57	Auto-Flo 24	24, 26	56	17, 21	720B3	80
10FFP75UN	56	16FFP75	57	24AP-25FBS	26	56G	17, 21	720B5	80
10FFP87UN	56	16FFP75BS	57	24AP-25FG	26	57	17, 21	720B7	80
10FFS16FMET	56	16FFP75UN	57	24AP-25H	26	59	17, 21	800	15
10FFS37	56	16FFP87UN	57	24AP-25MBST	26	59G	17, 21	900	15
10FFS37BS	56	16FFP106UN	57	24AP-25MG	26	60	17, 21	1000	14, 15
10FFS50	56	16FFS50	57	24AP-31H	26	60G	21	1000-63	15
10FFS50BS	56	16FFS50BS	57	24AP-37FBS	26	61	17, 21	1100	15
10FFS56ORM	56	16FFS75	57	24AP-37H	26	61G	17, 21	1200	15
10FFS56UN	56	16FFS75BS	57	24AP-37MBST	26	64A	22	1216P13	80
10FFS75ORM	56	16FFS75UN	57	24AP-50FBS	26	64GA	22	1216P15	80
10FFS75UN	56	16FFS87UN	57	24AP-50H	26	65A	22	1300	15
10FFS87UN	56	16FFS106UN	57	24AP-50MBST	26	65GA	22	1600	15
10G	15, 19, 25	16G	15, 19, 25	24CC25F	13	66A	22	1600P	15
10-H41	50	16P	15, 19, 25	24CC25FBS	13	66GA	22	1700	15
10-H41BS	50	16PG	15, 19, 25	24CC37F	13	67A	22	1700P	15
10-HK	49, 50	16-S51	68	25FFP100	57	67GA	22	1800	15
10-K41	50	16-S51BS	68	25FFP100BS	57	67, GD 10556	27	2607	25
10-K41BS	50	16-ST	67	25FFP125	57	68A	22	2608	25
10R23	80	16-T50	69	25FFP125BS	57	69A	22	2608B	25
10R25	80	16-T51	69	25FFP162UN	57	70A	22	2609	25
10R27	80	17	15, 19, 25	25FFS100	57	70GA	22	2609B	25
10-S41	68	17G	15, 19, 25	25FFS100BS	57	71A	22	2800	19
10-S41BS	68	17P	15, 19, 25	25FFS125	57	71GA	22	2900	19
10-ST	67	17PG	15, 19, 25	25FFS125BS	57	72A	22	3000	18, 19
10-T40	69	18	15, 19, 25	25FFS162UN	57	83, GD 10526	27	3000-43	19
10-T41	69	18-MAM	81	28S-12F	29	83, GD 10536	27	3000-63	19
11	15, 19, 25	19FFP75	57	28S-25M	29	96	58	3100	19
11B	15, 19, 25	19FFP75BS	57	31AP-25F	16	96-P31	58	3200	19
11G	15, 19, 25	19FFP100	57	31AP-25M	16	96-P36	58	3300	19
12	15, 19, 25	19FFP100BS	57	31AP-37F	16	96-P41	58	3600	19
12FFP50	56	19FFP106UN	57	31AP-37M	16	96-S31	58	3600P	19
12FFP50BS	56	19FFP131UN	57	38	16, 20	96-S36	58	3700	19
12FFP75	56	19FFS75	57	40	16, 20	96-S41	58	3700P	19
12FFP75BS	56	19FFS75BS	57	40G	16, 20	100	30	3800	19
12FFP75UN	56	19FFS100	57	40-SB3	16	100-006	74	3946	25
12FFP87UN	56	19FFS100BS	57	40-SB7	16	100-008	74	3947	25
12FFP106UN	56	19FFS106UN	57	40-SD7	16	100-010	74	4000	18, 20
12FFS50	56	19FFS131UN	57	40-SD9	16	100-012	74	4000-A	20
12FFS50BS	56	19-MBM	81	40-SD11	16	100-506	74	4000, RA	77
12FFS75	56	20AP-37F	25	40-SD13	16	100-508	74	4004	16
12FFS75BS	56	20AP-37M	25	40-SP13	16	100-510	74	4006	16
12FFS75UN	56	20-H51	50	40-SP15	16	100-512	74	4008	16
12FFS87UN	56	20-H51BS	50	40-SP17	16	180	28, 29	4050	16
12FFS106UN	56	20-H51C	50	40-SP19	16	183	29	4100	20
12G	15, 19, 25	20-H56	50	41	16, 20	185	29	4100-A	20
12-H41	50	20-H56BS	50	41G	16, 20	186	29	4200	20
12-H41BS	50	20-H56C	50	41, GD 10526	27	187	29	4300	20
12-H41C	50	20-H61	50	41, GD 10536	27	189	29	4400	20
12-H41CBS	50	20-H61BS	50	42	16, 20	280	28	4500	20
12-H46	50	20-H61C	50	42G	16, 20	400	14, 16	5000	18, 21
12-H46BS	50	20-HK	49, 50	43	16, 20	400-A	16	5000-A	21
12-H46C	50	20-K51	50	43G	16, 20	404	16, 20	5100	21

Tuthill Coupling Group	HANSEN™ QUICK SEAL® COUPLEURS GROMELLE™	North America	EMEA	Asia Pacific	China	Latin America	www.tuthill.com	85
		+1 440 826 1115	+33 450 84 11 22	+61 3 9839 7800	+86 21 5385 3369	+1 305 740 3381		

Part Number	Page	Part Number	Page	Part Number	Page	Part Number	Page		
LL2-K6	47	LL10-H41BS	50	P		SDC-2-HK	47, 74		
LL2-K16	47	LL10-K41	50		P2-HK	46, 48	SDC-3-HK	47, 74	
LL2-K16BS	47	LL10-K41BS	50		P2-ST	70	SDC-4-HK	47, 74	
LL2-S15	68	LL10-S41	68		P2-STP-25M	70	SDC6FF	57	
LL2-S15BS	68	LL10-T40	69		P2-STP-25H	70	SDC-6-HK	47, 74	
LL2-S16	68	LL10-T41	69		P3-ST	70	SDC-8-HK	47	
LL2-S16BS	68	LL-11	15, 19, 25		P3-STP-25M	70	SDC10FF	57	
LL2-S17	68	LL12-H41	50		P3-STP-37H	70	SDC12FF	57	
LL2-T15	69	LL12-H41BS	50		P3-STP-37M	70	SDC-12-HK	50	
LL2-T15BS	69	LL12-H46	50		P3-STP-37H	70	SDC16FF	57	
LL2-T16	69	LL12-H46BS	50		P4-30P-25M	23	SDC19FF	57	
LL2-T16BS	69	LL12-K41	50		P4-30S-25H	23	SDC-20-HK	50	
LL2-T17	69	LL12-K41BS	50		P7-40P-37M	23	SDC25FF	57	
LL3-H8	47	LL12-K46	50		P7-40S-37H	23	SDC-96-075	58	
LL3-H21	47	LL12-K46BS	50		P-30	23	SDC-96-100	58	
LL3-H21BS	47	LL12-S46	68		P-40	23	SDC-96-125	58	
LL3-K8	47	LL12-S46BS	68		PDC-1-HK	47	SDC-3000	22	
LL3-K21	47	LL12-T46	69		PDC-2-HK	47, 74	SN16	81	
LL3-K21BS	47	LL16-S51	68		PDC-3-HK	47, 74	SN17	81	
LL3-S20	68	LL16-S51BS	68		PDC-4-HK	47, 74	SN18	81	
LL3-S20BS	68	LL16-T50	69		PDC6FF	57	ST	67	
LL3-S21	68	LL16-T50BS	69	U	PDC-6-HK	47, 74			
LL3-S21BS	68	LL20-H51	50		PDC-8-HK	47			
LL3-S22	68	LL20-H51BS	50		PDC10FF	57	UP10	59, 60	
LL3-T20	69	LL20-H56	50		PDC12FF	57	UP10P-25F	60	
LL3-T20BS	69	LL20-H56BS	50		PDC-12-HK	50	UP10P-25M	60	
LL3-T21	69	LL20-H61	50		PDC16FF	57	UP10P-37F	60	
LL3-T21BS	69	LL20-H61BS	50		PDC19FF	57	UP10P-37M	60	
LL3-T22	69	LL20-K51	50		PDC-20-HK	50	UP10S-25F	60	
LL4-HP10	47	LL20-K51BS	50		PDC25FF	57	UP10S-25M	60	
LL4-HP26	47	LL20-K56	50		PDC-96-075	58	UP10S-37F	60	
LL4-HP26BS	47	LL20-K56BS	50		PDC-96-100	58	UP10S-37M	60	
LL4-KP10	47	LL20-K61	50	PDC-96-125	58	W			
LL4-KP26	47	LL20-K61BS	50	PDC-3000	22		WA 56114 00	61	
LL4-KP26BS	47	LL-1000	15	PP2-H25F	48		WA 56117 00	61	
LL4-S25	68	LL-1100	15	PP2-K25F	48		WA 56124 00	61	
LL4-S25BS	68	L1S16	81	P-PDC-1-HK	47		WA 56127 00	61	
LL4-S26	68	L1S20	81	P-PDC-2-HK	22, 47, 60,		WA 56514 00	61	
LL4-S26BS	68	L1S24	81		63, 74		WA 56517 00	61	
LL4-S27	68	L1S26	81	P-PDC-3-HK	22, 47, 74		WA 56524 00	61	
LL4-T25	69	L1S30	81	P-PDC-4-HK	47, 74		WA 56527 00	61	
LL4-T25BS	69	L1S35	81	P-PDC-6-HK	47, 69, 74				
LL4-T26	69	LNFT-200	72	P-PDC-8-HK	47, 69				
LL4-T26BS	69	LNFT-300	72	P-SDC-1-HK	16, 22, 47, 69				
LL4-T27	69	LNFT-500	72	P-SDC-2-HK	16, 22, 47,				
LL6-HP12	47				60, 69, 74				
LL6-HP31	47	M		P-SDC-3-HK	16, 47, 74				
LL6-HP31BS	47		ML1-H11	47	P-SDC-4-HK	47, 69, 74			
LL6-KP12	47		ML1-K11	47	P-SDC-6-HK	47, 74			
LL6-KP31	47		ML2-H16	47	P-SDC-8-HK	47			
LL6-KP31BS	47		ML2-H16BS	47					
LL6-S30	68		ML2-K16	47	R	RA 04210 00	77		
LL6-S31	68		ML2-K16BS	47		RA 04220 00	77		
LL6-S31BS	68		ML3-H21	47		RA 04230 00	77		
LL6-S32	68		ML3-H21BS	47		RA 04240 00	77		
LL6-T30	69		ML3-K21	47		RA 04250 00	77		
LL6-T30BS	69		ML3-K21BS	47		RA 04260 00	77		
LL6-T31	69	ML4-HP26	47	RA 04270 00		77			
LL6-T31BS	69	ML4-HP26BS	47	RA 04290 00		77			
LL6-T32	69	ML4-KP26	47						
LL8-HP16	47	ML4-KP26BS	47						
LL8-HP36	47	ML6-HP31	47	S		S19	81		
LL8-HP36BS	47	ML6-HP31BS	47		S20	81			
LL8-KP16	47	ML6-KP31	47		S21	81			
LL8-KP36	47	ML6-KP31BS	47		S22	81			
LL8-KP36BS	47	ML8HFR36	52		S23	81			
LL8-S36	68	ML8-HP36	47		S24	81			
LL8-S36BS	68	ML8-HP36BS	47		S25	81			
LL8-S37	68	ML8KFR36	52		S26	81			
LL8-T35	69	ML8-KP36	47		S205	81			
LL8-T36	69	ML8-KP36BS	47		SAFELINE	27			
LL8-T36BS	69	MLHFR36	52		SDC-1-HK	47			
LL-10	15, 19, 25								
LL10-H41	50								

TECHNICAL & WARRANTY INFORMATION

WARNING

About Industry Interchanges...It is possible to connect two different manufacturers' parts together so that they will effect a seal and work properly in a fluid system. Tuthill Coupling Group cannot guarantee the quality, workmanship, dimensions, or tolerances of the other manufacturers' parts, even though they might be interchangeable. Therefore, whenever mixing parts, the final assembly must always be tested before being put into service. Failure to test could result in a sudden failure of the coupling causing severe personal injury or death.

Pressure Ratings**

Since application conditions vary so widely, the pressures listed are intended as a guide only and not a guarantee of performance. Pressure peaks and extreme surge flows may cause a coupling to become inoperative.

****NOTE!**

Pressure ratings listed were determined by testing threaded sockets and plugs. Sockets and plugs with hose stem and hose clamp end connections are designed and recommended for use with shop air line pressure only (150 psig maximum) when used with the appropriate style hose.

WARNING

Over-pressurization could result in a sudden failure of the coupling causing severe bodily injury or death. Be sure to select the proper coupling for your application and use it only within the specified service pressure range.

WARNING

Couplings do wear out. In order to avoid severe bodily injury or death, couplings must be routinely checked for condition and replaced if necessary.

Warranty

Every effort has been made to have all photographs and drawings accurately represent the products as they actually were at the time this catalog was printed. However, in order to effectively continue to meet the requirements of our users, changes in some items may have been made during the life of this catalog—which may be made without notice.

All Tuthill Coupling Group products are guaranteed to be free of defects in material and workmanship for a period of 90 days from the date of shipment to a customer. Any claimed defect must be reported to the Tuthill Coupling Group in writing within the warranty period. This warranty is limited to replacing or repairing, at the Company's option, f.o.b. the Company's factory, any part which upon Company inspection is found to be defective. Components purchased by the Company from others are warranted only to the extent of the guarantee or warranty, if any, made to the Company.

THE ABOVE WARRANTY COMPRISES THE COMPANY'S SOLE AND ENTIRE WARRANTY OBLIGATION AND LIABILITY IN CONNECTION WITH TUTHILL COUPLING GROUP HANSEN COUPLINGS. ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. THE COMPANY IN NO EVENT SHALL BE LIABLE FOR INDIRECT OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE SALE OR USE OF HANSEN COUPLINGS.

Tuthill Coupling Group / **HANSEN™
QUICK SEAL®
COUPLEURS GROMELLE™**

www.tuthill.com

NORTH AMERICA
1000 West Bagley Road
Berea, Ohio 44017-0805
USA
440.826.1115 - Phone
440.826.1105 - Fax
hansencoupling@tuthill.com

EUROPE
7 Rue des Biches
Ville-la-Grand BP 325
Annemasse Cedex, 74112 France
334.5084.1122 - Phone
334.5084.1123 - Fax
coupleursgromelle@tuthill.com



Our quick couplings are available in over 6,000 configurations. They are available in brass, steel, stainless steel, plastic, and in a wide range of sizes. We provide quick couplings to meet the needs of every industry.

Tuthill Coupling Group, comprised of the Hansen™, Coupleurs Gromelle™ and QUICK SEAL® brands, manufactures a comprehensive range of quick coupling and quick testing solutions at its Berea, Ohio and Annemasse, France locations. Tuthill's precision products are widely marketed through a strong network of global distributorships.



ONE-WAY



TWO-WAY



STRAIGHT THROUGH



GAS



ACCESSORIES

QUICK CONNECT COUPLINGS Full Line Catalog

Berea, OH (NORTH AMERICA) • Annemasse, France (EUROPE/MIDDLE EAST/AFRICA) • Kilsyth, Australia (ASIA PACIFIC) • Shanghai, China (CHINA) • Coral Gables, FL (LATIN AMERICA)

Tuthill Coupling Group / **HANSEN™**
QUICK SEAL®
COUPLEURS GROMELLE™

1000 West Bagley Road, P.O. Box 805
Berea, Ohio USA 44017-0805
Tel 440 826-1115 Fax 440 826-0115
hansencoupling@tuthill.com
www.tuthill.com



+1 440 826 1115
+33 450 84 11 22
+61 3 9839 7800
+86 21 5385 3369
+1 305 740 3381



ISO 9001